

















Vulkem[®] **116**

Standard Colors

Colors shown are approximate and may not reflect the shade precisely. Different lighting conditions can influence color appearance, for truer color please view in daylight. Colors are not stocked in all available package types. Minimum order quantities will apply for custom colors and alternative packaging. For more information, please contact Tremco Customer Service.

	ANODIZED ALUMINUM
	IVORY
	ALMOND
	STONE
	LIMESTONE
	GRAY
	NATURAL CLAY
	BUFF
	ALUMINUM
	ALUMINUM STONE
	BEIGE
	REDWOOD TAN
	BRONZE
	DARK BRONZE
	BLACK
	WHITE

TREMCO®

Vulkem® 116

Vulkem® 116

Textured, Single-Component, Polyurethane Sealant

Vulkem® 116 is a multi-purpose, single-component, moisture-curing, gun grade, Polyurethane Sealant.

Applicable Standards

ASTM C 920 Type S, Grade NS, Class 25, Use T, NT, M, A, I class II, and O; CAN/CGSB-19.13-M87;

MCG-2-25-B-N; U.S. Federal Specification TT-S-00230C, Class A, Type II;

City of Los Angeles (COLA) approved standards; Meets AAMA 808.3-10.

Tremco Commercial Sealants & Waterproofing

3735 Green Road, Beachwood, OH 44122 // Phone: 216.292.5000 // 800.321.7906

220 Wicksteed Avenue, Toronto, ON M4H 1G7 // Phone: 416.421.3300 // 800.363.3213

1451 Jacobson Avenue, Ashland, OH 44805 // Phone: 419.289.2050 // 800.321.6457

1117N116SD