



TECHNICAL DATA SHEET

ACOUSTICAL/ CURTAINWALL SEALANT

One-Part, Non-Skinning, Sound
Dampening Sealant

PRODUCT DESCRIPTION

Tremco® Acoustical/Curtainwall Sealant is a single-component, non-skinning, non-hardening synthetic rubber sealant intended for use in sound dampening systems.

BASIC USES

Tremco Acoustical/Curtainwall Sealant was developed for acoustical sealing of the following:

- Drywall partitions
- Curtainwalls
- Corridors
- Party walls

FEATURES & BENEFITS

The application of Tremco Acoustical/Curtainwall Sealant greatly increases the Sound Transmission Class (STC value) of a system and reduces the decibel level when one or more beads are applied to a joint.

Tremco Acoustical/Curtainwall Sealant does not cure or dry by design. It is a non-skinning, non-hardening formula that will remain viscous and tacky to further aid in decreasing sound transmission.

AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 10.1 oz (300 mL) cartridges, 1 qt (850 mL) cartridges, and 5 gal (19 L) pails.

COLORS

Available in Dark Gray.

LIMITATIONS

Do not apply to damp or contaminated surfaces. Use with adequate ventilation.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

| PROPERTY | TEST METHOD | TYPICAL RESULTS |
|-----------------------------------|--------------------|-------------------------|
| Resistance to Sag | CGSB 7.1 | Passes |
| Extrusion Rate | CGSB 3.1 | Passes |
| Viscosity | CGSB Brookfield | 1,000,000 cps |
| Loss of Mass | CGSB 5.1 | Passes |
| Resistance to Staining & Bleeding | CGSB 9.2 | Passes |
| Low Temperature Flexibility | CGSB 11.1 | Passes, -10 °C |
| Cracking/Blistering | CGSB 19.2 | Passes |
| Shear Modulus | Using GR component | 45,000 N/m ² |
| Density | | 1,720 kb/m ³ |

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

ACSTCL-DS/0723

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com