



# TECHNICAL DATA SHEET

TREMprime®  
WB PRIMER  
A Quick-Drying Water  
Based Asphaltic Primer

---

## COMPOSTION

TREMprime® WB is a water based polymer modified asphalt primer formulated from refined select asphalt, special adhesion, promoters and synthetic polymers which conditions a variety of roofing substrates prior to the application of Tremco Roofing Systems and coatings. TREMprime WB is asbestos free, easy to use, and is low in volatile organic compounds to meet the requirements of the National Architectural Coatings regulation.

---

## BASIC USES

TREMprime WB promotes adhesion between new and weathered surfaces and Tremco Roofing Systems and coatings.

---

## LIMITATIONS

- Not intended to be used as a final coating.
- Do not apply when rain appears imminent.
- Do not apply below 45°F (7°C).
- Do not freeze container.
- Store indoors in a heated area.
- Surfaces primed with TREMprime WB must be reprimed if open for more than 24 hours.

---

## FEATURES AND BENEFITS

Non-fibrated - Allows maximum penetration of dried felts and porous substrates.

Adhesion promoters - Conditions asphalts and felts to provide highly receptive surface for protection treatments.

Quick drying formula – Minimizes wait for curing.

Readily workable consistency – Easily brushes into rougher substrates providing more uniform surfaces and can be used on metal work and other surfaces.

Water based – Environmentally cleaner and meets VOC standards.

---

## GRADE

Brush/roll/spray.

---

## RECOMMENED SPRAY EQUIPMENT

Minimum 11:1 ratio pump with 0.015" to 0.021" spray tip.

---

## PACKAGING

TREMprime WB is available in 1 gallon (3.78L), 5 gallon (19L) containers and 53 gallon (200L) plastic lined drums.

---

## APPLICATION

Remove all loose dust, dirt, rotted felt, and foreign matter. Surface must be clean and dry. When spraying TREMprime WB take necessary precautions to prevent overspray.

---

## COVERAGE

Coverage will vary depending upon actual surface and application conditions. Approximately 200-400 sq ft/gal (4.9-9.8 m<sup>2</sup>/L).

---

## CLEAN UP

Promptly clean tools and equipment with soap and water. Dried primer can be cleaned with mineral spirits.

---

## PRECAUTIONS

Use TREMprime WB with adequate ventilation. Users must read container labels and Material Safety Data Sheets for health and safety precautions prior to use.

---

## AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco distributor, or warehouse.

---

## MAINTENANCE

Your local Tremco Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

---

## WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

**NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.**

TPWB-DS/0323

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



[tremcosealants.com](http://tremcosealants.com) | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)