

### Product Description

TREMstop® MCR is a metal restricting collar for use with TREMstop SuperStrip to fabricate a firestop device in the field to fit a hub or uncommon pipe size.

### Basic Uses

TREMstop MCR is used to direct the intumescent action of the TREMstop SuperStrip inward to close off any gaps or voids left when a combustible penetration burns away during a fire.

### Features and Benefits

- TREMstop MCR is zinc-coated to reduce sharp edges and is made of 28-gauge steel, permitting easy manipulation.

### Availability

Immediately available from your local Tremco Field Representative, Tremco Distributor or Tremco Warehouse.

### Packaging

1.4" x 25' (3.6 cm x 7.6 m)

2.4" x 50' (6.1 cm x 15.2 m)

### Limitations

- Not recommended for use with passive fire containment systems not listed or approved by Tremco.

### Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase price of the quantity of Tremco Products proven to be defective and Tremco shall not be liable for any loss or damage.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

0316/TSMCRDS-ST

#### Tremco Commercial Sealants & Waterproofing

3735 Green Rd  
Beachwood OH 44122  
216.292.5000 / 800.321.7906

1451 Jacobson Ave  
Ashland OH 44805  
419.289.2050 / 800.321.6357

220 Wicksteed Ave  
Toronto ON M4H1G7  
416.421.3300 / 800.363.3213

1445 Rue de Coulomb  
Boucherville QC J4B 7L8  
514.521.9555