



Tremco Commercial Sealants & Waterproofing
3735 Green Road
Beachwood, OH 44122
US: 800.852.9068
Canada: 800.363.3213
www.tremcosealants.com



September 30, 2020

To Whom It May Concern:

RE: TREMproof 250GC LV—Green Building Product Information (LEED v4.1 Information)

Tremco Incorporated is an organization that is committed to quality, our employees, and our environment. We are responsive to both internal and external customers, and we pledge to treat everyone with good stewardship and respect.

Tremco Incorporated certifies the following for TREMproof 250GC LV:

Building Product Disclosure and Optimization:

TREMproof 250GC LV is manufactured in Cleveland, Ohio.

No single extracted material is used to produce the majority of this product.

Recycled content for TREMproof 250GC LV is not available, and for the purposes of LEED reporting should be assumed to be zero.

Low Emitting Materials - VOC Content Information:

TREMproof 250GC LV is an exterior applied waterproofer with a VOC content of R=100g/L, and SL=98g/lg/L equaling 8% as applied/mixed. As such, VOC levels are lower than the limits set by SCAQMD rule 1113.

For LEED v4.1 credit, this level meets California Air Resources Board (CARB) 2007 Suggested Control Measure (SCM) for Architectural Coatings.

Green Chemistry:

Tremco Incorporated is dedicated to the environment and prides itself on making its products as sustainable as possible.



Tremco Commercial Sealants & Waterproofing
3735 Green Road
Beachwood, OH 44122
US: 800.852.9068
Canada: 800.363.3213
www.tremcosealants.com

Manufacture Inventory (reported to 1000ppm):

Chemical Name or Role	CAS number	Amount	GHS Hazard
Aromatic process oil	64741-62-4		
Polyurethane Prepolymer		20-60%	Non-Hazardous
Calcium Carbonate (Limestone)	1317-65-3		
Plasticizer		<15%	Non-Hazardous
Polyvinyl chloride	9002-86-2		
Solvent		<5%	Non-Hazardous
Petroleum distillates	64742-47-8		
Calcium oxide	1305-78-8		
Carbon Black	1333-86-4		
Xylene	1330-20-7		
Isophorone Diisocyanate	4098-71-9		
Catalyst		<1%	Non-Hazardous
Ethylbenzene	100-41-4		
Hydrotreated heavy naphthenic distillate	64742-52-5		
Adhesion Promotor		<1%	Non-Hazardous

Additional Information:

Should you have any questions or require additional information, please do not hesitate to contact Technical Services or your local Tremco Field Representative.

Sincerely,

Joe Kravetz

Product Steward

Compliance and Regulatory Affairs