



**TREMFLEX 834
SILICONIZED ACRYLIC LATEX SEALANT**

Tremflex 834 is a pure acrylic latex sealant.

Viscosity: 150,000 to 200,000 cps @ 75F
 Packaging: Cartridges and 5 gallon pails.
 Rheology: Thixotropic

Pumping System is based on the maximum viscosity (200,000cps) using a ½” diameter hose, 25’ in length, manual gun w/swivel, ¼” bead size and flow rates of 1 to 2 pounds per minute.

GRACO EQUIPMENT RECOMMENDATION:

DESCRIPTION	PART#	COMMENTS
Gun: Ultra-Lite 6000 Manual Gun	235628	*Automatic applications need to be reviewed.
Swivel: Straight Style ½” m x ½” f	207947	
Fittings: Misc.		*Application Specific *Application driven

**Pump Selection:
Ram Included-
5- Gallon:**

34:1 Power Ratio	231112
55:1 Power Ratio	231115

55-Gallon:

34:1 Power Ratio	223818
55;1 Power Ratio	223819

Hose:

25´ x ½” ID	947089
-------------	--------

Moisture-Lok

**Installation/Start Up
& Training**

TBD by customer requirements.

Attention: For additional system information please contact:

- Graco Tech Assistance 800-543-0339 • www.graco.com
- Local Authorized Graco SAE Distributor.
- Steve Buerkle Graco AM 513-260-1235
- Bob Degenkolb Graco SS 734-516-0162