



**GENERAL PURPOSE  
BUTYL RUBBER SEALANT**

Butyl Rubber is formulated from a blend of butyl rubber and polyisobutylene.

Viscosity: 200,000 cps @ 75F

Packaging: Cartridges, 5's and 55 gallon containers.

Rheology: Usually non-lubristic

Pumping System is based on the maximum viscosity (200,000cps) using a 1/2" diameter hose, 25' in length, manual gun w/swivel, 1/4" bead size and approximate flow rates of 1/2 to 2 pounds per minute.

**GRACO EQUIPMENT RECOMMENDATION:**

<b>DESCRIPTION</b>	<b>PART#</b>	<b>COMMENTS</b>
<b>Gun:</b> Ultra-Lite 6000	235628	
<b>Swivel:</b> Straight Style 1/2" npt x 1/2"npt	207947	
<b>Fittings:</b> Misc.	*Application Specific	*Application driven
<b>Pump Selection:</b> <b>Ram Included-</b> <b>5- Gallon</b> 55:1 Power Ratio	231115	
<b>55-Gallon</b> 55:1 Power Ratio	223819	
<b>Hose:</b> 25' x 1/2" ID Moisture-Lok	947089	
<b>Installation/Start Up &amp; Training</b>	TBD by customer requirements.	

**Attention:** For additional system information please contact:

- Graco Tech Assistance 800-543-0339 • [www.graco.com](http://www.graco.com)
- Local Authorized Graco SAE Distributor.
- Steve Buerkle Graco AM 513-260-1235
- Bob Degenkolb Graco SS 734-516-0162