



GLAZING SOLUTIONS GROUP

**CURTAINWALL SEALANT**

Curtainwall sealant is a Synthetic Rubber. A non-drying, non-skinning sealant.

Viscosity: 200,000 cps @ 75F

Packaging: Cartridges, 5's and 55 gallon containers.

Rheology: Thixotropic

Pumping System is based on the maximum viscosity (200,000cps) using a 1/2" diameter hose, 25' in length, manual gun w/swivel, 1/4" bead size and flow rates of 1 to 2 pounds per minute.

**GRACO EQUIPMENT RECOMMENDATION:**

<b>DESCRIPTION</b>	<b>PART#</b>	<b>COMMENTS</b>
<b>Gun:</b> Ultra-Lite 6000 Manual Gun	235628	*Automatic applications need to be reviewed.
<b>Swivel:</b> Straight Style 1/2" m X 1/2" f	207947	
<b>Fittings:</b> Misc. (*	Application Specific	*Application driven

**Pump Selection:**

**Ram Included-**

**5- Gallon:**

34:1 Power Ratio 231112

55:1 Power Ratio 231115

**55-Gallon:**

34:1 Power Ratio 223818

55:1 Power Ratio 223819

**Hose:**

25' x 1/2" ID 947089

Moisture-Lok

**Installation/Start Up  
& Training**

TBD by customer requirements.

**Attention:** For additional system information please contact:

- Graco Tech Assistance 800-543-0339 • [www.graco.com](http://www.graco.com)
- Local Authorized Graco SAE Distributor.
- Steve Buerkle Graco AM 513-260-1235
- Bob Degenkolb Graco SS 734-516-0162