



**PROGLAZE SSG
STRUCTURAL GLAZING SILICONE SEALANT**

Proglaze SSG is a one-part, high modulus, neutral cure Silicone Sealant.

Viscosity: 150,000 to 200,000 cps @ 75F

Color: Black

Rheology: Thixotropic

Pumping System is based on the maximum viscosity (200,000cps) using a ½” diameter hose, 25’ in length, manual gun w/swivel, ¼” bead size and flow rates of 1 to 2 pounds per minute.

GRACO EQUIPMENT RECOMMENDATION:

DESCRIPTION	PART#	COMMENTS
Gun: Ultra-Lite 6000 Manual Gun	235628	*Automatic Applications need to be reviewed.
Swivel: Straight Style ½” m X ½” f	207947	
Fittings: Misc.	*Application Specific	*Application driven
Pump Selection:		
Ram Included-		
5- Gallon:		
34:1 Power Ratio	231112	
55:1 Power Ratio	231115	
55-Gallon:		
34:1 Power Ratio	223818	
55:1 Power Ratio	223819	
Hose:		
25’ x ½” ID Moisture-Lok	947089	
Installation/Start Up & Training	TBD by customer requirements.	

Attention: For additional system information please contact:

- Graco Tech Assistance 800-543-0339 • www.graco.com
- Local Authorized Graco SAE Distributor.
- Steve Buerkle Graco AM 513-260-1235
- Bob Degenkolb Graco SS 734-516-0162