



SPECTREM 2
High performance Silicone Sealant

Spectrem 2 is a medium-modulus, one part, high-performance, neutral-cure silicone sealant.

Viscosity: 150,000 to 200,000 cps at 75F

Colors: Various colors available

Rheology: Thixotropic

Pumping system is based on the maximum viscosity of (200,000 cps) using a ½” diameter Moisture-Lok hose 25’ in length, manual gun w/swivel, ¼” bead size with flow rates of 1 to 2 pounds per minute.

GRACO EQUIPMENT RECOMMENDATIONS:

DESCRIPTION	PART#	COMMENTS
Gun: Ultra-Lite 6000 Manual Gun	235628	*Automatic applications need to be reviewed.
Swivel: Straight Style ½” M x ½”F	207947	
Fittings: Misc. (Application Specific)		*Application Driven
Pump Selection: Ram included- 5-Gallon		
34:1 Power Ratio	231112	
55:1 Power Ratio	231115	
55-Gallon		
34:1 Power Ratio	223818	
55:1 Power Ratio	223819	
Hose: 25’x ½” ID Moisture-Lok	947089	
Installation/Start Up & Training		*To be determined by customer requirements

Attention: For additional system information please contact:

- Graco Tech Assistance 800-543-0339 • www.graco.com
- Local Authorized Graco SAE Distributor
- Steve Buerkle Graco AM 513-260-1235
- Bob Degenkolb Graco SS 734-516-0162