



**SPECTREM 3
NON-STAINING, LONG TOOLING TIME,
LOW-MODULUS SILICONE SEALANT**

Spectrem 3 is a general purpose, low modulus, high performance, 1part, neutral cure, non-staining, construction grade silicone sealant.

Viscosity: 150,000 to 200,000 cps at 75F

Color: Various colors available.

Rheology: Thixotropic

Pumping system is based on the maximum viscosity of (200,000 cps) using a ½” diameter Moisture-Lok hose 25’ in length, manual gun w/swivel, ¼” bead size with flow rates of 1 to 2 pounds per minute.

GRACO EQUIPMENT RECOMMENDATION:

DESCRIPTION	PART#	COMMENTS
Gun: Ultra-Lite 6000 Manual Gun	235628	*Automatic Applications need to be reviewed.
Swivel: Straight Style ½” M x ½” F	207947	
Fittings: Misc. (Application Specific)		*Application driven
Pump Selection: Ram included- 5-Gallon 34:1 Power Ratio 55:1 Power Ratio	231112 231115	
55-Gallon 34:1 Power Ratio 55:1 Power Ratio	223818 223819	
Hose: 25’ x ½” ID Moisture-Lok	947089	
Installation/Start Up & Training		*To be determined by customer requirements.

Attention: For additional system information please contact:

- Graco Tech Assistance 800-543-0339 • www.graco.com
- Local Authorized Graco SAE Distributor
- Steve Buerkle Graco AM 513-260-1235
- Bob Degenkolb Graco SS 734-516-0162