



**TREMSIL 600
SILICONE GLAZING SEALANT**

Tremsil 600 is a one-part, medium modulus, neutral cure Silicone Sealant.

Viscosity: 200,000 cps @ 75F

Packaging: Cartridges, 5's and 55 gallon containers.

Rheology: Thixotropic

Pumping System is based on the maximum viscosity (200,000cps) using a ½" diameter hose, 25' in length, manual gun w/swivel, ¼" bead size and flow rates of 1 to 2 pounds per minute based on application temperatures.

GRACO EQUIPMENT RECOMMENDATION:

DESCRIPTION	PART#	COMMENTS
Gun: Ultra-Lite 6000 Manual Gun	235628	*Automatic applications need to be reviewed.
Swivel: Straight Style ½" M x ½"F	207947	
Fittings: Misc.		*Application Specific *Application driven

Pump Selection:

Ram Included-

5- Gallon

34:1 Power Ratio 231112

55:1 Power Ratio 231115

55-Gallon

34:1 Power Ratio 223818

55:1 Power Ratio 223819

Hose:

25' x ½" ID 947089

Moisture-Lok

Installation/Start Up

& Training

TBD by customer requirements.

Attention: For additional system information please contact:

- Graco Tech Assistance 800-543-0339 • www.graco.com
- Local Authorized Graco SAE Distributor.
- Steve Buerkle Graco AM 513-260-1235
- Bob Degenkolb Graco SS 734-516-0162