

EXOAIR® FLEX FOAM

High-Performance Thermal and Acoustical Barrier

Product Overview

ExoAir® Flex Foam provides a high-performance thermal and acoustical barrier around windows and doors. Gain peace of mind as this flexible foam helps alleviate concerns of a comprised seal caused by window movement from wind loads or temperature changes. ExoAir Flex remains flexible after cure with an industry-leading movement range of +/-15%.

Features & Benefits

- Industry-leading movement range of +/-15% (Movement Accommodation Factor of 30%)
- CFC-free and can be applied over a wide temperature range, making it a reliable, four-season solution
- Minimal expanding/low pressure so windows won't bow or warp
- Non-rigid composition is highly flexible and won't crack
- Closed cell so it won't absorb water
- Can trim or cut in 45 minutes

Documented, Tested Performance

Flexibility Test: Even after 1000 testing cycles over 166 hours, where the ExoAir Flex Foam joint was stretched and compressed to 1/8 or 15%, the foam seal remained reliable.

AAMA 812: ExoAir Flex Foam had a maximum pressure build of 0.633 psi which indicates low potential for bowing or warping of windows and doors.

ASTM D2842-06: After 96 hours of immersion, ExoAir Flex Foam had a .03% water absorption which indicates there is little or no absorption.



Tremco Pu Applicator Guns

Pu Pro Applicator

- Part Number: 001798MG501
- Heavy-duty gun that provides durability and total control
- All-aluminum construction
- Lightweight and compact
- Corrosion and wear-resistant
- Ergonomically-designed for comfort during extended use
- Spring trigger for accurate flow control

Pu Contractor Applicator

- Part Number: 001701MG501
- Plastic and metal combination
- Lightweight and compact
- Economic choice
- Spring trigger for accurate flow control
- Standard screw thread design for bead size adjustment and flow control

Pu Standard Applicator

- Part Number: 001798PG501
- All-plastic design
- Highly cost-effective, "disposable" choice
- Standard screw thread design for bead size adjustment and flow control

Pu Foam Cleaner

- Part Number: 001922GC501
- Packaging: 12 per case
- Pre-pressurized in an aerosol spray can
- Dispenses in the upright or inverted position
- Evaporates quickly
- Can be fitted directly to a PU foam gun, or used as a handheld aerosol can

Pu Foam Applicator Tips

- Part Number: 001400 501
- Replacement tips for PU applicator guns
- Color: White
- Packaging: 50/box



Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.

 **TREMCO**
Construction Products Group

Tremco® and ExoAir® are registered trademarks of Tremco Incorporated.
Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.

0221/EAFFSS

tremcocpg.com