

Revision Date: 01/31/2017

SAFETY DATA SHEET

1. Identification

Material name: VULKEM 116 LV OFF WHITE 30 CTG/CS

Material: 426803L 323

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

Contact person:EH&S DepartmentTelephone:216-292-5000

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer Category 1
Skin sensitizer Category 1
Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral 15.95 %
Acute toxicity, dermal 21.58 %
Acute toxicity, inhalation, vapor
Acute toxicity, inhalation, dust 99.26 %

or mist

Environmental Hazards

Acute hazards to the aquatic Category 1 environment

Unknown toxicity - Environment

Acute hazards to the aquatic 76.4 %

environment

Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:



Revision Date: 01/31/2017



Signal Word: Danger

Hazard Statement: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer. Very toxic to aquatic life.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate

ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Use personal protective equipment as required. Avoid release

to the environment.

Response: If inhaled: If breathing is difficult, remove person to fresh air and keep

comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or

concerned: Get medical advice/attention. Specific treatment (see this label).

Wash contaminated clothing before reuse. Collect spillage.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise

classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity CAS | S number | Content in percent (%)* |
|-----------------------|----------|-------------------------|
|-----------------------|----------|-------------------------|



Revision Date: 01/31/2017

| Diisodecyl phthalate | 26761-40-0 | 10 - <25% |
|---|------------|-----------|
| Calcium Carbonate (Limestone) | 1317-65-3 | 10 - <20% |
| Polyethylene | 9002-88-4 | 1 - <5% |
| P-chlorobenzotrifluoride | 98-56-6 | 1 - <5% |
| Titanium dioxide | 13463-67-7 | 1 - <5% |
| Heavy aromatic naphtha | 64742-94-5 | 1 - <5% |
| Aromatic petroleum distillates | 64742-95-6 | 1 - <5% |
| 1,2,4-Trimethylbenzene | 95-63-6 | 0.1 - <1% |
| 4,4'-Methylene bis(phenylisocyanate) | 101-68-8 | 0.1 - <1% |
| 1,3,5-Trimethylbenzene | 108-67-8 | 0.1 - <1% |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 | 0.1 - <1% |
| Aluminum oxide | 1344-28-1 | 0.1 - <1% |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops,

provide artificial respiration. Move to fresh air. If breathing is difficult, give

oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly

clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an

allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.



Revision Date: 01/31/2017

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled

material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning

Collect spillage in containers, seal securely and deliver for disposal

according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so.

7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case

of handling which causes formation of dust.

Conditions for safe storage,

including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | type | Exposure Limit Values | Source |
|---------------------------|------|-----------------------|---|
| Calcium Carbonate | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air |
| (Limestone) - Total dust. | | _ | Contaminants (29 CFR 1910.1000) (02 2006) |
| Calcium Carbonate | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air |
| (Limestone) - Respirable | | | Contaminants (29 CFR 1910.1000) (02 2006) |





Revision Date: 01/31/2017

| for all an | | | | |
|---|---------|-----------|---------------------------------------|--|
| fraction. | TWA | | 40 == =/==0 | LIC ACCILITATE hald Limit Values (02 2015) |
| Polyethylene - Inhalable particles. | | | 10 mg/m3 | US. ACGIH Threshold Limit Values (03 2015) |
| Polyethylene - Respirable particles. | TWA | | 3 mg/m3 | US. ACGIH Threshold Limit Values (03 2015) |
| Polyethylene - Respirable fraction. | PEL | | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Polyethylene - Total dust. | PEL | | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | | 15 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | | 50 millions of | US. OSHA Table Z-3 (29 CFR 1910.1000) |
| | | | particles per cubic foot of air | (2000) |
| Polyethylene - Respirable fraction. | TWA | | 5 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | | 15 millions of | US. OSHA Table Z-3 (29 CFR 1910.1000) |
| | | | particles per cubic foot of | (2000) |
| | | | air | |
| Titanium dioxide | TWA | | 10 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Titanium dioxide - Total dust. | PEL | | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air |
| Titanium dioxide - Respirable | TWA | | 15 millions of | Contaminants (29 CFR 1910.1000) (02 2006) US. OSHA Table Z-3 (29 CFR 1910.1000) (03 |
| fraction. | 1 **/ (| | particles per | 2016) |
| | | | cubic foot of | · |
| Titanium dioxide - Total dust. | TWA | | air 15 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 |
| Titaliiuiii dioxide - Total dust. | 100 | | 13 1119/1113 | 2016) |
| Titanium dioxide - Respirable fraction. | TWA | | 5 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Titanium dioxide - Total dust. | TWA | | 50 millions of | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 |
| | | | particles per cubic foot of | 2016) |
| | | | air | |
| Heavy aromatic naphtha - Non-aerosol as total hydrocarbon vapor | TWA | | 200 mg/m3 | US. ACGIH Threshold Limit Values (03 2014) |
| Heavy aromatic naphtha | PEL | 100 ppm | 400 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| 1,2,4-Trimethylbenzene | REL | 25 ppm | 125 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | TWA | 25 ppm | 125 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 25 ppm | 125 mg/m3 | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) |
| | AN ESL | | 25 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | ST ESL | | 140 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013) |
| | ST ESL | | 700 μg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013) |
| | AN ESL | | 125 μg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | TWA PEL | 25 ppm | 125 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | TWA | 25 ppm | | US. ACGIH Threshold Limit Values (2011) |
| 4,4'-Methylene bis(phenylisocyanate) | TWA | 0.005 ppm | | US. ACGIH Threshold Limit Values (2011) |
| | Ceiling | 0.02 ppm | 0.2 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm | | US. ACGIH Threshold Limit Values (2011) |
| Crystalline Silica (Quartz)/ | TWA | | 0.025 mg/m3 | US. ACGIH Threshold Limit Values (2011) |





Revision Date: 01/31/2017

| Silica Sand - Respirable fraction. | | | |
|---|-----|--|--|
| Crystalline Silica (Quartz)/ Silica Sand | PEL | 0.05 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable. | TWA | 2.4 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | 0.1 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Aluminum oxide - Respirable fraction. | TWA | 1 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Respirable fraction. | TWA | 5 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Aluminum oxide - Total dust. | TWA | 15 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| | TWA | 50 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |
| Aluminum oxide - Respirable fraction. | TWA | 15 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016) |

| Chemical name | type | Exposure Limit Values | Source |
|--|------|-----------------------|---|
| Diisodecyl phthalate | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Calcium Carbonate (Limestone) - Total dust. | STEL | 20 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |





Revision Date: 01/31/2017

| Calcium Carbonate | TWA | | 3 mg/m3 | Canada. British Columbia OELs. (Occupational |
|---|---------|-----------|-------------|---|
| (Limestone) - Respirable fraction. | | | | Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Calcium Carbonate (Limestone) - Total dust. | TWA | | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Polyethylene - Respirable fraction. | TWA | | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Polyethylene - Total dust. | TWA | | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Polyethylene - Inhalable fraction. | TWA | | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Polyethylene - Respirable fraction. | TWA | | 3 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Polyethylene - Total dust. | TWA | | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011) |
| Titanium dioxide - Total dust. | TWA | | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide - Respirable fraction. | TWA | | 3 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide | TWA | | 10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Titanium dioxide - Total dust. | TWA | | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Heavy aromatic naphtha - Non-aerosol as total hydrocarbon vapor | TWA | | 200 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| Heavy aromatic naphtha - Non-aerosol as total hydrocarbon vapor | TWA | | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Heavy aromatic naphtha | TWA | | 525 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Heavy aromatic naphtha | TWA | 400 ppm | 1,590 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | 123 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | 123 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| 4,4'-Methylene bis(phenylisocyanate) | CEILING | 0.01 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 0.005 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |



Revision Date: 01/31/2017

| 4,4'-Methylene bis(phenylisocyanate) | TWA | 0.005 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
|---|-----|---------------------|--|
| | CEV | 0.02 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| 4,4'-Methylene bis(phenylisocyanate) | TWA | 0.005 ppm 0.051 mg/ | m3 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm 123 mg/ | m3 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.025 mg/ | m3 Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.10 mg/ | m3 Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. | TWA | 0.1 mg/ | m3 Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level

(in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter,

cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties



Revision Date: 01/31/2017

Appearance

Physical state: solid
Form: Paste
Color: Off-white
Odor: Mild

Odor threshold:

pH:

No data available.

No data available.

Melting point/freezing point:

No data available.

No data available.

No data available.

No data available.

Flash Point: 99 °C 210 °F(ISO 3679 (seta closed))

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.16

Solubility(ies)

Solubility in water: Insoluble in water
Solubility (other): No data available.
Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g.

nitric acid, peroxides and chromates). Strong bases. Water, moisture.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information



Revision Date: 01/31/2017

Information on likely routes of exposure

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 8,253.4 mg/kg

Dermal

Product: ATEmix: 7,995.09 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Diisodecyl phthalate LC 50 (Rat): > 12.54 mg/l

Polyethylene LC 50 (Rabbit): 20.1 mg/l

Titanium dioxide LC 50 (Rat): 3.43 mg/l

Heavy aromatic naphtha LC 50 (Rat): 25.7 mg/l

1,2,4-Trimethylbenzene LC 50 (Rat): 10,200 mg/m3

1,3,5-Trimethylbenzene LC 50 (Rat): 10,200 mg/m3

Aluminum oxide LC 50 (Rat): 7.6 mg/l



Revision Date: 01/31/2017

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

P-chlorobenzotrifluoride in vivo (Rabbit): Not irritant (unspecified classification) Experimental result,

Key study

Titanium dioxide in vivo (Rabbit): Not irritant Experimental result, Supporting study

Heavy aromatic

naphtha

in vivo (Rabbit): Irritating Experimental result, Key study

Aromatic petroleum

distillates

in vivo (Rabbit): Irritating Experimental result, Key study

1,2,4-Trimethylbenzene in vivo (Rabbit): Irritating Read-across from supporting substance (structural

analogue or surrogate), Key study

4,4'-Methylene

bis(phenylisocyanate)

in vivo (Rabbit): Irritating Read-across based on grouping of substances

(category approach), Key study

1,3,5-Trimethylbenzene in vivo (Rabbit): Irritating Experimental result, Key study

Aluminum oxide in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Titanium dioxide Rabbit, 24 hrs: Not irritating

Heavy aromatic

naphtha

Rabbit, 24 - 72 hrs: Not irritating

Aromatic petroleum

distillates

Rabbit, 24 - 72 hrs: Not irritating

1,2,4-Trimethylbenzene Rabbit, 30 min: Not irritating

1,3,5-Trimethylbenzene Rabbit, 30 min: Not irritating

Aluminum oxide Rabbit, 24 hrs: Not irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity



Revision Date: 01/31/2017

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica (Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

(Quartz)/ Silica

Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.



Revision Date: 01/31/2017

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Diisodecyl phthalate LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 0.47 mg/l Mortality

1,2,4-Trimethylbenzene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l

Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Diisodecyl phthalate EC 50 (Water flea (Daphnia magna), 48 h): > 0.02 mg/l Intoxication

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Heavy aromatic naphtha NOAEL (Oncorhynchus mykiss, 28 d): 0.098 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.



Revision Date: 01/31/2017

Mobility in soil: No data available.

Other adverse effects: Very toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity Reportable quantity

P-chlorobenzotrifluoride De minimis concentration: TSCA 4% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

4,4'-Methylene 5000 lbs.

bis(phenylisocyanate)

Cumene 5000 lbs.
2,4-Toluene diisocyanate 100 lbs.
Xylene 100 lbs.
Toluene-2,6-Diisocyanate 100 lbs.
Ethylbenzene 1000 lbs.



Revision Date: 01/31/2017

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

| Rei | oorta | ble |
|-----|-------|-----|
|-----|-------|-----|

Chemical IdentityquantityThreshold Planning Quantity2,4-Toluene diisocyanate100 lbs.500 lbs.Toluene-2,6-Diisocyanate100 lbs.100 lbs.

SARA 304 Emergency Release Notification

| Chemical Identity | Reportable quantity |
|----------------------|---------------------|
| Diisodecyl phthalate | · |

Diisodecyi phinaiale

4,4'-Methylene 5000 lbs.

bis(phenylisocyanate)

Cumene 5000 lbs.
2,4-Toluene diisocyanate Xylene 100 lbs.
Toluene-2,6-Diisocyanate Ethylbenzene Diisodecyl phthalate 5000 lbs.

(mixed Is)

SARA 311/312 Hazardous Chemical

| Chemical Identity | Threshold Planning Quantity |
|------------------------------|-----------------------------|
| 2,4-Toluene diisocyanate | 500lbs |
| Toluene-2,6-Diisocyanate | 100lbs |
| Diisodecyl phthalate | 10000 lbs |
| Calcium Carbonate | 10000 lbs |
| (Limestone) | |
| Polyethylene | 10000 lbs |
| P-chlorobenzotrifluoride | 10000 lbs |
| Titanium dioxide | 10000 lbs |
| Heavy aromatic naphtha | 10000 lbs |
| Aromatic petroleum | 10000 lbs |
| distillates | |
| 1,2,4-Trimethylbenzene | 10000 lbs |
| 4,4'-Methylene | 10000 lbs |
| bis(phenylisocyanate) | |
| 1,3,5-Trimethylbenzene | 10000 lbs |
| Crystalline Silica (Quartz)/ | 10000 lbs |
| Silica Sand | |
| Aluminum oxide | 10000 lbs |
| | |

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

| Chemical Identity F | Reportable quantity |
|---------------------|---------------------|
|---------------------|---------------------|

2,4-Toluene diisocyanate Ibs Toluene-2,6-Diisocyanate Ibs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u> <u>Reportable quantity</u>



Revision Date: 01/31/2017

Xylene Reportable quantity: lbs.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Titanium dioxide Carcinogenic. 09 2011
Cumene Carcinogenic. 09 2011
2,4-Toluene diisocyanate Carcinogenic. 09 2011
Toluene-2,6-Diisocyanate Ethylbenzene Carcinogenic. 09 2011
Carcinogenic. 09 2011
Carcinogenic. 09 2011
Carcinogenic. 09 2011

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium Carbonate (Limestone)

P-chlorobenzotrifluoride

Titanium dioxide

Heavy aromatic naphtha

Crystalline Silica (Quartz)/ Silica Sand

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium Carbonate (Limestone)

Titanium dioxide

Heavy aromatic naphtha

Crystalline Silica (Quartz)/ Silica Sand

2,4-Toluene diisocyanate

Toluene-2,6-Diisocyanate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Diisodecyl phthalate

Calcium Carbonate (Limestone)

Titanium dioxide

Heavy aromatic naphtha

US. Rhode Island RTK

Chemical Identity

Diisodecyl phthalate

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable



Revision Date: 01/31/2017

VOC:

Regulatory VOC (less water and : 48 g/l exempt solvent) : 48 g/l

VOC Method 310 : 4.01 %



Revision Date: 01/31/2017

Inventory Status:

Australia AICS:

One or more components in this product are

not listed on or exempt from the Inventory.

Canada DSL Inventory List:

All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory:

All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the inventory.

Mexico INSQ: One or more components in this product are

not listed on or exempt from the Inventory.

Ontario Inventory:

One or more components in this product are

not listed on or exempt from the Inventory.

Taiwan Chemical Substance Inventory:

One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 01/31/2017

16.Other information, including date of preparation or last revision

Revision Date: 01/31/2017

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.