

VULKEM 45 SSL GRAYVersion 4.
REVISION DATE: 09/21/2011

Print Date 09/22/2011

SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION**Product Information**Trade name : VULKEM 45 SSL GRAY
Product code : 445712 333Supplier : Tremco Canada division
220 Wicksteed Avenue
Toronto, ON M4H 1G7Telephone : (416) 421-3300
Emergency Phone: : (613) 996-6666

Product use : Sealant

Preparation InformationPrepared by: : Sewnauth Raghunandan
Date: : 09/21/2011
Telephone : (416) 421-3300**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Gray. Non-sag gunnable paste. May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

Acute Potential Health Effects/ Routes of EntryInhalation : May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization.
Eyes : Direct contact may cause mild irritation.
Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
Skin : May cause sensitization resulting in irritation, itching and redness.**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Prolonged or repeated exposure to butyl benzyl phthalate may cause reduced body weights and adverse effects on the liver, kidney, spleen, pancreas, and reproductive organs. Di(2-ethylhexyl) phthalate, (dioctyl phthalate) given in the diet, produced increased incidence of liver cancers in female rats and male and female mice. An increased incidence of liver cancers or neoplasms were observed in male rats. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting,

VULKEM 45 SSL GRAY

Version 4.

Print Date 09/22/2011

REVISION DATE: 09/21/2011

drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

Target Organs: Skin, Eye, Ingestion, Lung

SECTION 3 : HAZARDOUS INGREDIENTS

Chemical Name	CAS-No.	Weight % Range
Butyl benzyl phthalate	85-68-7	15.0 - 40.0
Stoddard solvent (Mineral Spirits)	8052-41-3	5.0 - 10.0
Calcium oxide	1305-78-8	1.0 - 5.0
Xylene	1330-20-7	1.0 - 5.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Ethylbenzene	100-41-4	0.1 - 1.0
Diocetyl phthalate	117-81-7	0.1 - 1.0
1,2,4-Trimethylbenzene	95-63-6	0.1 - 1.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5: FIRE / EXPLOSION HAZARDS

- Flash point : 68 °C, 154 °F
- Method : Setaflash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate

VULKEM 45 SSL GRAY

Version 4.
REVISION DATE: 09/21/2011

Print Date 09/22/2011

container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion and contact with skin, eyes and clothing. Preferably use entire contents in one continuous work session. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not store or use near food. Keep container closed when not in use. Since emptied containers retain product residue and vapor, observe precautions even after container is emptied. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures** : Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Butyl benzyl phthalate	85-68-7			
Stoddard solvent (Mineral Spirits)	8052-41-3	Ontario TWAEV: ACGIH TWA:	525 mg/m3 100 ppm	
Calcium oxide	1305-78-8	Ontario TWAEV: ACGIH TWA:	2 mg/m3 2 mg/m3	
Xylene	1330-20-7	Ontario TWAEV: Ontario STEV: ACGIH TWA: ACGIH STEL:	435 mg/m3 650 mg/m3 100 ppm 150 ppm	
Titanium dioxide	13463-67-7	Ontario TWAEV: ACGIH TWA:	10 mg/m3 10 mg/m3	Total dust.
Ethylbenzene	100-41-4	Ontario TWAEV: Ontario STEV: ACGIH TWA: ACGIH STEL:	435 mg/m3 540 mg/m3 100 ppm 125 ppm	

VULKEM 45 SSL GRAY

Version 4.

Print Date 09/22/2011

REVISION DATE: 09/21/2011

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Diocetyl phthalate	117-81-7	Ontario TWAEV: Ontario STEV: ACGIH TWA:	3 mg/m3 5 mg/m3 5 mg/m3	
1,2,4-Trimethylbenzene	95-63-6	Ontario TWAEV: ACGIH TWA:	123 mg/m3 25 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: Liquid (paste)
Form	: Non-sag gunnable paste
Color	: Gray
Odor	: Petroleum
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Insoluble
Evaporation Rate:	: Not available.
Specific Gravity	: 1.3178
% Volatile Weight	: 7 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Amines. Water or moisture and oxidizing agents. Alcohols. Strong acids. Strong bases.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Butyl benzyl phthalate, CAS-No.: 85-68-7 Acute oral toxicity (LD-50 oral)	13,500 mg/kg (Rat)
Xylene, CAS-No.: 1330-20-7 Acute oral toxicity (LD-50 oral)	4,300 mg/kg (Rat) 1,590 mg/kg (Mouse) 6,670 mg/kg (Rat) 3,523 - 8,600 mg/kg (Rat) 5,627 mg/kg (Mouse)
Acute inhalation toxicity (LC-50)	6,350 mg/l for 4 h (Rat) 3,907 mg/l for 6 h (Mouse) 8,000 mg/l for 4 h (Rat)
Ethylbenzene, CAS-No.: 100-41-4 Acute oral toxicity (LD-50 oral)	5,460 mg/kg (Rat) 3,500 mg/kg (Rat)



VULKEM 45 SSL GRAY

Version 4.

Print Date 09/22/2011

REVISION DATE: 09/21/2011

Acute dermal toxicity (LD-50 dermal)	17,800 mg/kg (Rabbit)
Dioctyl phthalate, CAS-No.: 117-81-7	
Acute oral toxicity (LD-50 oral)	25,000 mg/kg (Rat) 25,000 mg/kg (Rat) 30,000 mg/kg (Mouse) 33,900 mg/kg (Rabbit) 26,300 mg/kg (Guinea pig)
Acute dermal toxicity (LD-50 dermal)	25,000 mg/kg (Rabbit) 10,000 mg/kg (Guinea pig) 25,000 mg/kg (Rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Disposal Method : Dispose as hazardous waste according to all local, state, federal and provincial regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

Canadian Regulations:

WHMIS Classification : D2A, D2B, B3

This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Other Regulations:

Regulatory VOC (less water and exempt solvent) : 104 g/l



VULKEM 45 SSL GRAY

Version 4.
REVISION DATE: 09/21/2011

Print Date 09/22/2011

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	2
Reactivity	0
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Sewnauth Raghunandan

Legend

- ACGIH - American Conference of Governmental Hygienists
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System