



**TREMPRO 656 WHITE - 30 CTG**

Version 1.3  
 REVISION DATE: 12/21/2007

Print Date 05/02/2008

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : TREMPRO 656 WHITE - 30 CTG  
 Product code : 656806 323

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

**SECTION 2 - HAZARDS IDENTIFICATION**

**Emergency Overview**

White. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system.  
 Eyes : Slightly irritating.  
 Ingestion : May cause irritation to the mouth, throat and stomach.  
 Skin : Irritant effect may be delayed.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Acrylic polymer	NJ TSRN# 51721300-5277P	40.0 - 70.0
Water	7732-18-5	30.0 - 60.0
White mineral oil	8042-47-5	7.0 - 13.0
Amorphous silica	7631-86-9	1.0 - 5.0
Propylene glycol	57-55-6	1.0 - 5.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Ammonium hydroxide	1336-21-6	<1.0
Zinc oxide	1314-13-2	<1.0
Chlorothalonil	1897-45-6	<1.0
Formaldehyde	50-00-0	<0.1



**TREMPRO 656 WHITE - 30 CTG**

Version 1.3  
 REVISION DATE: 12/21/2007

Print Date 05/02/2008

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash with water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use. Use that which is appropriate to the surroundings.
- Hazardous combustion products : Smoke, fumes.
- Protective equipment for firefighters : Not applicable. Product is not expected to burn.
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal. Keep out of water courses.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not use in confined or poorly ventilated areas. Store in sealed containers in a dry, ventilated warehouse location above freezing.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

**TREMPRO 656 WHITE - 30 CTG**

Version 1.3

Print Date 05/02/2008

REVISION DATE: 12/21/2007

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Use safety glasses if eye contact is likely.
- Protective measures : Use professional judgment in the selection, care, and use. Other equipment not normally required.
- Engineering measures : General ventilation is sufficient. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Amorphous silica	7631-86-9	ACGIH TWA: ACGIH TWA: OSHA PEL: OSHA PEL: OSHA TWA:	3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3 0.8 mg/m3	Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Ammonium hydroxide	1336-21-6	ACGIH TWA: ACGIH STEL: OSHA PEL:	25 ppm 35 ppm 35 mg/m3	
Zinc oxide	1314-13-2	ACGIH TWA: ACGIH STEL: OSHA PEL: OSHA PEL: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 10 mg/m3 5 mg/m3 5 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable fraction. Fume. Respirable fraction. Total dust. Total dust. Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Non-sag gunnable paste
- Color : White
- Odor : Acrylate
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : < 32 °C, < 90 °F
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Miscible

**TREMPRO 656 WHITE - 30 CTG**

Version 1.3

Print Date 05/02/2008

REVISION DATE: 12/21/2007

Specific Gravity : 1.0931  
 % Volatile Weight : 35 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Oxidizing agents.Strong acids.Strong bases.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Amorphous silica, CAS-No.: 7631-86-9 Acute oral toxicity (LD-50 oral)	22,500 mg/kg ( Rat ) 22,500 mg/kg ( Rat ) 15,000 mg/kg ( Mouse ) 15,000 mg/kg ( Mouse )
Propylene glycol, CAS-No.: 57-55-6 Acute oral toxicity (LD-50 oral)	30,000 mg/kg ( Rat ) 18,000 mg/kg ( Rabbit ) 19,000 mg/kg ( Dog ) 23,900 - 31,800 mg/kg ( Mouse ) 18,400 - 196,000 mg/kg ( Guinea pig )
Ammonium hydroxide, CAS-No.: 1336-21-6 Acute oral toxicity (LD-50 oral)	350 mg/kg ( Rat )
Zinc oxide, CAS-No.: 1314-13-2 Acute oral toxicity (LD-50 oral)	7,950 mg/kg ( Mouse ) 7,950 mg/kg ( Mouse )
Chlorothalonil, CAS-No.: 1897-45-6 Acute oral toxicity (LD-50 oral) Acute dermal toxicity (LD-50 dermal)	10,000 mg/kg ( Rat ) 10,000 mg/kg ( Albino rat )
Formaldehyde, CAS-No.: 50-00-0 Acute oral toxicity (LD-50 oral) Acute inhalation toxicity (LC-50)	800 mg/kg ( Rat ) 260 mg/kg ( Guinea pig ) 100 mg/kg ( Rat ) 42 mg/kg ( Mouse ) 0.82 mg/l for 30 min ( Rat ) 0.48 mg/l for 4 h ( Rat ) 0.414 mg/l for 4 h ( Mouse ) 0.4 mg/l for 2 h ( Mouse )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
 NOT REGULATED

**TREMPRO 656 WHITE - 30 CTG**

Version 1.3  
 REVISION DATE: 12/21/2007

Print Date 05/02/2008

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : Chlorothalonil 1897-45-6

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :

Amorphous silica	7631-86-9
Titanium dioxide	13463-67-7
Ammonium hydroxide	1336-21-6
Zinc oxide	1314-13-2
Chlorothalonil	1897-45-6
Formaldehyde	50-00-0

OSHA Status: Considered : Irritant  
 hazardous based on the following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and exempt solvent) : 36 g/l

VOC Method 310 : 1 %

**U.S. State Regulations:**

MASS RTK Components : Amorphous silica 7631-86-9  
 Titanium dioxide 13463-67-7  
 Formaldehyde 50-00-0

Penn RTK Components : Acrylic polymer NJ TSRN# 51721300-5277P  
 Water 7732-18-5  
 White mineral oil 8042-47-5  
 Amorphous silica 7631-86-9  
 Propylene glycol 57-55-6  
 Titanium dioxide 13463-67-7

NJ RTK Components : Acrylic polymer NJ TSRN# 51721300-5277P  
 Water 7732-18-5  
 White mineral oil 8042-47-5  
 Amorphous silica 7631-86-9  
 Propylene glycol 57-55-6  
 Titanium dioxide 13463-67-7

**WARNING!** Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

1897-45-6	Chlorothalonil
50-00-0	Formaldehyde



**TREMPRO 656 WHITE - 30 CTG**

Version 1.3  
 REVISION DATE: 12/21/2007

Print Date 05/02/2008

140-88-5 Ethyl Acrylate

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT - Department of Transportation  
 DSL - Domestic Substance List  
 EPA - Environmental Protection Agency  
 HMIS - Hazardous Materials Information System  
 IARC - International Agency for Research on Cancer  
 MSHA - Mine Safety Health Administration  
 NDSL - Non-Domestic Substance List  
 NIOSH - National Institute for Occupational Safety and Health  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 RTK - Right To Know  
 SARA - Superfund Amendments and Reauthorization Act  
 STEL - Short Term Exposure Limit  
 TLV - Threshold Limit Value  
 TSCA - Toxic Substances Control Act  
 TWA - Time Weighted Average  
 V - Volume  
 VOC - Volatile Organic Compound  
 WHMIS - Workplace Hazardous Materials Information System