

**TREMGLAZE U1600 BEIGE - 30 CTG CS**

Version 2.

Print Date 10/11/2008

REVISION DATE: 10/10/2008

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : TREMGLAZE U1600 BEIGE - 30 CTG CS  
 Product code : 786808 323

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

**SECTION 2 - HAZARDS IDENTIFICATION**
**Emergency Overview**

Beige. Non-sag gunnable paste. May cause nausea, headaches, and dizziness. May cause allergic respiratory sensitization. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause nausea, headaches, and dizziness. May cause allergic respiratory sensitization.  
 Eyes : Direct contact may cause mild irritation.  
 Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.  
 Skin : May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Prolonged or repeated exposure to butyl benzyl phthalate may cause reduced body weights and adverse effects on the liver, kidney, spleen, pancreas, and reproductive organs. Organosilane may cause liver injury with fibrosis after repeated and prolonged overexposure. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Calcium carbonate	471-34-1	30.0 - 60.0
Polyurethane Polymer	NJ TSRN# 51721300-5388P	15.0 - 40.0
Butyl benzyl phthalate	85-68-7	15.0 - 40.0
Calcium Carbonate (Limestone)	1317-65-3	7.0 - 13.0
Diisodecyl phthalate	26761-40-0	3.0 - 7.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <0.1



**TREMGRAZE U1600 BEIGE - 30 CTG CS**

Version 2.  
REVISION DATE: 10/10/2008

Print Date 10/11/2008

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not store or use near food. Store under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

**TREMGLAZE U1600 BEIGE - 30 CTG CS**

Version 2.

Print Date 10/11/2008

REVISION DATE: 10/10/2008

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Wear impervious gloves, such as nitrile or neoprene and suitable protective apparel..
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

**Exposure Limits**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Non-sag gunnable paste
- Color : Beige
- Odor : Slight
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Specific Gravity : 1.454
- % Volatile Weight : 0 %

**SECTION 10 - REACTIVITY / STABILITY**

- Substances to avoid : Amines. Water or moisture. Alcohols. Strong acids. Strong bases.

**TREMGLAZE U1600 BEIGE - 30 CTG CS**

Version 2.

Print Date 10/11/2008

REVISION DATE: 10/10/2008

Stability : Stable  
 Hazardous polymerization : Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Calcium carbonate, CAS-No.: 471-34-1  
 Acute oral toxicity (LD-50 oral) 6,450 mg/kg ( Rat )

Butyl benzyl phthalate, CAS-No.: 85-68-7  
 Acute oral toxicity (LD-50 oral) 13,500 mg/kg ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
 NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

## OSHA Hazardous Components :

Butyl benzyl phthalate 85-68-7  
 Calcium Carbonate (Limestone) 1317-65-3  
 Diisodecyl phthalate 26761-40-0  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

OSHA Status: Considered : Irritant  
 hazardous based on the  
 following criteria:

OSHA Flammability : Not Regulated

**TREMGRAZE U1600 BEIGE - 30 CTG CS**

Version 2.

Print Date 10/11/2008

REVISION DATE: 10/10/2008

Regulatory VOC (less water and exempt solvent) : 6 g/l

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:  
Butyl benzyl phthalate 85-68-7

**U.S. State Regulations:**

- MASS RTK Components : Calcium carbonate 471-34-1  
Butyl benzyl phthalate 85-68-7  
Calcium Carbonate (Limestone) 1317-65-3  
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
- Penn RTK Components : Calcium carbonate 471-34-1  
Polyurethane Polymer NJ TSRN# 51721300-5388P  
Butyl benzyl phthalate 85-68-7  
Calcium Carbonate (Limestone) 1317-65-3  
Diisodecyl phthalate 26761-40-0
- NJ RTK Components : Calcium carbonate 471-34-1  
Polyurethane Polymer NJ TSRN# 51721300-5388P  
Butyl benzyl phthalate 85-68-7  
Calcium Carbonate (Limestone) 1317-65-3  
Diisodecyl phthalate 26761-40-0

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

- 85-68-7 Butyl benzyl phthalate
- 26761-40-0 Diisodecyl phthalate
- 68515-49-1 Diisodecyl phthalate (mixed Is)
- 1333-86-4 Carbon Black
- 14808-60-7 Crystalline Silica (Quartz)/ Silica Sand
- 117-81-7 Dioctyl phthalate

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	1
Reactivity	1
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**



**TREMGLAZE U1600 BEIGE - 30 CTG CS**

Version 2.

Print Date 10/11/2008

REVISION DATE: 10/10/2008

ACGIH - American Conference of Governmental Hygienists  
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
DOT - Department of Transportation  
DSL - Domestic Substance List  
EPA - Environmental Protection Agency  
HMIS - Hazardous Materials Information System  
IARC - International Agency for Research on Cancer  
MSHA - Mine Safety Health Administration  
NDSL - Non-Domestic Substance List  
NIOSH - National Institute for Occupational Safety and Health  
NTP - National Toxicology Program  
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
RCRA - Resource Conservation and Recovery Act  
RTK - Right To Know  
SARA - Superfund Amendments and Reauthorization Act  
STEL - Short Term Exposure Limit  
TLV - Threshold Limit Value  
TSCA - Toxic Substances Control Act  
TWA - Time Weighted Average  
V - Volume  
VOC - Volatile Organic Compound  
WHMIS - Workplace Hazardous Materials Information System