

VULKEM 950NF GRAY PART A

 Version 1.3
 REVISION DATE: 06/19/2008

Print Date 06/20/2008

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : VULKEM 950NF GRAY PART A
 Product code : 870712NF805

COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300

SECTION 2 - HAZARDS IDENTIFICATION
Emergency Overview

Gray. Liquid (paste). No serious effects anticipated under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.
 Eyes : Slightly irritating.
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.
 Skin : No effects anticipated.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged and repeated exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening). Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Long chain ester	NJ TSRN# 51721300-5801P	> 60.0
Polyester Resin	NJ TSRN# 51721300-5802P	15.0 - 40.0
Talc	14807-96-6	7.0 - 13.0
Titanium dioxide	13463-67-7	3.0 - 7.0
Diisodecyl phthalate	26761-40-0	1.0 - 5.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Generally not required under normal conditions of use.
 Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
 Skin contact : Wash with water. If irritation, rash or other disorders develop, get medical attention

VULKEM 950NF GRAY PART A

Version 1.3
 REVISION DATE: 06/19/2008

Print Date 06/20/2008

Ingestion : immediately.
 : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point : Not available.
 Method : Not available.
 Lower explosion limit : Not available.
 Upper explosion limit : Not available.
 Autoignition temperature : Not available.
 Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
 Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form.
 Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
 Fire and explosion conditions : This product not expected to ignite under normal conditions of use. Product may ignite if heated in excess of its flash point.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a cool, dry, ventilated warehouse location.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

Respiratory protection : Not required under normal conditions of use.
 Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
 Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
 Protective measures : Use professional judgment in the selection, care, and use.
 Engineering measures : General ventilation is sufficient. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

VULKEM 950NF GRAY PART A

Version 1.3

Print Date 06/20/2008

REVISION DATE: 06/19/2008

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Talc	14807-96-6	ACGIH TWA: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable. Total dust. Total dust. Respirable fraction.
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid (paste)
Color	: Gray
Odor	: MildEster
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Negligible
Specific Gravity	: 1.13
% Volatile Weight	: 0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Oxidizing agents.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available



VULKEM 950NF GRAY PART A

Version 1.3
REVISION DATE: 06/19/2008

Print Date 06/20/2008

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :

Talc 14807-96-6
Titanium dioxide 13463-67-7

OSHA Status: Considered : Irritant
hazardous based on the Carcinogen
following criteria:

OSHA Flammability : Not Regulated

When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:
1 g/l

Regulatory VOC (less water and : 1 g/l
exempt solvent)

VOC Method 310 : 0 %

U.S. State Regulations:

MASS RTK Components : Talc 14807-96-6
Titanium dioxide 13463-67-7

Penn RTK Components : Long chain ester NJ TSRN# 51721300-5801P



VULKEM 950NF GRAY PART A

Version 1.3
 REVISION DATE: 06/19/2008

Print Date 06/20/2008

	Polyester Resin	NJ TSRN# 51721300-5802P
	Talc	14807-96-6
	Titanium dioxide	13463-67-7
	Diisodecyl phthalate	26761-40-0
NJ RTK Components :	Long chain ester	NJ TSRN# 51721300-5801P
	Polyester Resin	NJ TSRN# 51721300-5802P
	Talc	14807-96-6
	Titanium dioxide	13463-67-7
	Diisodecyl phthalate	26761-40-0

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:
 1333-86-4 Carbon Black

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	1
Reactivity	1
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- | | |
|--|--|
| ACGIH - American Conference of Governmental Hygienists | PEL - Permissible Exposure Limit |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act |
| DOT - Department of Transportation | RTK - Right To Know |
| DSL - Domestic Substance List | SARA - Superfund Amendments and Reauthorization Act |
| EPA - Environmental Protection Agency | STEL - Short Term Exposure Limit |
| HMIS - Hazardous Materials Information System | TLV - Threshold Limit Value |
| IARC - International Agency for Research on Cancer | TSCA - Toxic Substances Control Act |
| MSHA - Mine Safety Health Administration | TWA - Time Weighted Average |
| NDSL - Non-Domestic Substance List | V - Volume |
| NIOSH - National Institute for Occupational Safety and Health | VOC - Volatile Organic Compound |
| NTP - National Toxicology Program | WHMIS - Workplace Hazardous Materials Information System |
| OSHA - Occupational Safety and Health Administration | |