

**VULKEM 951 NF BLACK 3.75 GAL**Version 2.  
REVISION DATE: 10/15/2008

Print Date 10/16/2008

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : VULKEM 951 NF BLACK 3.75 GAL  
 Product code : 871802 805

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

Product use : Coating

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Black. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

Eyes : Vapor and/or mist may cause eye irritation.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Eye, Lung, Liver, Kidney, Skin, Nerve

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Polyurethane Polymer	NJ TSRN# 51721300-5379P	> 60.0
Propanoic acid ester	6846-50-0	10.0 - 30.0
Propylene carbonate	108-32-7	10.0 - 30.0

## VULKEM 951 NF BLACK 3.75 GAL

Version 2.

Print Date 10/16/2008

REVISION DATE: 10/15/2008

Diisodecyl phthalate	26761-40-0	5.0 - 10.0
Carbon Black	1333-86-4	1.0 - 5.0
Isophorone Diisocyanate	4098-71-9	- <1.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <0.1

### SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

### SECTION 5 - FIRE FIGHTING MEASURES

Flash point	:	> 212 °F, > 100 °C
Method	:	Setaflash Closed Cup
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	Product may ignite if heated in excess of its flash point. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition and flashback.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

### SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store

**VULKEM 951 NF BLACK 3.75 GAL**

Version 2.  
REVISION DATE: 10/15/2008

Print Date 10/16/2008

under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator (TC19C or equivalent) for isocyanates.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Carbon Black	1333-86-4	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	3.5 mg/m3 3.5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Isophorone Diisocyanate	4098-71-9	ACGIH TWA:	0.005 ppm	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Liquid
- Color : Black
- Odor : Solvent odor
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.

**VULKEM 951 NF BLACK 3.75 GAL**

Version 2.

Print Date 10/16/2008

REVISION DATE: 10/15/2008

Boiling point/range : Not available.  
 Water solubility : Negligible  
 Specific Gravity : 1.28  
 % Volatile Weight : 0 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Strong acids.Strong bases.Amines.Water or moisture.Alcohols.  
 Stability : Material is stable under normal storage, handling, and use.  
 Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Isophorone Diisocyanate, CAS-No.: 4098-71-9  
 Acute oral toxicity (LD-50 oral) 2,500 mg/kg ( Mouse ) 1,000 mg/kg ( Rat )  
 Acute inhalation toxicity (LC-50) 0.033 mg/l for 4 h ( Rat ) 0.123 mg/l for 4 h ( Rat )  
 Acute dermal toxicity (LD-50 dermal) 1,060 mg/kg ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
 NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.  
 SARA 311/312 Hazards : Acute Health Hazard  
 Chronic Health Hazard

**VULKEM 951 NF BLACK 3.75 GAL**

Version 2.

Print Date 10/16/2008

REVISION DATE: 10/15/2008

OSHA Hazardous Components :

Diisodecyl phthalate	26761-40-0
Carbon Black	1333-86-4
Isophorone Diisocyanate	4098-71-9
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

OSHA Status: Considered : Irritant  
 hazardous based on the Carcinogen  
 following criteria:

OSHA Flammability : IIIB

Regulatory VOC (less water and : 7 g/l  
 exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Carbon Black 1333-86-4

**U.S. State Regulations:**

MASS RTK Components : Carbon Black 1333-86-4  
 Isophorone Diisocyanate 4098-71-9  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Penn RTK Components : Polyurethane Polymer NJ TSRN# 51721300-5379P  
 Propanoic acid ester 6846-50-0  
 Propylene carbonate 108-32-7  
 Diisodecyl phthalate 26761-40-0  
 Carbon Black 1333-86-4

NJ RTK Components : Polyurethane Polymer NJ TSRN# 51721300-5379P  
 Propanoic acid ester 6846-50-0  
 Propylene carbonate 108-32-7  
 Diisodecyl phthalate 26761-40-0  
 Carbon Black 1333-86-4

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

26761-40-0	Diisodecyl phthalate
1333-86-4	Carbon Black
117-81-7	Dioctyl phthalate
75-56-9	Propylene oxide
14808-60-7	Crystalline Silica (Quartz)/ Silica Sand

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	1
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**VULKEM 951 NF BLACK 3.75 GAL**

Version 2.

Print Date 10/16/2008

REVISION DATE: 10/15/2008

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
DOT - Department of Transportation  
DSL - Domestic Substance List  
EPA - Environmental Protection Agency  
HMIS - Hazardous Materials Information System  
IARC - International Agency for Research on Cancer  
MSHA - Mine Safety Health Administration  
NDSL - Non-Domestic Substance List  
NIOSH - National Institute for Occupational Safety and Health  
NTP - National Toxicology Program  
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
RCRA - Resource Conservation and Recovery Act  
RTK - Right To Know  
SARA - Superfund Amendments and Reauthorization Act  
STEL - Short Term Exposure Limit  
TLV - Threshold Limit Value  
TSCA - Toxic Substances Control Act  
TWA - Time Weighted Average  
V - Volume  
VOC - Volatile Organic Compound  
WHMIS - Workplace Hazardous Materials Information System