

Revision Date: 07/28/2015

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC WHITE

Material: 955806 323

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants 220 Wicksteed Ave Toronto ON M4H 1G7 CA

Contact person:EH&S DepartmentTelephone:1-800-263-6046

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity Category 1A
Toxic to reproduction Category 2

Unknown toxicity - Health

Acute toxicity, oral 14.47 %
Acute toxicity, dermal 30.9 %
Acute toxicity, inhalation, vapor 98.27 %
Acute toxicity, inhalation, dust or mist 86.33 %

Environmental Hazards

Acute hazards to the aquatic Category 3 environment

Unknown toxicity - Environment

Acute hazards to the aquatic 80.64 % environment

Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:



Signal Word: Danger



Revision Date: 07/28/2015

Hazard Statement: May cause cancer.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Precautionary Statement:

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective

equipment as required.

Response: If exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|---|------------|-------------------------|
| Calcium Carbonate (Limestone) | 1317-65-3 | 10 - 30% |
| Calcium salt | 7778-18-9 | 10 - 30% |
| Titanium dioxide | 13463-67-7 | 3 - 7% |
| White mineral oil | 8042-47-5 | 1 - 5% |
| Petroleum distillates | 64742-47-8 | 1 - 5% |
| Toluene | 108-88-3 | 1 - 5% |
| Paraffin | 8002-74-2 | 0.5 - 1.5% |
| Methyl isobutyl ketone | 108-10-1 | 0.1 - 1% |
| Aluminum oxide | 1344-28-1 | 0.1 - 1% |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 | 0.1 - 1% |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. If skin irritation occurs: Get

medical advice/attention.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.



Revision Date: 07/28/2015

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: No data available.

Methods and material for containment and cleaning

up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe

to do so.



Revision Date: 07/28/2015

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in

case of handling which causes formation of dust.

Conditions for safe storage,

including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | type | Exposure Lim | nit Values | Source |
|--|--------------|--------------|--------------|---|
| Calcium Carbonate (Limestone) - Total dust. | PEL | | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Calcium Carbonate (Limestone) - Respirable fraction. | PEL | | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Calcium salt - Inhalable fraction. | TWA | | 10 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Calcium salt - Total dust. | PEL | | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Calcium salt - Respirable fraction. | PEL | | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Titanium dioxide | TWA | | 10 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Titanium dioxide - Total dust. | PEL | | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| White mineral oil - Inhalable fraction. | TWA | | 5 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| White mineral oil - Mist. | PEL | | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Petroleum distillates - Non-aerosol as total hydrocarbon vapor | TWA | | 200 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | TWA | | 200 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Toluene | TWA | 20 ppm | | US. ACGIH Threshold Limit Values (2011) |
| | TWA | 200 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | Ceiling | 300 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | MAX. CONC | 500 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |



TREMCO.

Version: 1.0


Revision Date: 07/28/2015

| Paraffin - Fume. | TWA | | 2 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
|---|------|---------|---|---|
| Methyl isobutyl ketone | TWA | 20 ppm | | US. ACGIH Threshold Limit Values (2011) |
| | STEL | 75 ppm | | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 100 ppm | 410 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Respirable fraction. | TWA | | 1 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| | PEL | | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Total dust. | PEL | | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | | 0.025 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable. | TWA | | 2.4 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | | 0.1 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Crystalline Silica (Quartz)/ Silica Sand - Total dust. | TWA | | 0.3 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |

| Chemical name | type | Exposure Limit Values | Source |
|---|------|-----------------------|---|
| Calcium Carbonate (Limestone) - Total dust. | STEL | 20 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |



Revision Date: 07/28/2015



TREMCU



Revision Date: 07/28/2015

| White mineral oil - Mist. | TWA | | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
|--|-------|--------|--------------|---|
| | STEL | | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Petroleum distillates - Non-aerosol as total hydrocarbon vapor | TWA | | 200 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Petroleum distillates | TWAEV | | 525 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Petroleum distillates - Non-aerosol as total hydrocarbon vapor | TWAEV | | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | TWAEV | | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Toluene | TWA | 20 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Toluene | TWAEV | 20 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Toluene | TWA | 50 ppm | 188 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Methyl isobutyl ketone | TWA | 20 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| | STEL | 75 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Methyl isobutyl ketone | TWAEV | 50 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | STEL | 75 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Methyl isobutyl ketone | STEL | 75 ppm | 307 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| | TWA | 50 ppm | 205 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the |



Revision Date: 07/28/2015

| | | | Quality of the Work Environment) (12 2008) |
|---|-------|----------------|---|
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.025 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable. | TWAEV | 0.10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. | TWA | 0.1 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |

Biological Limit Values

| Chemical Identity | Exposure Limit Values | Source |
|--|--------------------------------|---------------------|
| Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.) | 0.3 mg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Toluene (toluene: Sampling time: Prior to last shift of work week.) | 0.02 mg/l (Blood) | ACGIH BEL (03 2013) |
| Toluene (toluene: Sampling time: End of shift.) | 0.03 mg/l (Urine) | ACGIH BEL (03 2013) |
| Methyl isobutyl ketone (methyl isobutyl ketone: Sampling time: End of shift.) | 1 mg/l (Urine) | ACGIH BEL (03 2013) |

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure

limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: No data available.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Do not handle until all safety precautions have been read and understood. Obtain special instructions

before use.



Revision Date: 07/28/2015

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Paste
Color: White
Odor: Mild

Odor threshold:

pH:

No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas):

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.286

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
Auto-ignition temperature:
No data available.
Decomposition temperature:
No data available.
Viscosity:
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous

Reactions:

No data available.

Conditions to Avoid: Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Strong bases. Water, moisture.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information



Revision Date: 07/28/2015

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: Causes mild skin irritation.

Eye contact: Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 40,135.46 mg/kg

Dermal

Product: ATEmix: 7,910.98 mg/kg

Inhalation

Product: No data available.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium salt in vivo (Rabbit, 72 hrs): Not irritating

Titanium dioxide in vivo (Rabbit, 24 - 72 hrs): Not irritating

White mineral oil in vivo (Rabbit, 24 - 72 hrs): Not irritating

Petroleum distillates in vivo (Rabbit, 24 - 72 hrs): Not irritating

Toluene in vivo (Rabbit, 24 - 72 hrs): Not irritating

Paraffin in vivo (Rabbit, 24 - 72 hrs): Not irritating

Methyl isobutyl ketone in vivo (Rabbit, 24 - 72 hrs): Slightly irritating (Not Classified)

Aluminum oxide in vivo (Rabbit, 24 hrs): Not irritating

Respiratory or Skin Sensitization

Product: No data available.



Revision Date: 07/28/2015

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Methyl isobutyl

ketone

Overall evaluation: Possibly carcinogenic to humans.

Crystalline Silica

(Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

(Quartz)/ Silica

Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:



Revision Date: 07/28/2015

Fish

Product: No data available.

Specified substance(s):

Calcium salt LC 50 (Fathead minnow (Pimephales promelas), 96 h): > 1,970 mg/l

Mortality

Titanium dioxide LC 50 (Mummichog (Fundulus heteroclitus), 96 h): > 1,000 mg/l Mortality

Petroleum distillates LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 96 h): 2.9

mg/l Mortality

Toluene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 71.7 - 82.8 mg/l

Mortality

Methyl isobutyl ketone LC 50 (Fathead minnow (Pimephales promelas), 96 h): 496 - 514 mg/l

Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Calcium salt LC 50 (Water flea (Daphnia magna), 24 h): > 1,970 mg/l Mortality

LC 50 (Water flea (Ceriodaphnia dubia), 24 h): > 1,940 mg/l Mortality LC 50 (Water flea (Ceriodaphnia dubia), 48 h): > 1,970 mg/l Mortality LC 50 (Water flea (Ceriodaphnia dubia), 48 h): > 1,910 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Toluene LC 50 (Water flea (Daphnia magna), 24 h): 240 - 420 mg/l Mortality

EC 50 (Water flea (Daphnia magna), 48 h): < 9.83 mg/l Intoxication

Methyl isobutyl ketone LC 50 (Water flea (Daphnia magna), 24 h): 4,280 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental

result

White mineral oil NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l QSAR

Petroleum distillates NOAEL (Oncorhynchus mykiss, 28 d): 0.098 mg/l QSAR

Toluene NOAEL (Pimephales promelas, 32 d): 4 mg/l experimental result

Paraffin NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l QSAR

Aluminum oxide NOAEL (Pimephales promelas, 28 d): 4.7 mg/l experimental result

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants



Revision Date: 07/28/2015

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Toluene Green algae (Selenastrum capricornutum), Bioconcentration Factor (BCF):

3,016 (Static)

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Toluene Log Kow: 2.73

Methyl isobutyl ketone Log Kow: 1.31

Mobility in Soil: No data available.

Other Adverse Effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated



Revision Date: 07/28/2015

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u> <u>OSHA hazard(s)</u>

Benzene Blood

respiratory tract irritation Central nervous system

Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

Toluene 1000 lbs.
Methyl isobutyl ketone 5000 lbs.
Benzene 10 lbs.
Methanol 5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

Toluene 1000 lbs.

Methyl isobutyl ketone 5000 lbs.

Benzene 10 lbs.

Methanol 5000 lbs.



Revision Date: 07/28/2015

SARA 311/312 Hazardous Chemical

| Chemical Identity | Threshold Planning Quantity |
|------------------------------|-----------------------------|
| Calcium Carbonate | 500 lbs |
| (Limestone) | |
| Calcium salt | 500 lbs |
| Titanium dioxide | 500 lbs |
| White mineral oil | 500 lbs |
| Petroleum distillates | 500 lbs |
| Toluene | 500 lbs |
| Paraffin | 500 lbs |
| Methyl isobutyl ketone | 500 lbs |
| Aluminum oxide | 500 lbs |
| Crystalline Silica (Quartz)/ | 500 lbs |
| Silica Sand | |

Silica Sand

SARA 313 (TRI Reporting)

Chemical Identity

Toluene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium Carbonate (Limestone)

Calcium salt

Titanium dioxide

White mineral oil

Petroleum distillates

Toluene

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium Carbonate (Limestone)

Calcium salt

Titanium dioxide

White mineral oil

Petroleum distillates

Toluene

Crystalline Silica (Quartz)/ Silica Sand

Benzene



Revision Date: 07/28/2015

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium Carbonate (Limestone)
Calcium salt
Titanium dioxide
White mineral oil
Petroleum distillates
Toluene

US. Rhode Island RTK Chemical Identity

Toluene

Other Regulations:

Regulatory VOC (less water 57 g/l and exempt solvent):

VOC Method 310: 2.61 %

Inventory Status:

Australia AICS: One or more components in this product are

not listed on or exempt from the Inventory.

Canada DSL Inventory List:

One or more components in this product are

not listed on or exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory:

One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory:

One or more components in this product are

not listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are



Revision Date: 07/28/2015

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 07/28/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.