

Revision Date: 10/06/2015

SAFETY DATA SHEET

1. Identification

Material name: DYMONIC 100 ANODIZED ALUMINUM- 30 CTG CS

Material: 965878C323

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants 220 Wicksteed Ave Toronto ON M4H 1G7 CA

Contact person:
Telephone:

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

EH&S Department

1-800-263-6046

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	25.31 %
Acute toxicity, dermal	28.32 %
Acute toxicity, inhalation, vapor	99.98 %
Acute toxicity, inhalation, dust or mist	99.18 %

Environmental Hazards

Acute hazards to the aquatic	Category 2
environment	

Unknown toxicity - Environment

Acute hazards to the aquatic	66.36 %
environment	
Chronic hazards to the aquatic	100 %
environment	

Label Elements

Hazard Symbol:





Revision Date: 10/06/2015

Signal Word: Danger

Hazard Statement: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer. Toxic to aquatic life.

Precautionary Statement:

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate

ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Use personal protective equipment as required.

Response: If inhaled: If breathing is difficult, remove person to fresh air and keep

comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or

concerned: Get medical advice/attention. Specific treatment (see this label).

Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Polyvinyl chloride	9002-86-2	7 - 13%
Calcium Carbonate (Limestone)	1317-65-3	3 - 7%
Xylene	1330-20-7	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Ethylbenzene	100-41-4	0.5 - 1.5%
Isophorone Diisocyanate	4098-71-9	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures



Revision Date: 10/06/2015

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation: Call a physician or poison control center immediately. If breathing stops,

provide artificial respiration. Move to fresh air. If breathing is difficult, give

oxygen.

Skin Contact: If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly

clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an

allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.



Revision Date: 10/06/2015

Methods and material for containment and cleaning

up:

Collect spillage in containers, seal securely and deliver for disposal

according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Ventilate well, avoid breathing vapors. Use approved respirator if air

contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and

clothing. Wash hands thoroughly after handling.

Conditions for safe storage,

including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
			(02 2006)
Calcium carbonate -	PEL	5 mg/m3	
Respirable fraction.			Contaminants (29 CFR 1910.1000)
Dolugiout oblorido	TWA	1 m a/m	(02 2006) US. ACGIH Threshold Limit Values
Polyvinyl chloride - Respirable fraction.	IVVA	1 mg/m3	(2011)
Polyvinyl chloride - as	TWA	1 ppm	US. OSHA Specifically Regulated
vinyl chloride monomer			Substances (29 CFR 1910.1001-
		_	1050) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated
			Substances (29 CFR 1910.1001-
		0.5	1050) (02 2006)
	OSHA_A	0.5 ppm	US. OSHA Specifically Regulated
	СТ		Substances (29 CFR 1910.1001- 1050) (02 2006)
Polyvinyl chloride -	PEL	5 mg/m3	3 US. OSHA Table Z-1 Limits for Air
Respirable fraction.			Contaminants (29 CFR 1910.1000)
			(02 2006)
Polyvinyl chloride -	PEL	15 mg/m3	
Total dust.			Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions	,
		of particles	,



			per cubic	
			foot of air	
Polyvinyl chloride -	TWA		15 millions	US. OSHA Table Z-3 (29 CFR
Respirable fraction.			of particles	1910.1000) (2000)
			per cubic	
			foot of air	
Polyvinyl chloride -	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR
Total dust.				1910.1000) (2000)
Polyvinyl chloride -	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR
Respirable fraction.				1910.1000) (2000)
Calcium Carbonate	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air
(Limestone) - Total				Contaminants (29 CFR 1910.1000)
dust.	551		- , ,	(02 2006)
Calcium Carbonate	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air
(Limestone) -				Contaminants (29 CFR 1910.1000)
Respirable fraction.	77.47.4	400		(02 2006)
Xylene	TWA	100 ppm		US. ACGIH Threshold Limit Values
		450		(2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values
		400	405	(2011)
	PEL	100 ppm	435	US. OSHA Table Z-1 Limits for Air
			mg/m3	Contaminants (29 CFR 1910.1000)
Coloium avida	TWA		2 m a/m 2	(02 2006)
Calcium oxide	IVVA		2 mg/m3	US. ACGIH Threshold Limit Values
			E m a/m 2	(2011) US. OSHA Table Z-1 Limits for Air
	PEL		5 mg/m3	
				Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA		10 mg/m3	US. ACGIH Threshold Limit Values
Titaliium dioxide	1007		10 mg/m3	(2011)
Titanium dioxide - Total	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air
dust.	'		10 1119/1110	Contaminants (29 CFR 1910.1000)
adot.				(02 2006)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values
,				(2011)
	PEL	100 ppm	435	US. OSHA Table Z-1 Limits for Air
			mg/m3	Contaminants (29 CFR 1910.1000)
			J	(02 2006)
Isophorone	TWA	0.005 ppm		US. ACGIH Threshold Limit Values
Diisocyanate				(2011)
Hydrotreated heavy	TWA		5 mg/m3	US. ACGIH Threshold Limit Values
naphthenic distillate -			· ·	(03 2014)
Inhalable fraction.				
Hydrotreated heavy	PEL	500 ppm	2,000	US. OSHA Table Z-1 Limits for Air
naphthenic distillate			mg/m3	Contaminants (29 CFR 1910.1000)
				(02 2006)
Hydrotreated heavy	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air
naphthenic distillate -				Contaminants (29 CFR 1910.1000)
Mist.				(02 2006)
Stearic acid	TWA		10 mg/m3	US. ACGIH Threshold Limit Values
				(2011)
Dibutyl tin dilaurate - as	STEL		0.2 mg/m3	US. ACGIH Threshold Limit Values
Sn				(2011)
	TWA		0.1 mg/m3	US. ACGIH Threshold Limit Values
				(2011)
	PEL		0.1 mg/m3	US. OSHA Table Z-1 Limits for Air



Contaminants (29 CFR 1910.1000)
(02 2006)

Chemical name	type	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)



Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	150 ppm	651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)



Calcium oxide	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA		2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Ethylbenzene	TWA	20 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	STEL	125 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWAEV	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethylbenzene	TWA	100 ppm	434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	125 ppm	543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational



Revision Date: 10/06/2015

				Health and Safety Regulation 296/97,
Isophorone Diisocyanate	TWAEV	0.005 ppm		as amended) (07 2007) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.



Revision Date: 10/06/2015

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists,

mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves,

footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific

information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level

(in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter.

cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: solid
Form: Paste
Color: Gray
Odor: Mild

Odor threshold:

pH:

No data available.

Evaporation rate: Slower than n-Butyl Acetate

Flammability (solid, gas): No
Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and



Revision Date: 10/06/2015

in the bottom of containers.

Relative density: 1.3297

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
Viscosity:
No data available.
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g.

nitric acid, peroxides and chromates). Strong bases. Water, moisture.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes mild skin irritation. May cause

an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 45,084.51 mg/kg

Dermal

Product: ATEmix: 4,958.43 mg/kg

Inhalation

Product: No data available.



Revision Date: 10/06/2015

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate in vivo (Rabbit, 24 - 72 hrs): Not irritating

Xylene in vivo (Rabbit, 24 hrs): Moderately irritating

Calcium oxide in vivo (Rabbit, 1 hrs): Irritating

Titanium dioxide in vivo (Rabbit, 24 - 72 hrs): Not irritating

Ethylbenzene Irritating

Isophorone in vivo (Rabbit, 24 - 72 hrs): Category 1

Diisocyanate

Hydrotreated heavy naphthenic distillate

in vivo (Rabbit, 24 hrs): Not irritating

Stearic acid in vivo (Rabbit, 27 - 72 hrs): Not irritating

Dibutyl tin dilaurate in vivo (Rabbit, 24 hrs): Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

Ethylbenzene Overall evaluation: Possibly carcinogenic to humans.

Hydrotreated heavy Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

naphthenic distillate evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy Known To Be Human Carcinogen.

naphthenic distillate



Revision Date: 10/06/2015

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Calcium carbonate LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 56,000 mg/l

Mortality

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Titanium dioxide LC 50 (Mummichog (Fundulus heteroclitus), 96 h): > 1,000 mg/l Mortality

Ethylbenzene LC 50 (Bluegill (Lepomis macrochirus), 24 h): 70 - 149 mg/l Mortality

LC 50 (Bluegill (Lepomis macrochirus), 24 h): 112 - 170 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 113 - 162 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 24 h): 66 - 276 mg/l Mortality

LC 50 (Rainbow trout, donaldson trout (Oncorhynchus mykiss), 24 h): 11 - 18

mg/I Mortality



Revision Date: 10/06/2015

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Xylene LC 50 (Water flea (Daphnia magna), 24 h): > 100 - 1,000 mg/l Mortality

Titanium dioxide EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Ethylbenzene EC 50 (Water flea (Daphnia magna), 24 h): 1.47 - 2.18 mg/l Intoxication

EC 50 (Water flea (Daphnia magna), 24 h): 1.51 - 2.14 mg/l Intoxication EC 50 (Water flea (Daphnia magna), 24 h): 1.63 - 2.28 mg/l Intoxication

EC 50 (Water flea (Daphnia magna), 24 h): 2.2 mg/l Intoxication

EC 50 (Water flea (Daphnia magna), 24 h): 1.53 - 3.17 mg/l Intoxication

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental

result

Hydrotreated heavy

naphthenic distillate

NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)



Revision Date: 10/06/2015

Product: No data available.

Specified substance(s):

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Stearic acid Log Kow: 8.23

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in Soil: No data available.

Other Adverse Effects: Toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.



Revision Date: 10/06/2015

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity OSHA hazard(s)

Polyvinyl chloride Blood

Liver Cancer Flammability

Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

Xylene 100 lbs.
Ethylbenzene 1000 lbs.
Toluene 1000 lbs.
Dioctyl phthalate 100 lbs.
Methanol 5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

Reportable

<u>Chemical Identity</u> <u>quantity</u> <u>Threshold Planning Quantity</u>

Isophorone Diisocyanate 500 lbs. 500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

Xylene 100 lbs.

Diisodecyl phthalate

Ethylbenzene 1000 lbs.

Isophorone Diisocyanate

Toluene 1000 lbs.

Diisodecyl phthalate

(mixed Is)

Dioctyl phthalate 100 lbs. Methanol 5000 lbs.



Revision Date: 10/06/2015

SARA 311/312 Hazardous Chemical

<u>Che</u>	mical Identity	Threshold Planning Quantity
Isop	horone Diisocyanate	500lbs
Calc	cium carbonate	500 lbs
Poly	vinyl chloride	500 lbs
Calc	cium Carbonate	500 lbs
(Lim	estone)	
Xyle	ene	500 lbs
Calc	cium oxide	500 lbs
Titaı	nium dioxide	500 lbs
Ethy	/lbenzene	500 lbs
Hyd	rotreated heavy	500 lbs
napl	nthenic distillate	
Stea	aric acid	500 lbs
Dibu	ıtyl tin dilaurate	500 lbs

SARA 313 (TRI Reporting)

Chemical Identity

Xylene

Ethylbenzene

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium carbonate

Polyvinyl chloride

Calcium Carbonate (Limestone)

Xylene

Calcium oxide

Titanium dioxide

Ethylbenzene

Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium carbonate

Calcium Carbonate (Limestone)

Xylene

Calcium oxide

Titanium dioxide

Isophorone Diisocyanate

Dioctyl phthalate

Crystalline Silica (Quartz)/ Silica Sand



Revision Date: 10/06/2015

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Calcium carbonate
Calcium Carbonate (Limestone)
Xylene
Calcium oxide
Titanium dioxide

US. Rhode Island RTK

Chemical Identity

Xylene

Other Regulations:

Regulatory VOC (less water 40 g/l and exempt solvent):

VOC Method 310: 3.01 %

Inventory Status:

Australia AICS: One or more components in this product are

not listed on or exempt from the Inventory.

Canada DSL Inventory List:

All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory: All components in this product are listed on or

exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 10/06/2015

Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 10/06/2015

Version #: 1.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.