

SAFETY DATA SHEET

1. Identification

Material name: TREMCO 830 CLEAR

Material: 985800 320

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants

220 Wicksteed Ave

Toronto ON M4H 1G7

CA

Contact person:

EH&S Department

Telephone:

1-800-263-6046

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable solid Category 1

Health Hazards

Serious Eye Damage/Eye Irritation Category 2B

Carcinogenicity Category 2

Toxic to reproduction Category 2

Unknown toxicity - Health

Acute toxicity, oral 37.47 %

Acute toxicity, dermal 37.47 %

Acute toxicity, inhalation, vapor 99.64 %

Acute toxicity, inhalation, dust
or mist 99.38 %

Environmental Hazards

Acute hazards to the aquatic
environment Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic
environment 64 %

Chronic hazards to the aquatic
environment 100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable solid.
Causes eye irritation.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. In case of fire: Use... to extinguish.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|-------------------|------------|-------------------------|
|-------------------|------------|-------------------------|

| | | |
|--------------------------|-----------|----------|
| Xylene | 1330-20-7 | 15 - 40% |
| Ethylbenzene | 100-41-4 | 5 - 10% |
| Toluene | 108-88-3 | 0.1 - 1% |
| Butylated hydroxytoluene | 128-37-0 | 0.1 - 1% |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Move to fresh air.
- Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

| | |
|---|--|
| Personal precautions, protective equipment and emergency procedures: | Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). |
| Methods and material for containment and cleaning up: | Collect spillage in containers, seal securely and deliver for disposal according to local regulations. |
| Notification Procedures: | In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. |
| Environmental Precautions: | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. |

7. Handling and storage

| | |
|--|--|
| Precautions for safe handling: | Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. |
| Conditions for safe storage, including any incompatibilities: | Store locked up. Store in a cool place. |

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | Type | Exposure Limit Values | Source |
|-------------------|------|-------------------------------|--|
| Xylene | STEL | 150 ppm 655 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | REL | 100 ppm 435 mg/m ³ | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | STEL | 150 ppm 655 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 100 ppm 435 mg/m ³ | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 100 ppm 435 mg/m ³ | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) |
| | STEL | 150 ppm 655 mg/m ³ | US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) |

| | | | |
|--|-----------|-------------------|--|
| | ST ESL | 350 µg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | ST ESL | 80 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | AN ESL | 42 ppb | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | AN ESL | 180 µg/m3 | US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011) |
| | STEL | 150 ppm 655 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | Ceiling | 300 ppm | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | TWA PEL | 100 ppm 435 mg/m3 | US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010) |
| | TWA | 100 ppm | US. ACGIH Threshold Limit Values (2011) |
| | STEL | 150 ppm | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 100 ppm 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Ethylbenzene | TWA | 20 ppm | US. ACGIH Threshold Limit Values (2011) |
| | PEL | 100 ppm 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Toluene | TWA | 20 ppm | US. ACGIH Threshold Limit Values (2011) |
| | TWA | 200 ppm | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | Ceiling | 300 ppm | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | MAX. CONC | 500 ppm | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| Butylated hydroxytoluene - Inhalable fraction and vapor. | TWA | 2 mg/m3 | US. ACGIH Threshold Limit Values (2011) |

| Chemical name | Type | Exposure Limit Values | Source |
|---------------|------|-----------------------|---|
| Xylene | TWA | 100 ppm 434 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| | STEL | 150 ppm 651 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| Xylene | TWA | 100 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | STEL | 150 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Xylene | TWA | 100 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | STEL | 150 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Xylene | STEL | 150 ppm 651 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

| | | | |
|--------------|------|-------------------|---|
| Ethylbenzene | TWA | 20 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Ethylbenzene | TWA | 20 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| Ethylbenzene | STEL | 125 ppm 543 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| | TWA | 100 ppm 434 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |
| Toluene | TWA | 20 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Toluene | TWA | 20 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Toluene | TWA | 50 ppm 188 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017) |

Biological Limit Values

| Chemical Identity | Exposure Limit Values | Source |
|--|--------------------------------|---------------------|
| Xylene (Methylhippuric acids: Sampling time: End of shift.) | 1.5 g/g (Creatinine in urine) | ACGIH BEI (03 2013) |
| Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.) | 0.15 g/g (Creatinine in urine) | ACGIH BEI (02 2014) |
| Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.) | 0.3 mg/g (Creatinine in urine) | ACGIH BEI (03 2013) |
| Toluene (toluene: Sampling time: Prior to last shift of work week.) | 0.02 mg/l (Blood) | ACGIH BEI (03 2013) |
| Toluene (toluene: Sampling time: End of shift.) | 0.03 mg/l (Urine) | ACGIH BEI (03 2013) |

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

- General information:** Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
- Eye/face protection:** Wear goggles/face shield.
- Skin Protection**
- Hand Protection:** Use suitable protective gloves if risk of skin contact.
- Other:** No data available.

| | |
|--------------------------------|--|
| Respiratory Protection: | In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor. |
| Hygiene measures: | Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. |

9. Physical and chemical properties

Appearance

| | |
|--|---|
| Physical state: | solid |
| Form: | Paste |
| Color: | Colorless |
| Odor: | Strong petroleum/solvent |
| Odor threshold: | No data available. |
| pH: | No data available. |
| Melting point/freezing point: | No data available. |
| Initial boiling point and boiling range: | No data available. |
| Flash Point: | No data available. |
| Evaporation rate: | Slower than Ether |
| Flammability (solid, gas): | Yes |
| Upper/lower limit on flammability or explosive limits | |
| Flammability limit - upper (%): | No data available. |
| Flammability limit - lower (%): | No data available. |
| Explosive limit - upper (%): | No data available. |
| Explosive limit - lower (%): | No data available. |
| Vapor pressure: | No data available. |
| Vapor density: | Vapors are heavier than air and may travel along the floor and in the bottom of containers. |
| Relative density: | 0.92 |
| Solubility(ies) | |
| Solubility in water: | Insoluble in water |
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | No data available. |
| Auto-ignition temperature: | No data available. |
| Decomposition temperature: | No data available. |
| Viscosity: | No data available. |

10. Stability and reactivity

| | |
|----------------------------|---|
| Reactivity: | No data available. |
| Chemical Stability: | Material is stable under normal conditions. |

| | |
|--|---|
| Possibility of hazardous reactions: | No data available. |
| Conditions to avoid: | Heat, sparks, flames. |
| Incompatible Materials: | Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). |
| Hazardous Decomposition Products: | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. |

11. Toxicological information

Information on likely routes of exposure

| | |
|----------------------|---|
| Inhalation: | In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes. |
| Skin Contact: | Causes mild skin irritation. |
| Eye contact: | Causes eye irritation. |
| Ingestion: | May be ingested by accident. Ingestion may cause irritation and malaise. |

Symptoms related to the physical, chemical and toxicological characteristics

| | |
|----------------------|--------------------|
| Inhalation: | No data available. |
| Skin Contact: | No data available. |
| Eye contact: | No data available. |
| Ingestion: | No data available. |

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

| | |
|---|--|
| Oral Product: | ATEmix: 7,249.48 mg/kg |
| Dermal Product: | ATEmix: 12,753.13 mg/kg |
| Inhalation Product: | Not classified for acute toxicity based on available data. |
| Specified substance(s): Toluene | LC 50 (Rat): 25.7 mg/l |

| | |
|--|--------------------|
| Repeated dose toxicity Product: | No data available. |
|--|--------------------|

Skin Corrosion/Irritation**Product:** No data available.**Specified substance(s):**

| | |
|--------------------------|---|
| Xylene | in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study |
| Toluene | in vivo (Rabbit): Irritating Experimental result, Key study |
| Butylated hydroxytoluene | in vivo (Rabbit): Not irritant Experimental result, Key study |

Serious Eye Damage/Eye Irritation**Product:** No data available.**Specified substance(s):**

| | |
|--------------------------|---------------------------------------|
| Xylene | Rabbit, 24 hrs: Moderately irritating |
| Ethylbenzene | Rabbit, 7 d: Slightly irritating |
| Toluene | Rabbit, 24 - 72 hrs: Not irritating |
| Butylated hydroxytoluene | Rabbit, 24 - 72 hrs: Not irritating |

Respiratory or Skin Sensitization**Product:** No data available.**Carcinogenicity****Product:** Suspected of causing cancer.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

| | |
|--------------|--|
| Ethylbenzene | Overall evaluation: Possibly carcinogenic to humans. |
|--------------|--|

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity

Product: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Xylene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality

Ethylbenzene LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality

Toluene LC 50 (Fathead minnow (Pimephales promelas), 96 h): 20.5 - 23.8 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Ethylbenzene EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

| | |
|--------------------------|--|
| Toluene | LC 50 (Water flea (Daphnia magna), 24 h): 240 - 420 mg/l Mortality |
| Butylated hydroxytoluene | EC 50 (Water flea (Daphnia pulex), 48 h): 1.44 mg/l Intoxication |

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

| | |
|---------|--|
| Toluene | LOAEL (Oncorhynchus kisutch, 40 d): 2.77 mg/l Experimental result, Key study NOAEL (Pimephales promelas, 32 d): 4 mg/l Experimental result, Supporting study LOAEL (Pimephales promelas, 32 d): 6 mg/l Experimental result, Supporting study NOAEL (Oncorhynchus kisutch, 40 d): 1.39 mg/l Experimental result, Key study |
|---------|--|

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

| | |
|---------|--|
| Toluene | Green algae (Selenastrum capricornutum), Bioconcentration Factor (BCF): 3,016 (Static) |
|---------|--|

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

| | |
|--------------|----------------------|
| Xylene | Log Kow: 3.12 - 3.20 |
| Ethylbenzene | Log Kow: 3.15 |
| Toluene | Log Kow: 2.73 |

Mobility in soil: No data available.
Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging: No data available.

14. Transport information

TDG:

UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Xylene), 4.1, PG II

CFR / DOT:

UN3175, Solids containing flammable liquid, n.o.s. (Xylene), 4.1, PG II

IMDG:

UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Xylene), 4.1, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)
None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | 100 lbs. |
| Ethylbenzene | 1000 lbs. |
| Toluene | 1000 lbs. |

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene | 100 lbs. |
| Ethylbenzene | 1000 lbs. |
| Toluene | 1000 lbs. |

SARA 311/312 Hazardous Chemical

| <u>Chemical Identity</u> | <u>Threshold Planning Quantity</u> |
|--------------------------|------------------------------------|
| Xylene | 10000 lbs |
| Ethylbenzene | 10000 lbs |
| Toluene | 10000 lbs |
| Butylated hydroxytoluene | 10000 lbs |

SARA 313 (TRI Reporting)

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene |
| Ethylbenzene |

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene |
| Ethylbenzene |

US. Massachusetts RTK - Substance List

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene |
| Ethylbenzene |

US. Pennsylvania RTK - Hazardous Substances

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene |
| Ethylbenzene |

US. Rhode Island RTK

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene |
| Ethylbenzene |

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 330 g/l

VOC Method 310 : 35.89 %

Inventory Status:

| | |
|--|--|
| Australia AICS: | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada DSL Inventory List: | One or more components in this product are not listed on or exempt from the Inventory. |
| EINECS, ELINCS or NLP: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan (ENCS) List: | One or more components in this product are not listed on or exempt from the Inventory. |
| China Inv. Existing Chemical Substances: | One or more components in this product are not listed on or exempt from the Inventory. |
| Korea Existing Chemicals Inv. (KECI): | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada NDSL Inventory: | One or more components in this product are not listed on or exempt from the Inventory. |
| Philippines PICCS: | One or more components in this product are not listed on or exempt from the Inventory. |
| US TSCA Inventory: | All components in this product are listed on or exempt from the Inventory. |
| New Zealand Inventory of Chemicals: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan ISHL Listing: | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan Pharmacopoeia Listing: | One or more components in this product are not listed on or exempt from the Inventory. |

16. Other information, including date of preparation or last revision

| | |
|-----------------------------|--------------------|
| Revision Date: | 11/30/2018 |
| Version #: | 1.1 |
| Further Information: | No data available. |

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.