

# SAFETY DATA SHEET

## 1. Identification

**Material name:** TREMCO 830 IVORY

**Material:** 985858 320

### Recommended use and restriction on use

**Recommended use:** Sealant

**Restrictions on use:** Not known.

### Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants

220 Wicksteed Ave

Toronto ON M4H 1G7

CA

**Contact person:**

EHS Department

**Telephone:**

1-800-263-6046

**Emergency telephone number:**

1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Physical Hazards

Flammable solid Category 1

#### Health Hazards

Serious Eye Damage/Eye Irritation Category 2B

Carcinogenicity Category 2

Toxic to reproduction Category 2

#### Unknown toxicity - Health

Acute toxicity, oral 32.76 %

Acute toxicity, dermal 34.28 %

Acute toxicity, inhalation, vapor 99.66 %

Acute toxicity, inhalation, dust or mist 99.55 %

#### Environmental Hazards

Acute hazards to the aquatic environment Category 3

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment 65.29 %

Chronic hazards to the aquatic environment 100 %

### Label Elements

**Hazard Symbol:**



**Signal Word:** Danger

**Hazard Statement:** Flammable solid.  
Causes eye irritation.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
Harmful to aquatic life.

**Precautionary Statement:**  
**Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

**Response:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. In case of fire: Use ... to extinguish.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** None.

### 3. Composition/information on ingredients

#### Mixtures

| Chemical Identity        | CAS number | Content in percent (%)* |
|--------------------------|------------|-------------------------|
| Xylene                   | 1330-20-7  | 15 - 40%                |
| Ethylbenzene             | 100-41-4   | 5 - 10%                 |
| Titanium dioxide         | 13463-67-7 | 1 - 5%                  |
| Toluene                  | 108-88-3   | 0.1 - 1%                |
| Butylated hydroxytoluene | 128-37-0   | 0.1 - 1%                |

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

**Ingestion:** Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air.

**Skin Contact:** Wash skin thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention.

**Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

**Most important symptoms/effects, acute and delayed**

**Symptoms:** Respiratory tract irritation.

**Indication of immediate medical attention and special treatment needed**

**Treatment:** Symptoms may be delayed.

**5. Fire-fighting measures**

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

**Suitable (and unsuitable) extinguishing media**

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

**Methods and material for containment and cleaning up:** Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

**7. Handling and storage**

**Precautions for safe handling:** Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment.

**Conditions for safe storage, including any incompatibilities:** Store locked up. Store in a cool place.

**8. Exposure controls/personal protection**

**Control Parameters**

**Occupational Exposure Limits**

| Chemical Identity  | type      | Exposure Limit Values  | Source  |
|--|-----------|------------------------|---|
| Xylene   | TWA       | 100 ppm                | US. ACGIH Threshold Limit Values (2011)                                     |
|  | STEL      | 150 ppm                | US. ACGIH Threshold Limit Values (2011)                                     |
|  | PEL       | 100 ppm      435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Ethylbenzene   | TWA       | 20 ppm                 | US. ACGIH Threshold Limit Values (2011)                                     |
|  | PEL       | 100 ppm      435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Titanium dioxide   | TWA       | 10 mg/m3               | US. ACGIH Threshold Limit Values (2011)                                     |
| Titanium dioxide - Total dust.                           | PEL       | 15 mg/m3               | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Toluene  | TWA       | 20 ppm                 | US. ACGIH Threshold Limit Values (2011)                                     |
|  | TWA       | 200 ppm                | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)                             |
|  | Ceiling   | 300 ppm                | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)                             |
|  | MAX. CONC | 500 ppm                | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)                             |
| Butylated hydroxytoluene - Inhalable fraction and vapor. | TWA       | 2 mg/m3                | US. ACGIH Threshold Limit Values (2011)                                     |

| Chemical name                    | type  | Exposure Limit Values | Source  |
|----------------------------------|-------|-----------------------|---|
| Xylene                           | TWA   | 100 ppm               | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
|                                  | STEL  | 150 ppm               | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Xylene                           | TWAEV | 100 ppm               | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
|                                  | STEL  | 150 ppm               | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Xylene                           | TWA   | 100 ppm<br>434 mg/m3  | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
|                                  | STEL  | 150 ppm<br>651 mg/m3  | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
| Aluminum silicates - Total dust. | TWAEV | 10 mg/m3              | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Ethylbenzene                     | TWA   | 20 ppm                | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Ethylbenzene                     | STEL  | 125 ppm               | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
|                                  | TWAEV | 100 ppm               | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Ethylbenzene                     | TWA   | 100 ppm<br>434 mg/m3  | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
|                                  | STEL  | 125 ppm<br>543 mg/m3  | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |

|   |       |                                 |   |
|---|-------|---------------------------------|---|
| Titanium dioxide - Total dust.          | TWA   | 10 mg/m <sup>3</sup>            | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide - Respirable fraction. | TWA   | 3 mg/m <sup>3</sup>             | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide                        | TWAEV | 10 mg/m <sup>3</sup>            | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Titanium dioxide - Total dust.          | TWA   | 10 mg/m <sup>3</sup>            | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |
| Toluene                                 | TWA   | 20 ppm                          | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Toluene                                 | TWAEV | 20 ppm                          | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)  |
| Toluene                                 | TWA   | 50 ppm<br>188 mg/m <sup>3</sup> | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)  |

### Biological Limit Values

| Chemical Identity  | Exposure Limit Values          | Source              |
|--|--------------------------------|---------------------|
| Xylene (Methylhippuric acids: Sampling time: End of shift.)                                | 1.5 g/g (Creatinine in urine)  | ACGIH BEL (03 2013) |
| Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.) | 0.15 g/g (Creatinine in urine) | ACGIH BEL (02 2014) |
| Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)                          | 0.3 mg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Toluene (toluene: Sampling time: Prior to last shift of work week.)                        | 0.02 mg/l (Blood)              | ACGIH BEL (03 2013) |
| Toluene (toluene: Sampling time: End of shift.)  | 0.03 mg/l (Urine)              | ACGIH BEL (03 2013) |

### Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

**Individual protection measures, such as personal protective equipment**

- General information:** Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
- Eye/face protection:** Wear goggles/face shield.
- Skin Protection**
- Hand Protection:** Use suitable protective gloves if risk of skin contact.
- Other:** No data available.
- Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.

|  |
|--|
| <b>9. Physical and chemical properties</b> |
|--|

**Appearance**

- Physical state:** solid
- Form:** Paste
- Color:** Off-white
- Odor:** Strong petroleum/solvent
- Odor threshold:** No data available.
- pH:** No data available.
- Melting point/freezing point:** No data available.
- Initial boiling point and boiling range:** No data available.
- Flash Point:** No data available.
- Evaporation rate:** Slower than Ether
- Flammability (solid, gas):** Flammable solid.
- Upper/lower limit on flammability or explosive limits**
- Flammability limit - upper (%):** No data available.
- Flammability limit - lower (%):** No data available.
- Explosive limit - upper (%):** No data available.
- Explosive limit - lower (%):** No data available.
- Vapor pressure:** No data available.
- Vapor density:** Vapors are heavier than air and may travel along the floor and in the bottom of containers.
- Relative density:** 0.99
- Solubility(ies)**
- Solubility in water:** Insoluble in water
- Solubility (other):** No data available.
- Partition coefficient (n-octanol/water):** No data available.

|                                   |                    |
|-----------------------------------|--------------------|
| <b>Auto-ignition temperature:</b> | No data available. |
| <b>Decomposition temperature:</b> | No data available. |
| <b>Viscosity:</b>                 | No data available. |

**10. Stability and reactivity**

|  |   |
|--|---|
| <b>Reactivity:</b>                         | No data available.  |
| <b>Chemical Stability:</b>                 | Material is stable under normal conditions.   |
| <b>Possibility of Hazardous Reactions:</b> | No data available.  |
| <b>Conditions to Avoid:</b>                | Heat, sparks, flames.   |
| <b>Incompatible Materials:</b>             | Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).                |
| <b>Hazardous Decomposition Products:</b>   | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. |

**11. Toxicological information****Information on likely routes of exposure**

|                      |   |
|----------------------|---|
| <b>Ingestion:</b>    | May be ingested by accident. Ingestion may cause irritation and malaise.                      |
| <b>Inhalation:</b>   | In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes. |
| <b>Skin Contact:</b> | Causes mild skin irritation.  |
| <b>Eye contact:</b>  | Causes eye irritation.  |

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)**

|                            |                        |
|----------------------------|------------------------|
| <b>Oral Product:</b>       | ATEmix: 8,418.31 mg/kg |
| <b>Dermal Product:</b>     | ATEmix: 15,443.5 mg/kg |
| <b>Inhalation Product:</b> | No data available.     |

|  |                    |
|--|--------------------|
| <b>Repeated dose toxicity Product:</b> | No data available. |
|--|--------------------|

|   |                    |
|---|--------------------|
| <b>Skin Corrosion/Irritation Product:</b> | No data available. |
|---|--------------------|



**Serious Eye Damage/Eye Irritation**

**Product:** No data available.

**Specified substance(s):**

|                          |   |
|--------------------------|---|
| Xylene                   | in vivo (Rabbit, 24 hrs): Moderately irritating |
| Ethylbenzene             | Irritating                                      |
| Titanium dioxide         | in vivo (Rabbit, 24 - 72 hrs): Not irritating   |
| Toluene                  | in vivo (Rabbit, 24 - 72 hrs): Not irritating   |
| Butylated hydroxytoluene | in vivo (Rabbit, 24 - 72 hrs): Not irritating   |

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Carcinogenicity**

**Product:** Suspected of causing cancer.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

|                  |  |
|------------------|--|
| Ethylbenzene     | Overall evaluation: Possibly carcinogenic to humans. |
| Titanium dioxide | Overall evaluation: Possibly carcinogenic to humans. |

**US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**

**Product:** No data available.

**In vivo**

**Product:** No data available.

**Reproductive toxicity**

**Product:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

|                                   |
|-----------------------------------|
| <b>12. Ecological information</b> |
|-----------------------------------|

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

|                          |   |
|--------------------------|---|
| Xylene                   | LC 50 (Fathead minnow ( <i>Pimephales promelas</i> ), 96 h): 13.41 mg/l Mortality   |
| Ethylbenzene             | LC 50 (Bluegill ( <i>Lepomis macrochirus</i> ), 24 h): 70 - 149 mg/l Mortality<br>LC 50 (Bluegill ( <i>Lepomis macrochirus</i> ), 24 h): 112 - 170 mg/l Mortality<br>LC 50 (Bluegill ( <i>Lepomis macrochirus</i> ), 24 h): 113 - 162 mg/l Mortality<br>LC 50 (Bluegill ( <i>Lepomis macrochirus</i> ), 24 h): 66 - 276 mg/l Mortality<br>LC 50 (Rainbow trout, donaldson trout ( <i>Oncorhynchus mykiss</i> ), 24 h): 11 - 18 mg/l Mortality |
| Titanium dioxide         | LC 50 (Mummichog ( <i>Fundulus heteroclitus</i> ), 96 h): > 1,000 mg/l Mortality  |
| Toluene                  | LC 50 (Fathead minnow ( <i>Pimephales promelas</i> ), 96 h): 71.7 - 82.8 mg/l Mortality   |
| Butylated hydroxytoluene | LC 50 (Medaka, high-eyes ( <i>Oryzias latipes</i> ), 48 h): 17.5 mg/l Mortality   |

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

|                          |  |
|--------------------------|--|
| Xylene                   | LC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): > 100 - 1,000 mg/l Mortality  |
| Ethylbenzene             | EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 1.47 - 2.18 mg/l Intoxication<br>EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 1.51 - 2.14 mg/l Intoxication<br>EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 1.63 - 2.28 mg/l Intoxication<br>EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 2.2 mg/l Intoxication<br>EC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 1.53 - 3.17 mg/l Intoxication |
| Titanium dioxide         | EC 50 (Water flea ( <i>Daphnia magna</i> ), 48 h): > 1,000 mg/l Intoxication   |
| Toluene                  | LC 50 (Water flea ( <i>Daphnia magna</i> ), 24 h): 240 - 420 mg/l Mortality<br>EC 50 (Water flea ( <i>Daphnia magna</i> ), 48 h): < 9.83 mg/l Intoxication   |
| Butylated hydroxytoluene | EC 50 (Water flea ( <i>Daphnia pulex</i> ), 48 h): 1.44 mg/l Intoxication  |

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

|                  |  |
|------------------|--|
| Xylene           | NOAEL (Oncorhynchus mykiss, 56 d): > 1.3 mg/l experimental result            |
| Titanium dioxide | LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental result |
| Toluene          | NOAEL (Pimephales promelas, 32 d): 4 mg/l experimental result                |

**Aquatic Invertebrates****Product:** No data available.**Toxicity to Aquatic Plants****Product:** No data available.**Persistence and Degradability****Biodegradation****Product:** No data available.**BOD/COD Ratio****Product:** No data available.**Bioaccumulative Potential****Bioconcentration Factor (BCF)****Product:** No data available.**Specified substance(s):**

Toluene Green algae (Selenastrum capricornutum), Bioconcentration Factor (BCF): 3,016 (Static)

**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Toluene Log Kow: 2.73

**Mobility in Soil:** No data available.**Other Adverse Effects:** Harmful to aquatic organisms.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.

**14. Transport information**

**TDG:**

UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Xylene), 4.1, PG II

**CFR / DOT:**

UN3175, Solids containing flammable liquid, n.o.s. (Xylene), 4.1, PG II

**IMDG:**

UN3175, SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Xylene), 4.1, PG II

**Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

**15. Regulatory information**

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

| <u>Chemical Identity</u> | <u>OSHA hazard(s)</u>  |
|--------------------------|--|
| Benzene                  | Blood<br>respiratory tract irritation<br>Central nervous system<br>Flammability<br>Cancer<br>Skin<br>Aspiration<br>Eye |

**CERCLA Hazardous Substance List (40 CFR 302.4):**

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene                   | 100 lbs.                   |
| Ethylbenzene             | 1000 lbs.                  |
| Toluene                  | 1000 lbs.                  |
| Benzene                  | 10 lbs.                    |

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

**SARA 304 Emergency Release Notification**

| <u>Chemical Identity</u> | <u>Reportable quantity</u> |
|--------------------------|----------------------------|
| Xylene                   | 100 lbs.                   |
| Ethylbenzene             | 1000 lbs.                  |
| Toluene                  | 1000 lbs.                  |
| Copper phthalocyanine    |                            |
| Benzene                  | 10 lbs.                    |

**SARA 311/312 Hazardous Chemical**

| <u>Chemical Identity</u> | <u>Threshold Planning Quantity</u> |
|--------------------------|------------------------------------|
| Xylene                   | 500 lbs                            |
| Ethylbenzene             | 500 lbs                            |
| Titanium dioxide         | 500 lbs                            |
| Toluene                  | 500 lbs                            |
| Butylated hydroxytoluene | 500 lbs                            |

**SARA 313 (TRI Reporting)**

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene                   |
| Ethylbenzene             |

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

None present or none present in regulated quantities.

**US State Regulations**

**US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

**US. New Jersey Worker and Community Right-to-Know Act**

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene                   |
| Ethylbenzene             |
| Titanium dioxide         |

**US. Massachusetts RTK - Substance List**

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene                   |
| Ethylbenzene             |
| Titanium dioxide         |

**US. Pennsylvania RTK - Hazardous Substances**

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene                   |
| Ethylbenzene             |
| Titanium dioxide         |

**US. Rhode Island RTK**

| <u>Chemical Identity</u> |
|--------------------------|
| Xylene                   |
| Ethylbenzene             |

**Other Regulations:**

|  |         |
|--|---------|
| <b>Regulatory VOC (less water and exempt solvent):</b> | 330 g/l |
| <b>VOC Method 310:</b>                                 | 33.35 % |

**Inventory Status:**

|  |  |
|--|--|
| Australia AICS:                          | One or more components in this product are not listed on or exempt from the Inventory. |
| EINECS, ELINCS or NLP:                   | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan (ENCS) List:                       | One or more components in this product are not listed on or exempt from the Inventory. |
| China Inv. Existing Chemical Substances: | One or more components in this product are not listed on or exempt from the Inventory. |
| Korea Existing Chemicals Inv. (KECI):    | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada NDSL Inventory:                   | One or more components in this product are not listed on or exempt from the Inventory. |
| Philippines PICCS:                       | One or more components in this product are not listed on or exempt from the Inventory. |
| US TSCA Inventory:                       | One or more components in this product are not listed on or exempt from the Inventory. |
| New Zealand Inventory of Chemicals:      | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan ISHL Listing:                      | One or more components in this product are not listed on or exempt from the Inventory. |
| Japan Pharmacopoeia Listing:             | One or more components in this product are not listed on or exempt from the Inventory. |
| Canada DSL Inventory List:               | All components in this product are listed on or exempt from the Inventory.             |

|  |
|--|
| <b>16. Other information, including date of preparation or last revision</b> |
|--|

**Revision Date:** 08/13/2015

**Version #:** 1.0

**Further Information:**

No data available.

**Disclaimer:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.