

Spectrem® Simple Seal™

Extruded Silicone Bridge

Product Description

Spectrem® Simple Seal™ is an ultra-low modulus preformed silicone tape extrusion specifically designed to have high elongation properties that can be bonded to a wide range of substrates with Tremco Spectrem 1 or Spectrem 2 to provide a waterproof seal.

Basic Uses

Tremco Spectrem Simple Seal is designed for both new construction and restoration work involving window perimeter and EIFS joints, parapet walls, skylights, aluminum window seals, transition seals, curtain wall joints, sheet metal roof joints and other lap joints.

For use on substrates other than EIFS, concrete, glass and metal, contact Tremco Technical Services for recommendations and approval.

Packaging

100 Ft. rolls

Standard Sizes

1.5", 2", and 3" Widths.

Custom sizes are available upon request.

Standard Colors

Bronze, Off White, Aluminum Stone, Black and White
Custom colors are available upon request.

Installation

Surface Preparation:

The joint interface must be sound, clean and dry. Use a nonmetallic stiff-bristle brush for cleaning EIFS substrates. Remove all dirt and dust from the joint surface. Other porous and non-porous substrates may require a thorough wire brushing, grinding, sandblasting, solvent washing and primer.

Masking

Apply masking tape to the substrate surface at the width edges of the Spectrem Simple Seal to provide a clean edge.

Application

Select the Spectrem Simple Seal width material a minimum of 3/4" wider than the joint. Apply Spectrem 1 or Spectrem 2 to each side of the joint in approximately 1/4" diameter beads. Immediately embed the Spectrem Simple Seal into the wet sealant using a roller. Apply consistent pressure to ensure uniform contact. Remove masking tape and any excess sealant.

Detailed application instructions are available from Tremco Technical Services or www.tremcosealants.com.

Availability

Immediately available from all authorized Tremco Silicone Distributors.

Maintenance

Damaged Spectrem Simple Seal can be repaired. Contact your local Tremco Representative or Technical Services for repair procedures.

Limitations

- Do not apply on damp or contaminated surfaces.
- Do not use clear Spectrem 2 for application of Spectrem Simple Seal.

Warranty

Tremco warrants its products to be free of defects in materials, but makes no warranty as to appearance or color. Since method of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE. Tremco's sole obligation shall be at, its opinion, to replace or to refund the purchase price of the quantity of product proved to be defective and Tremco shall not be liable for any loss or damage.

