



- TREMDRAIN AS SPECIFIED, APPLIED ABOVE WATERTABLE ONLY
- PARASTICK N DRY OVER STAPLED SEAMS
- PARASEAL GM/LG TARGET SHEET TO BE SECURED WITH NAILS AND WASHERS AT THE CORNERS AND WITH BOX CROWN STAPLES EVERY 3" O.C. THEREAFTER
- PARAMASTIC OR DYMONIC 100
- LINK-SEAL, BY OTHERS
- PARASTICK N DRY OR SUPERSTOP WRAPPED AROUND PIPE AND SECURED WITH TIE-WIRE
- PARA JT TAPE
- PARASEAL GM/LG, BENTONITE SIDE FACING INSTALLER

NOTES: PARASEAL PRODUCTS REQUIRE A MIN 24 PSF OF COMPACTION/CONFINEMENT IN ORDER TO FUNCTION AS DESIGNED.

The architecture, engineering, and design of the project using the Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Tremco to ensure you have the most recent version.

**Paraseal GM/LG 20 Mil Blindside Walls**



Detail: Paraseal GM/LG 20 Mil at Pipe Penetration with Link-Seal				File Name:
Drawn by: KAB	Checked by: WH	Scale: NTS	Date: 3/29/2022	BSW-GM20-P-02
<a href="http://www.tremcocpg.com">www.tremcocpg.com</a>				

