



- NOTES:**
- Apply ExoAir Primer to all exposed gypsum core prior to application of membrane
  - Slope to the exterior 1/8" per 12"
  - Install reinforcing mesh with 70 wet mils of ExoAir 230, completely covering reinforcing mesh

See [seurockexoair.com](http://seurockexoair.com) for the most up-to-date product information

*This detail is intended for conceptual purposes only. Must be reviewed by a project/design professional*

*The following trademarks used herein are owned by USG Corporation or its subsidiaries: SECUROCK, USG, USG in stylized letters. The following trademarks used herein are owned by Tremco Incorporated or its subsidiaries: Tremco, ExoAir, Spectrem, Dymonic, Proglaze, Vulkem.*

 <p><b>PERFORMANCE BUILT IN</b> www.seurockexoair.com</p>	<p><b>United States Gypsum Company</b> 550 West Adams Street Chicago, IL 60661</p> <p>USG Technical &amp; Customer Support: 800.USG.4YOU (874-4968)</p>	<p><b>Tremco Commercial Sealants &amp; Waterproofing</b> 3735 Green Road Beachwood, OH 44122</p> <p>Tremco Technical Support: 866.209.2404</p>	<p>SECUROCK® ExoAir® 430 Panel</p>		<p>File Name: <b>12789</b></p>	<p>Rev # <b>00</b></p>
			<p>Project: Detail: <b>Offset Application</b></p>	<p>Drawn by: <b>KAB</b></p>		