

## CERTIFICATION LETTER

We certify that ExoAir Termination Mastic has been tested against the following ASTM Standards and does conform to the typical specification requirements.

### TYPICAL PHYSICAL PROPERTIES

<b>Property</b>	<b>Typical Value</b>	<b>Test Method</b>
Asbestos content	None	EPA/600/R-93/116
VOC*300 g/L, max		ASTM D 3960-89
Viscosity @ 25°C (77°F)	600-2,000 Pa•s (600K-2,000K cP)	ASTM D 2196-86
Density @ 25°C (77°F)	8.1 lb/gal (970 kg/m <sup>3</sup> )	ASTM D 1475-85
Nonvolatile matter	70%	ASTM D 4586-86
Tensile strength @ 25°C (77°F)	207-690 kPa (30 - 100 psi) @ 100% elongation	ASTM D 412-87
Elongation@ 25°C (77°F)	1,000%	ASTM D 412-87
@ -34°C (-30°F)	100%	ASTM D 412-87
Recovery from 500% elongation	90% min.	ASTM D 412-87
Moisture vapor transmission rate	0.42 g/100 in <sup>2</sup> /24 hrs	ASTM F-1249-90
Behavior @ 60°C (140°F) (Sag Resistance)	6 mm (max.) (1/4 in. max.)	ASTM D 4586-86
Flexibility @ -40°C (-40°F)	No cracking	ASTM D-3111-88