

### PRODUCT DESCRIPTION

POWERply® Standard Smooth is a smooth surfaced, modified bitumen sheet used in conjunction with recommended waterproofing membranes as an extremely heavy-duty protection course, primarily in horizontal applications

### BASIC USES

POWERply Standard Smooth sheeting is used as a strong protection course for Tremco hot applied waterproofing membranes.

### AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

### PACKAGING

3' x 56' 8" (0.91 M x 17.3 M) / roll

### LIMITATIONS

- Not to be exposed to solvents, oils, or other contaminants harmful to asphaltic materials.
- Not intended for use with Tremco TREMproof® 201/60 or Tremco TREMproof 250GC cold fluid-applied waterproofing membranes.
- Not intended for UV exposure.

### INSTALLATION

Immediately install POWERply Standard Smooth over the TREMproof 6100 while membrane is still warm and tacky. Adjacent sheets should be overlapped a minimum of 2" (51 mm).

### WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

### TYPICAL PHYSICAL PROPERTIES

| PROPERTY            | VALUES US                                      | VALUES SI                                       |
|---------------------|------------------------------------------------|-------------------------------------------------|
| Composition         | SBS Bitumen Modified                           |                                                 |
| Thickness           | 80 mils (2 mm)                                 | 2 mm                                            |
| Puncture Resistance | 70 lb                                          |                                                 |
| Weight              | 105 lb /roll                                   | 3' x 56' 8" / roll, 170 ft <sup>2</sup> / roll  |
| Dimension           | 3' x 56' 8" / roll, 170 ft <sup>2</sup> / roll | 0.91 M x 17.3 M/roll, 15.7 M <sup>2</sup> /roll |

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

**NOTE:** All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

PSS-DS/0323



Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



[tremcosealants.com](http://tremcosealants.com) | 800.321.7906



*Construction Products Group*

3735 Green Rd. | Beachwood, OH 44122  
800.321.7906 | [tremcocpg.com](http://tremcocpg.com)