

### Product Description

Superstop is a composite waterstop containing expandable, granular bentonite. One edge is layered with a pressure sensitive adhesive.

### Basic Uses

Superstop is used for sealing cold joints in concrete and to prevent water migration through construction joints below grade. Properly installed under compaction, Superstop will stop the passage of water through a static cold joint or between two abutting impermeable surfaces. Superstop is also available in saltwater grade for use in approved brackish water conditions.

### Availability

Immediately available from your local Tremco Sales Representative or Tremco Distributor. For Distributor locations visit [www.tremcosealants.com](http://www.tremcosealants.com).

### Packaging

1" x 1/2" x 20' rolls (25 mm x 13 mm x 6.1 M) 10 rolls/case, 30 cases/pallet  
1" x 3/4" x 13' rolls (25 mm x 19 mm x 4 M) 10 rolls/case, 30 cases/pallet

### Colors

Gray

### Storage

Store in original, undamaged packages in a clean, dry, protected location.

### Limitations

- If ground water is brackish, please contact your local Tremco Sales Representative four weeks prior to a pending application, and provide a water and/or soil sample for testing purposes in order to determine the correct bentonite formula for your project's application.
- Do not apply in standing water or over ice and snow.
- Must be installed a minimum of 2" (51 mm) from face of wall.

### Installation

Penetrations, Corners, Joints, Tie-ins to other building envelope systems: Please consult [www.tremcosealants.com](http://www.tremcosealants.com) for detail drawings and technical bulletins.

Consult your local Tremco Sales Representative or Tremco Technical Service for design specific requirements.

Joint surface where Superstop is to be installed should be troweled smooth. Remove all debris and sweep the surface prior to installation. Install 2" (51 mm) from face of wall.

It is recommended to apply Paraprimer to clean surface prior to adhering Superstop on vertical surfaces. Primer is not required for horizontal surfaces.

Remove release paper to expose adhesive. Butt ends together and fasten using a nail with 1" (25 mm) washer every 12" (30 cm) O.C.

### Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

## TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	US VALUES	SI VALUES
Specific Gravity	ASTM D71	1.75	
Softening Point	ASTM D30	212 °F	100 °C
Flash Point	ASTM D93-97	None	
Application Temperature		0 to 120 °F	-17.8 to 110 °C
Service Temperature		-40 to 230 °F	-40 to 100 °C
Color		Gray	
Tear Strength		70 lb	31.7 kg
Water Flow through a concrete joint with 100' water head	ASTM D751 Method A	No Flow	

0316/SUPERSTOPDS-BG

### Tremco Commercial Sealants & Waterproofing

3735 Green Rd  
Beachwood OH 44122  
216.292.5000 / 800.321.7906

1451 Jacobson Ave  
Ashland OH 44805  
419.289.2050 / 800.321.6357

220 Wicksteed Ave  
Toronto ON M4H1G7  
416.421.3300 / 800.363.3213

1445 Rue de Coulomb  
Boucherville QC J4B 7L8  
514.521.9555

