

### Product Description

TREMGard® Masonry Primer is a water-based, 100% acrylic resin emulsion block filler used as a primer for TREMGard HB Fiber Reinforced, Elastomeric, Acrylic Wall Coatings. Primer is formulated with finely graded texture minerals for exterior above grade applications.

### Basic Uses

TREMGard Masonry Primer is designed for both new construction and restoration work involving brick, block, stone and stucco surfaces.

### Features & Benefits

- Fills pores for a smoother appearance
- Ease application
- Can be sprayed, rolled or brushed
- Textured

### Packaging

5 gal (18.9L) pails.

### Coverage Rates

- 40 - 80 ft<sup>2</sup>/gal (0.98 - 1.96 m<sup>2</sup>/L)

Coverage rates listed are approximate and may differ depending upon surface temperature, porosity of surface and texture of the substrate finish. Any questions regarding drying times, coverage rates and unique application techniques regarding the individual primers should be directed to Tremco Technical Services or your local Tremco Sales Representative.

### Storage

Store at temperatures between 50°F and 90°F (10°C and 32°C).

### Limitations

- Protect from moisture and freezing.
- Do not thin or dilute primers.
- Do not apply to external surfaces if rain is expected within eight hours.
- Do not apply over frozen or frost-filled surfaces.
- Do not apply if temperatures are below 40°F (4°C) or above 100°F (38°C).
- Do not apply to non-absorbent materials such as glass, metal, glazed brick or glazed tile.
- Not for use on traffic bearing surfaces.
- Primer should be topcoated within 24 hours after application. In all cases, consult the Safety Data Sheet before use.
- Not for use in below-grade applications

### Surface Preparation

All surfaces must be sound, clean, dry and free from contamination. New concrete and masonry surfaces shall be a minimum of 28 days cured and shall not have moisture content more than 12% prior to application. Provide an absorptive surface on all substrates, including smooth precast or formed concrete, by abrading the surface. Defective concrete, honeycombs, cracks, cavities and other defects should be routed to sound concrete and patched

using compatible materials, such as approved Tremco Sealants or Euclid repair materials. Tremco recommends that air temperatures be 40 °F (5 °C) or above before applying any primer. If colder weather is imminent, please refer to the Tremco Guide for Cold Weather Applications at [www.tremcosealants.com](http://www.tremcosealants.com).

### Mixing

Primers should be mechanically mixed using a low speed 3/4 in. (19mm) drill with a mixing paddle. Mix thoroughly to a uniform, smooth consistency. Do not aerate the mix.

### Application

- Use heavy-duty spray equipment capable of spraying ceiling texture, plaster or cement-based coatings, or use stiff brushes or rollers.
- When sprayed, bankrolling is required to ensure good uniform contact with the surface.
- Avoid applying to excess which can cause the product to run down the wall or puddle.
- For hand application, use brushes or 3/4 to 1-1/4 in. (19-32mm) nap rollers designated for latex paints.
- Dampen brushes or rollers with water before use.
- Topcoats may be applied 12-24 hours following primer application (at 70°F (21°C), 50% RH).

Detailed application instructions are available from Tremco Technical Services.

### Availability

Availability and cost may be obtained from your local Tremco Field Representative, or by contacting our Customer Service Department in Beachwood, Ohio at 800-321-7906, or Toronto at 800-363-3213.

### Clean-Up

Clean tools and application equipment immediately after use with soap and hot water. Clean overspray or drips while still wet with soap and hot water. Clean glass and metal surfaces before material dries. Dried material may require strong solvents or mechanical abrasion for removal.

### Warranty

Tremco warrants its Products to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase price of the quantity of Tremco Products proven to be defective and Tremco shall not be liable for any loss or damage.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.



0419/ TGHPPRIDS-GL

### Tremco Commercial Sealants & Waterproofing

3735 Green Rd  
Beachwood OH 44122  
216.292.5000 / 800.321.7906

1451 Jacobson Ave  
Ashland OH 44805  
419.289.2050 / 800.321.6357

220 Wicksteed Ave  
Toronto ON M4H1G7  
416.421.3300 / 800.363.3213

1445 Rue de Coulomb  
Boucherville QC J4B 7L8  
514.521.9555

[www.tremcosealants.com](http://www.tremcosealants.com)

Page 1 of 1