

Product Description

TREMprime LV Primer is a solvent-based modified bituminous primer for use in preparing porous and non-porous surfaces for application of Tremco® hot-applied asphaltic fluids.

Basic Uses

TREMprime LV promotes adhesion of Tremco asphaltic hot applied fluids such as TREMproof® 6100. TREMprime LV is a multi-surface purpose primer that can be used on a variety of surfaces, such as concrete, masonry, metal, gypsum, and new or weather bituminous surfaces.

TREMprime LV meets the VOC requirements established for bituminous roof primer category of Architectural Coatings.

Coverage Rate

Approximately 200 – 400 ft²/gal

Packaging

5-gal (18.9 L) pails

Availability

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

Application

Remove all loose dust and foreign surface matter. Surface must be clean and dry prior to application of TREMprime LV.

Priming weathered bituminous surfaces prior to installing new material is good waterproofing practice, however, priming is not a substitute for proper surface preparation, such as sweeping, power washing and repairing unsound surfaces.

TREMprime LV is applied by brush, short nap roller or airless spray system. When spraying TREMprime LV, take necessary precautions to prevent overspray.

Do not over-prime. Application of excessive amounts will increase cure time and may lead to installation issues such as slippage, poor adhesion or staining/bleed through.

Allow TREMprime LV to fully cure prior to application of TREMproof 6100.

Limitations

- Not intended for use as a final coat or for exposure to weathering.
- Surfaces primed with TREMprime LV must be reprimed if allowed to remain open for more than 24 hours or if area has been wetted or contaminated with dust or debris.
- May be thicker and viscous at cool temperatures. If stored in cool conditions, transfer to a heated area at approximately 77°F (25°C) at least 1 day prior to use.
- Cure times may be extended under cool and overcast conditions.
- Do not subject TREMprime LV to freezing temperatures during cure.
- Do not apply when rain is imminent.
- Not intended for application using a hand pump (Hudson) spray unit.
- Not for use on backfilled walls, mud slabs, tunnels or planters not over occupied space.
- All surfaces must be sound, clean, dry and free from contamination. A thorough wire brushing, grinding, sandblasting or solvent cleaning may be required to expose clean, sound, virgin surfaces.
- Any questions regarding drying times, coverage rates and unique application techniques regarding the individual primers should be directed to Tremco Technical Services or your local Tremco Sales Representative.
- Do not apply over contaminated or damp surfaces.
- Do not thin.

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

1218/TPLVDS

Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555

www.tremcosealants.com

