



TECHNICAL DATA SHEET

TREMprime® MULTI- SURFACE URETHANE PRIMER

Urethane Tie-In Primer

PRODUCT DESCRIPTION

TREMprime Multi-Surface Urethane Primer is a two-component, quick drying, epoxy-based, VOC-compliant primer primarily for use with Vulkem® urethane deck coatings and liquid-applied waterproofing products. It may also be used with Vulkem and Tremco branded urethane sealants.

BASIC USES

Porous surfaces, interlaminary, urethane coatings. Low-VOC (<60 g/L), two-part epoxy primer used to condition and prep porous surfaces and existing coatings for application of a new coating layer. Apply with a short nap roller or brush evenly to the surface. Primer must dry completely before coating application as indicated by turning from milky-white to completely clear.

FEATURES & BENEFITS

- Improved wear and chemical resistance
- Reduced water and salt absorption
- Water-based, low odor
- Resistant to mild acids
- Can be used as a primer under epoxy or urethane coatings
- Resistant to gasoline and other solvent spills

COVERAGE RATE

Approximately 200-300 ft²/gal

PACKAGING

3-gal (11.4-L) kits:

Part A: 2-gal (7.6-L) can

Part B: 1-gal (3.8-L) can

AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco distributor, or warehouse.

STORAGE

Store indoors, protected from moisture, at temperatures between 45 °F and 110 °F (7 °C and 43 °C) and out of direct sunlight.

LIMITATIONS

- Protect from freezing.
- All surfaces must be sound, clean, dry, and free from contamination. A thorough wire brushing, grinding, sandblasting, or solvent cleaning may be required to expose clean, sound, virgin surfaces.
- Any questions regarding drying times, coverage rates, and unique application techniques regarding the individual primers should be directed to Tremco Technical Services or your local Tremco Sales Representative.
- Do not apply over contaminated or damp surfaces.
- Do not thin.
- Substrate must be at least 5 °F (3 °C) above the measured dew point temperatures to avoid dew point conditions.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUE
Mix Ratio (A: B by Volume)	2:1
Total Solids	20%
VOC Content	68 g/L
Pot Life	4 hrs
Storage Temperature Range	45 °F (7 °C) minimum to 110 °F (43 °C) maximum

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TMSUP-DS/0922

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com