

TECHNICAL DATA SHEET

TREMSTOP® FS BLANKET

A Firestopping Fiber Blanket

PRODUCT DESCRIPTION

TREMstop® FS Blanket is a bio-soluble fiber insulation developed from a calcia, magnesia, silica chemistry to provide thermal insulation at operating temperatures up to 1832 °F (1000 °C).

BASIC USES

TREMstop FS Blanket is used as a packing material around metal pipe penetrations, cables and cable trays and in joints.

FEATURES AND BENEFITS

• TREMstop FS Blanket has low thermal conductivity making it the ideal choice when a high level of fire protection is required.

AVAILABILITY

Immediately available from your local Tremco Sales Representatives, Tremco Distributor or Tremco Warehouse.

PACKAGING

TREMstop FS Blanket 1/2" x 3" x 25' 16 rolls/case TREMstop FS Blanket 1/2" x 6" x 25' 8 rolls/case

APPLICABLE STANDARDS

- UL 2079
- UI 1479 (ASTM E-814)
- UL 263 (ASTM E-119)
- UL 723 (ASTM E-84)
- CAN4-S115M
- CAN/ULC-S101M

LIMITATIONS

Not recommended for use with passive fire containment systems not listed or approved by Tremco.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit https://www.tremcosealants.com/warranties/ for details.

TYPICAL PHYSICAL PROPERTIES			
PROPERTY	TEST METHOD	TYPICAL VALUES	
Flame Spread	ASTM E84	0	
Melting Point		2300 °F (1260 °C)	
Density		8 pcf (128 kg/m)	

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TSFSB-DS/0523





Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



