



TECHNICAL DATA SHEET

TREMSTOP® SUPERSTRIP

Graphite-Based Intumescent Wrap Strip

PRODUCT DESCRIPTION

TREMstop® SuperStrip is made of a flexible graphite-based intumescent compound with a polyethylene backer. It is designed to expand when exposed to a fire to fill any voids left as the combustible materials burn away.

BASIC USES

TREMstop SuperStrip is intended for use with plastic pipe in concrete assemblies and wood floor/ceiling assemblies. It can also be used with fluted metal decks.

FEATURES & BENEFITS

TREMstop SuperStrip is flexible enough to easily wrap around the pipe to make installation quick and simple. It is packaged in rolls and precut strips to reduce waste and accommodate a variety of pipe diameters and types.

TREMstop SuperStrip meets or exceeds the requirements of the following specifications:

- ASTM E814 (UL1479)
- CAN/ULC S115

The Greenguard Gold certification on TREMstop SuperStrip ensures safety for use in the most sensitive indoor environments including hospitals and schools.

AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 1.5 inch wide pre-cut strips (8, 11.34, or 15 inch lengths) or rolls (12 ft length) of varying thicknesses (0.125, 0.25, or 0.375 inch).

COLORS

Available in Dark Gray.

LIMITATIONS

Not recommended for use with passive fire containment systems not listed or approved by Tremco. Refer to UL listings at www.UL.com. Contact Tremco Technical Services for additional information.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	PRE-CUT STRIPS			ROLLS		
	SS-T2	SS-T3	SS-T4	SS-R2	SS-R3	SS-R4
Identifier	SS-T2	SS-T3	SS-T4	SS-R2	SS-R3	SS-R4
Color	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray
Width (inch)	1.5	1.5	1.5	1.5	1.5	1.5
Thickness (inch)	0.125	0.25	0.375	0.125	0.25	0.375
Normal Pipe Size	2	3	4	2	3	4
Case Quantity	10	10	10	9	4	1
Length (inch)	8	11.34	15	144	144	144

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TSSPS-DS/0123



Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com