



TECHNICAL DATA SHEET

TREMPRO® JS-773+

Non-Skinning, Non-Drying,
Flexible, Synthetic Butyl Sealant

PRODUCT DESCRIPTION

TREMPRO® JS-773+ is a high solids, non-skinning, non-drying, synthetic, butyl elastomer sealant.

BASIC USES

TREMPRO JS-773+ is designed for in-plant caulking of panel joints. TREMPRO JS-773+ is also ideal for buttering or bedding non-porous components that are squeezed together by fastening or for caulking of the interior panel joints of PEMB panels. It can be used to separate dissimilar metals to prevent galvanic action.

The product exhibits excellent adhesion to a variety of metals and metal finishes including hot-dip galvanized steel, Galvalume®, Kynar 500®, stainless steel, polyvinylidene fluoride (PVDF), aluminum, and fiberglass.

PACKAGING

10.1-oz cartridges, Quart (850ml) cartridge
20-oz (600-mL) sausages
5-gal pails and 52-gal drums

COLORS

Off-White.

AVAILABILITY

Immediately available from your local Tremco Field Representative, Tremco Distributor or Tremco Warehouse.

LIMITATIONS

- Not recommended for use on exposed applications.
- For In Plant Use Only.

SUBSTRATE PREPARATION

For good adhesion, the joint surface must be sound, clean and dry.

APPLICATION

TREMPRO JS-773+ is easily applied with conventional caulking equipment. Pails and drums can be applied with standard pumps. Tremco recommends a minimum 20:1 ratio pump.

TREMPRO JS-773+ will adhere to substrate and mating surfaces in temperatures ranging from -5 °F (-20 °C) to 120 °F (49 °C). Product should be stored at room temperature to ensure optimal product performance.

After application is complete, assemble components within 24 hr. to prevent tracking and dirt attraction that may inhibit adhesion.

For recommendations on extended storage conditions, please consult Tremco Technical Services at 1-866-209-2404. Extended exposure under elevated temperatures may alter the non-skinning and non-drying characteristics of the sealant.

Damaged Sealant can be repaired. Consult Tremco Technical Services or a Sales Representative for repair procedures.

CLEAN UP

Tooling is recommended immediately after application to ensure firm, intimate contact with the joint interface. Dry tooling is preferred. Excess sealant and smears adjacent to the joint can be removed with mineral spirits or a similar solvent.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Application Temperature		-5 °F (20 °C) to 120 °F (49 °C)
Percent Solids		90 to 92%
Service Temperature		-65 °F (1.52 54 °C) to 200 °F (93 °C)
Specific Gravity		1.52

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TPJS773+-DS/0623

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit, Nudura and Willseal brands; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com