

Product Description

Tremco Rubber Aggregate is a 12-20-mesh, cryogenically ground rubber from post-industrial sources. It is designed for use with Vulkem OC810 Coating.

Basic Uses

Tremco Rubber Aggregate is used to impart skid-resistance and provide texture to light pedestrian applications.

Features and Benefits

- Durable recycled content
- Imparts skid resistance
- Comfortable to bare feet
- Neighborhood friendly
- Enhances waterproofing system
- Aesthetically pleasing

Availability

Tremco Rubber Aggregate is immediately available from your local Tremco Sales Representative, distributor, or warehouse.

Packaging

- 50-lb (22.7 kg)

Colors

Off-White

Application

Please refer to the Vulkem OC810 Coating Application Instructions for complete installation details.

Compatibility and Connectivity

The Vulkem OC810 system, which includes Tremco Rubber Aggregate, requires the use of primers for full installation. Surface preparation also may require the use of approved Tremco sealants to repair the substrate prior to coating.

Compatible materials include:

- Vulkem 116 Polyurethane Sealant
- Dymeric 240FC Polyurethane Sealant
- Vulkem 45SSL Polyurethane Sealant
- Vulkem Primer No. 191 (Low-VOC Primer)
- TREMprime Multi-Surface Urethane Primer
- TREMprime Non-Porous Primer

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or refund the purchase price of the quantity of Tremco Products proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Hardness, Shore A		60-80
Size		12-20 mesh (0.5-1.5 mm)

0316/TRA12-20DS-DC

Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555

