

Product Description

Vulkem® 191 Primer is a quick-drying, one-part, moisture-curing primer.

Basic Uses

Porous surfaces, interlaminary, urethane sealants, coatings and TREMproof membranes. It is used to prepare surfaces of cured urethane sealants, coatings and TREMproof membranes that will be sealed with a fresh coat.

Coverage Rate

400 to 450 ft²/gal for interlaminary applications. VOC compliant.

Packaging

1-qt (946-mL) can
1-gal (3.8-L) pails
5-gal (18.9-L) pails

Availability

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

Storage

Store indoors, protected from moisture, at temperatures between 50°F and 90°F (10°C and 32°C) and out of direct sunlight.

Limitations

- All surfaces must be sound, clean, dry and free from contamination. A thorough wire brushing, grinding, sandblasting or solvent cleaning may be required to expose clean, sound, virgin surfaces.
- Any questions regarding drying times, coverage rates and unique application techniques regarding the individual primers should be directed to Tremco Technical Services or your local Tremco Sales Representative.
- Do not apply over contaminated or damp surfaces.
- Do not thin.

Application

Apply with a clean brush or roller. Do not apply in excess or allow to puddle. Use a short nap roller only. Dry time is 25 to 45 min at 70 °F (21°C). Apply coating or sealant within 1 to 2 hr after application when primer is still tacky but does not come off substrate. Primer will yellow with time if left exposed. Do not apply in excess to other substrates not intended to be coated. Do not apply sealant or coating if primer becomes hard or glossy. If it does, clean with a Tremco approved solvent and reprime with Vulkem 191 Primer. Primer will yellow with time if left exposed.

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density	ASTM D1475	1.24 kg/l
Specific Gravity @ 77°F	ASTM D70	1.23 kg/l
Viscosity @ 77°F	ASTM D562	55 KU
Storage Temperature Range		50 °F (10 °C) minimum to 90 °F (32 °C) maximum

0419/V191DS-DC

Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555