



Tremco Commercial Sealants & Waterproofing
3735 Green Road
Beachwood, OH 44122
US: 800.852.9068
Canada: 800.363.3213
www.tremcosealants.com



September 30, 2020

To Whom It May Concern:

RE: Dymeric 240 FC—Green Building Product Information (LEED v4.1 Information)

Tremco Incorporated is an organization that is committed to quality, our employees, and our environment. We are responsive to both internal and external customers, and we pledge to treat everyone with good stewardship and respect.

Tremco Incorporated certifies the following for Dymeric 240 FC:

Building Product Disclosure and Optimization:

Dymeric 240 FC is manufactured in Cleveland, Ohio.

No single extracted material is used to produce the majority of this product.

Recycled content for Dymeric 240 FC is not available, and for the purposes of LEED reporting should be assumed to be zero.

Low Emitting Materials - VOC Content Information:

Dymeric 240 FC is a urethane sealant with a VOC content of 5g/L equaling 1% as applied/mixed. As such, VOC levels are lower than the limits set by SCAQMD rule 1168.

This product is Greenguard certified, meaning it has met some of the world's most difficult and complete standards for low emissions of VOC's into indoor air. This product also adheres to the California Department of Public Health (CDPH) Standard Method V1.1-2010, a standard vital to demonstrate compliance with LEED.

Green Chemistry:

Tremco Incorporated is dedicated to the environment and prides itself on making its products as sustainable as possible.



Tremco Commercial Sealants & Waterproofing
3735 Green Road
Beachwood, OH 44122
US: 800.852.9068
Canada: 800.363.3213
www.tremcosealants.com

Manufacture Inventory (reported to 1000ppm):

Chemical Name or Role	CAS number	Amount	GHS Hazard
Polyol		30-70%	Non-Hazardous
Polyurethane prepolymer		30-70%	Non-Hazardous
Calcium carbonate	471-34-1		
Fibrous Glass	65997-17-3		
Calcium oxide	1305-78-8		
Plasticizer		<5%	Non-Hazardous
Filler		<1%	Non-Hazardous
Stearic acid	57-11-4		
Amorphous silica	7631-86-9		
Hydrotreated heavy naphthenic distillate	64742-52-5		
Stabilizer		<1%	Non-Hazardous
Antioxidant		<1%	Non-Hazardous
2,4-Toluene diisocyanate	584-84-9		
Moisture Scavenger		<1%	Non-Hazardous
Adhesion promoter		<1%	Non-Hazardous
Toluene-2,6-Diisocyanate	91-08-7		

Additional Information:

Should you have any questions or require additional information, please do not hesitate to contact Technical Services or your local Tremco Field Representative.

Sincerely,

Joe Kravetz

Product Steward

Compliance and Regulatory Affairs