



May 22, 2018

To Whom It May Concern:

RE: Dymonic 100—Green Building Product Information (LEED x4 Information)

Tremco Incorporated is an organization that is committed to quality, our employees, and our environment. We are responsive to both internal and external customers, and we pledge to treat everyone with good stewardship and respect.

Tremco Incorporated certifies the following for Dymonic 100:

Building Product Disclosure and Optimization:

Dymonic 100 is manufactured in Cleveland, Ohio.

No single extracted material is used to produce the majority of this product.

Recycled content for Dymonic 100 is not available, and for the purposes of LEED x4 reporting should be assumed to be zero.

Low Emitting Materials - VOC Content Information:

Dymonic 100 is a urethane sealant with a VOC content of 40g/L equaling 3% as applied/mixed. As such, VOC levels are lower than the limits set by SCAQMD rule 1168.

Note: VOC content values are as reported for the highest VOC content color for all Dymonic 100 colors. Other colors may have a lower VOC content reported on their MSDS. .

This product is Greenguard certified, meaning it has met some of the world's most difficult and complete standards for low emissions of VOC's into indoor air. This product also adheres to the California Department of Public Health (CDPH) Standard Method V1.1-2010, a standard vital to demonstrate compliance with LEED.

Green Chemistry:

Tremco Incorporated is dedicated to the environment and prides itself on making its products as sustainable as possible.

Manufacture Inventory:

| Chemical Name | CAS Number | Role | Amount | GHS Hazard |
|--|------------|--------------------------|--------|---------------|
| | | Isocyanate Prepolymer | 20-60% | Non-Hazardous |
| Calcium carbonate | 471-34-1 | | | |
| | | Plasticizer | 0-40% | Non-Hazardous |
| Polyvinyl chloride | 9002-86-2 | | | |
| Calcium Carbonate (Limestone) | 1317-65-3 | | | |
| Xylene | 1330-20-7 | | | |
| Calcium oxide | 1305-78-8 | | | |
| | | Reactive Agent | <5% | Non-Hazardous |
| | | Colorant Dispersion | <5% | Non-Hazardous |
| | | Filler | <1% | Non-Hazardous |
| Ethylbenzene | 100-41-4 | | | |
| Isophorone Diisocyanate | 4098-71-9 | | | |
| | | Environmental Stabilizer | <1% | Non-Hazardous |
| Carbon Black | 1333-86-4 | | | |
| Hydrotreated heavy naphthenic distillate | 64742-52-5 | | | |
| | | Adhesion Promoter | <1% | Non-Hazardous |
| Stearic acid | 57-11-4 | | | |
| Dibutyl tin dilaurate | 77-58-7 | | | |
| Titanium dioxide | 13463-67-7 | | | |
| | | Pigment | <1% | Non-Hazardous |
| Iron oxide | 1309-37-1 | | | |

Additional Information:

Should you have any questions or require additional information, please do not hesitate to contact Technical Services or your local Tremco Field Representative.

Sincerely,



Amy Woodard
Manager
Compliance and Regulatory