



Tremco Commercial Sealants & Waterproofing  
3735 Green Road  
Beachwood, OH 44122  
US: 800.852.9068  
Canada: 800.363.3213  
www.tremcosealants.com



September 30, 2020

To Whom It May Concern:

RE: ExoAir Termination Mastic—Green Building Product Information (LEED v4.1 Information)

Tremco Incorporated is an organization that is committed to quality, our employees, and our environment. We are responsive to both internal and external customers, and we pledge to treat everyone with good stewardship and respect.

Tremco Incorporated certifies the following for ExoAir Termination Mastic:

**Building Product Disclosure and Optimization:**

ExoAir Termination Mastic is manufactured in Toronto, Ontario, Canada.

No single extracted material is used to produce the majority of this product.

Recycled content for ExoAir Termination Mastic is not available, and for the purposes of LEED reporting should be assumed to be zero.

**Low Emitting Materials - VOC Content Information:**

ExoAir Termination Mastic is an exterior applied adhesive primer with a VOC content of 300g/L equaling 30% as applied/mixed. This product is typically used as an exterior applied product, as such, it does apply to the Low Emitting Materials credit in LEED v4.1.

**Green Chemistry:**

Tremco Incorporated is dedicated to the environment and prides itself on making its products as sustainable as possible. We are pleased to report that this product is produced without any Red List chemicals. As such, it can be used to assist in finishing projects aimed towards achieving a Living Building Challenge certification.



Tremco Commercial Sealants & Waterproofing  
3735 Green Road  
Beachwood, OH 44122  
US: 800.852.9068  
Canada: 800.363.3213  
www.tremcosealants.com

**Manufacture Inventory (reported to 1000ppm):**

Chemical Name or Role	CAS Number	Amount	GHS Hazard
Asphalt	8052-42-4		
Xylene	1330-20-7		
Polymer Resin		0-40%	Non-Hazardous
Amorphous silica	7631-86-9		
Ethylbenzene	100-41-4		
Coal tar pitch	65996-93-2		
Petroleum distillates	64741-81-7		
Thermal Cracked Petroleum Residue	64741-80-6		
Polyethylene	9002-88-4		
Moisture Scavenger		<1%	Non-Hazardous
Carbon Black	1333-86-4		
Plasticizer		<1%	Non-Hazardous
Emulsifier		<1%	Non-Hazardous
Hydrodesulfurized middle distillate	64742-80-9		
Toluene	108-88-3		
Fluorathene	206-44-0		

**Additional Information:**

Air barrier systems, when properly installed, have been shown to reduce energy costs for HVAC by as much as 40% versus buildings without fully-adhered air barriers. Should you have any questions or require additional information, please do not hesitate to contact Technical Services or your local Tremco Field Representative.

Sincerely,

Joe Kravetz

Product Steward

Compliance and Regulatory Affairs