

Technical Bulletin SSG 1.2

EnerEDGE® and EnerEDGE® Pro Warm-Edge Spacer Dimensions

The following chart details the airspace size availability of parts in fractional increments. Along with listed size code used within Tremco SKU part numbers, additional dimensional reference in decimal Imperial and decimal metric equivalents are provided. Note that spacers are available in two heights and two spool formats that dictate the length of spacer supplied on each of the two spool packages.

Nominal Airspace Sizes Fractional Inches ± 1/64"	Size Code within SKU string	Airspace Decimal Imperial Inches ± 3% of width	Airspace Decimal Metric mm ± 3% of width	Length of EnerEDGE on Mini Spool Height = .182" (4.62 mm), ± 5%	Length of EnerEDGE on Auto/Large Spool Height = .182" (4.62 mm), ± 5%	Length of EnerEDGE Pro on Mini Spool Height = .242" (6.15 mm), ± 5%	Length of EnerEDGE Pro on Auto/Large Spool Height = .242" (6.15 mm), ± 5%
3/16	19	.188	4.8	1786' (544 m)	N/A	N/A	N/A
1/4	25	.250	6.2	1503' (458 m)	4441' (1354 m)	1145' (349 m)	3920' (1195 m)
9/32	28	.281	7.0	1409' (429 m)	4112' (1253 m)	1074' (327 m)	3540' (1079 m)
5/16	31	.313	7.8	1222' (372 m)	3725' (1135 m)	930' (283 m)	3287' (1002 m)
11/32	34	.344	8.5	1128' (344 m)	3439' (1048 m)	859' (262 m)	3047' (929 m)
3/8	38	.375	9.3	1034' (315 m)	3404' (1038 m)	787' (240 m)	2782' (848 m)
13/32	41	.406	10.1	1034' (315 m)	3009' (917 m)	787' (240 m)	2655' (809 m)
7/16	44	.438	10.9	940' (287 m)	2722' (830 m)	716' (218 m)	2402' (732 m)
15/32	47	.469	11.7	846' (258 m)	2579' (786 m)	644' (196 m)	2276' (694 m)
1/2	50	.500	12.5	846' (258 m)	2436' (742 m)	644' (196 m)	2149' (655 m)
17/32	53	.531	13.3	752' (229 m)	2292' (699 m)	573' (175 m)	2023' (617 m)
9/16	56	.563	14.1	752' (229 m)	2292' (699 m)	573' (175 m)	2023' (617 m)
19/32	59	.594	14.9	752' (229 m)	2149' (655 m)	573' (175 m)	1897' (578 m)
5/8	62	.625	15.7	658' (201 m)	2006' (611 m)	501' (153 m)	1770' (539 m)
21/32	66	.656	16.5	658' (201 m)	2006' (611 m)	501' (153 m)	1770' (539 m)
11/16	69	.688	17.3	658' (201 m)	1863' (568 m)	501' (153 m)	1644' (501 m)
23/32	72	.719	18.1	564' (172 m)	1863' (568 m)	501' (153 m)	1644' (501 m)
3/4	75	.750	18.9	564' (172 m)	1719' (524 m)	430' (131 m)	1517' (462 m)
25/32	78	.782	19.7	564' (172 m)	1719' (524 m)	430' (131 m)	1517' (462 m)
13/16	81	.813	20.5	564' (172 m)	1576' (480 m)	430' (131 m)	1390' (424 m)
7/8	88	.875	22.2	470' (143 m)	N/A	N/A	N/A

GENERAL NOTES: Barrier film minimum coverage is 0.031" (.8 mm) at borderline.

Please contact Tremco Technical Service at 866-209-2404 with any questions regarding this bulletin.