



EnerEDGE[®]
warm-edge spacer

EnerEDGE[®] Equipment & Tools

PERIMETER TRACE TOOLS

The perimeter trace tools are used to cleanly apply spacer to the IG unit's glass perimeter, while precisely controlling start point, inset and notch locations. The tools allow for either inside cutting (that preserves the integrity of the spacer's moisture vapor barrier) or back cutting. Either allows for a wider range of applied perimeter sealant options.



ENAIN 502



ENAONT 502

PART NUMBER	DESCRIPTION
ENAIN 502	INSIDE NOTCH
ENAONT 502	BACK NOTCH

ENEREDGE STORAGE DRUMS

The storage drums are used to keep opened EnerEDGE spools (either the larger Auto spools or smaller Mini spools) fresh. The drums will preserve the desiccant between extractions.



PART NUMBER	DESCRIPTION
ENADRUM 762	MINI SPOOL STORAGE DRUM
ENADRUM 763	AUTO SPOOL STORAGE DRUM

WARRANTY

Tremco warrants its products to be free of defects in material but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or refund the purchase price of the quantity of Tremco Products proven to be defective, and Tremco shall not be liable for any loss or damage.