

SECUROCK® EXOAIR® 430

System Components

Dymonic® 100



A high-performance, medium-modulus, low-VOC, UV-stable, non-sag polyurethane sealant that can be used for detailing fasteners, board joints, around penetrations, as angle beads in transition areas, in control/expansion joints with break metal, for terminating ExoAir® 110AT, and under all the Vulkem Coating Systems and TREMproof® waterproofing membranes.

Packaging: Fifteen 20 oz. Tubes/Carton

Spectrem® 1



An ultra-low modulus, high-performance, one-part moisture curing silicone joint sealant used to adhere Proglaze® ETA Connections to the Securock ExoAir 430 Panel. Spectrem 1 should never be used underneath any membrane or sealant unless adhesion has been verified.

Packaging: Fifteen 20 oz. Tubes/Carton

Proglaze ETA Connections



A pre-engineered silicone material used as a transition membrane for expansion joints between the Securock ExoAir 430 Panels. It is comprised of a flat, single-ribbed silicone extrusion that is adhered to the panel with Spectrem 1 silicone sealant.

Packaging: One 4" x 50' Roll/Carton

ExoAir 100AT



ExoAir 110AT is a 22-mil composite impermeable membrane that is comprised of 16 mils of butyl and 6 mils of HDPP facer. It is an impermeable, self-adhered sheet designed to be applied to exterior cavity walls to mitigate air infiltration/exfiltration, vapor transmission and water penetration.

Packaging: **(6" Wide)** Eight 6" x 75' Rolls (300 Ft²)/Carton, **(9" Wide)** Four 9" x 75' Rolls (225 Ft²)/ Carton, **(12" Wide)** Four 12" x 75' Rolls (300 Ft²)/Carton

ExoAir 230



A fluid-applied, synthetic, vapor-permeable air barrier designed for use in commercial construction applications. It can be sprayed, rolled or trowel-applied to common substrates. ExoAir 230 can be used as an air barrier membrane on adjacent substrates such as concrete or CMU, and can also be used in conjunction with Securock ExoAir Reinforcing Mesh as a transition material.

Packaging: One 5-gal Pail

Securock ExoAir Reinforcing Mesh



A mesh that is fully embedded in ExoAir 230 in light orange for transition areas.

Packaging: Six 6" x 150' rolls/Carton

ExoAir Primer



A VOC-compliant adhesive formulated to promote adhesion to the exposed gypsum core of the exterior sheathing prior to the application of flashing.

Packaging: One 5-Gal Pail

ExoAir LEF



A single-component, moisture-curing, gun-grade polyurethane foam that is used to insulate and act as a bond breaker around penetrations.

Packaging: Twelve 24 fl oz. Cans/Carton

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

For Tremco Technical Support
866-209-2402
216-292-5181
tremcosealants.com



SECUROCK® EXOAIR®

Tremco®, ExoAir®, Dymonic®, TREMproof®, Spectrem®, and Proglaze® are registered trademarks of Tremco Incorporated. The trademarks USG, FIRECODE, SECURROCK, the USG logo, and related marks are trademarks of USG Corporation or its affiliates. Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.