

TREMfloor[™] **SELECTION GUIDE**

		irettane	inethane	Wethane Broatcast	irettane	Inethane	irettane	illethane 16
	TREME	in the state of th	Juliettane 11/2 like	Line Halle Register 1 LHT Co.	de la	The Hall be seen and the first of the first	Trestate TREMI	an Hettare 13 16
NTENDED USE	, 0	. , , ,	Co. d	. C	2. \ CR. 4	ign, , Cr.	/	, <i>' ' ' '</i>
Medium Duty				•	•		•	
Heavy Duty	•	•	•			•		
FEATURES & BENEFITS								
Fast Return-to-Service	•	•		•	•	•	•	•
Seamless	•	•	•	•	•	•	•	•
Polygiene® Antimicrobial	•	•	•	•	•	•	•	•
Chemical Resistance	•	•	•	•	•	•	•	•
Slip Resistance	•	•	•		•	•		
Continuous Temperature Resistance Up to 180° F	•	•	•	•	•	•	•	
Continuous Temperature Resistance Up to 200° F	•	•				•		
Unaffected by MVT	•	•	•	•	•	•	•	
Low Odor		•		•			•	
Easily Cleaned				•			•	
EXTURE								
Smooth				•			•	•
Textured	•	•	•		•	•		
FINISH								
Matte		•	*Finish Varies w/	•	*Finish Varies w/	•	•	•
Semi-Gloss	•		Sealer ↓		Sealer \downarrow			
SEALERS								

TREMfloor FC**: Matte Finish Sealer with Polygiene with Polygiene Anti-Microbial Additive. Not UV-Resistant.

TREMfloor FCUV: Glossy Finish, UV-Resistant Sealer with Polygiene Anti-Microbial Additive.

TREMfloor SR Sealer: High-Gloss Finish, Cost-Effective Sealer with Polygiene Anti-Microbial Additive. Not UV-Resistant.

TREMCO Sealer 200: Clear Gloss, UV-Stable, Aliphatic Polyurethane Sealer.

TREMCO Sealer 300: Clear Gloss, UV-Stable, Polyaspartic Sealer.



TREMfloor™ SELECTION GUIDE

		ilethale	ilettate i	Wethane Brodust	inethane	Hettalle	ilettale	inethane 16
	TREMHOO	The that I feether the feether that I feether	nutettale like	A THE HELD TO SEE THE PROPERTY OF THE PROPERTY	ulightak Keng Keng Keng	THE HOLE THE CO	net Hetale Leight	In the transfer of the state of
INTENDED USE	/							
Medium Duty				•	•		•	
Heavy Duty	•	•	•			•		
COMMON USE AREAS								
Kitchens	•							
Fire Stations	•					•		
Animal Welfare	•				•	•		
Detention Centers				•			•	
Manufacturing Areas (Dry)				•			•	
Manufacturing Areas (Wet)	•				•			
Shower Areas		•	•		•			*All Areas
Locker Rooms			•	•	•		•	Requiring Coving
Bathrooms		•	•		•			Ooving
Car Dealership / Workshops					•		•	
Trash Areas	•				•	•		
Mechanical Rooms	•			•	•		•	
Hospitality Back-of-House Areas		•			•		•	
Service Corridors					•		•	

*TREMfloor Urethane Cement SL and MF without a quartz broadcast requires the use of a sealer coat or primer.

**TREMfloor Urethane Cement FC can be used as a primer over very porous surfaces and/or heavily trafficed ennvironments.

Tremco | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.

