



TREMGLAZE® WINDOW AND DOOR GLAZING PRODUCTS

Sealants, Foams, and Tapes

Superior Solutions for the Residential Window & Door Market

Since its founding in 1928, Tremco® has been a technology leader in the construction sealants and weatherproofing industry. With one of the industry's largest Research and Development groups devoted to construction sealants, technology development is ongoing and the breadth of product includes Silicone and Urethane Glazing Systems, Exterior Sealant Systems, Interior Sealant Systems and Sealant & Flashing Systems with technologies ranging from Silicones and Urethanes to Hybrids, Acrylic and Butyl. As a result, selection of an appropriate product for the application within specified parameters is never a problem.

The TremGlaze® residential window and door glazing products represent one of the largest product portfolios in the industry with products meeting the requirements of high volume in-plant window manufacturing including impact glazing and field installation. In-plant products provide exceptional green strength development and are used for in-plant back bedding, cap, toes and heel bead applications, expediting turnaround while reducing inventory. As one of the original associate members of the American Architectural Manufacturers Association (AAMA), TremGlaze sealants, extruded tapes and gaskets are regularly independently tested and approved as verified components for use in AAMA Certified Products.

To assist in the selection and proper application of these consistent, high-quality products, Tremco's Technical Services Group assist in-plant applicators, contractors, architects and engineers with project designs and applications to ensure optimal performance on the job. Assistance may include adhesion testing, compatibility testing and problem-solving with even the most challenging projects.

Customer service support is among the most experienced in the industry and a company commitment to LEAN manufacturing ensures product availability and a commitment to efficient distribution no matter what product or color you may need or where you may be located.

| PRODUCT | DESCRIPTION | BASIC USES | PACKAGING | PRODUCT TYPE |
|-----------------|---|---|---|--------------------------|
| TremGlaze S500+ | One-part, neutral curing, silicone sealant | <ul style="list-style-type: none"> Tenacious adhesion and quick cure time make it perfect for the most demanding window and door installations and in-plant glazing Formulated with biocide aides in the prevention of mildew and fungus build up | 10.1 oz cartridge, 4.5 gal pail, 50 gal drum | In-Plant |
| TremGlaze S600 | Single-component, neutral-cure, fast-skinning, medium-modulus silicone sealant | <ul style="list-style-type: none"> Ideal for use as an in-plant glazing sealant for applications that include back-bedding, cap, heel and toe beads, and sash joinery | 10.1 oz cartridge, 20 oz sausage, 4.5 gal pail, 50 gal drum | In-Plant |
| TremGlaze S700 | One-part, high modulus, neutral cure silicone sealant | <ul style="list-style-type: none"> Impact/Hurricane Tested, including Miami/Dade protocol Meets stringent performance requirements for Impact Glazing Excellent tensile and elongation properties that allow it to perform in a variety of glazing systems | 10.1 oz cartridge, 50 gal drum | In-Plant |
| TremGlaze S900 | Two-part, 1:1 ratio, reactive silicone sealant | <ul style="list-style-type: none"> In-plant back bedding sealant in the manufacturing of window and door products Quick green strength and fast setting | 4.5 gal pail, 50 gal drum | In-Plant |
| TremGlaze S1400 | High-performance, single-component, neutral-cure, medium-modulus silicone sealant | <ul style="list-style-type: none"> Specifically designed to achieve a watertight seal as a general perimeter caulking sealant of windows, doors and frames, and within wood, brick, vinyl, and other residential installations substrates | 10.1 oz cartridge, 20 oz sausage | Installation |
| TremGlaze U1500 | Textured, single-component, moisture-curing, gun-grade polyurethane sealant. | <ul style="list-style-type: none"> An excellent general-purpose sealant designed for use on stucco, window and door perimeters, masonry work, poured and precast concrete, and similar types of construction joints | 20 oz sausage | Installation |
| TremGlaze U1600 | One-part, quick curing, low modulus, hybrid polyurethane | <ul style="list-style-type: none"> Back bedding and general purpose applications Window and door installation UV stable, quick skin time, and paintable Mutiple colors available | 10.1 oz cartridge, 20 oz sausage, 4.5 gal pail, 50 gal drum | Installation In-Plant |



TREMGLAZE® WINDOW AND DOOR GLAZING PRODUCTS

| PRODUCT | DESCRIPTION | BASIC USES | PACKAGING | PRODUCT TYPE |
|-----------------------------|---|---|--|--------------------------|
| TremGlaze UA1300 | High-performance urethane acrylic sealant | <ul style="list-style-type: none"> Interior or exterior caulking where a durable and permanently flexible sealant is needed UV stable, quick skin time and excellent adhesion | 10.3 oz cartridge | Installation |
| TremGlaze SA1100 | One-part, siliconized acrylic latex sealant | <ul style="list-style-type: none"> General purpose interior sealant Ideal for interior window and door applications Paintable | 10.1 oz cartridge, 4.5 gal pail, 50 gal drum | Installation In-Plant |
| Tremco 830 (Canada Only) | A one-part, thermoplastic elastomer that provides a highperformance, flexible seal in glazing and siding applications | <ul style="list-style-type: none"> Use with sill trim, flashings, fascia, J-trim, F-channel, and crown molding | 10.1 oz cartridge, 20 oz sausage | Installation |

| PRODUCT | DESCRIPTION | BASIC USES | PACKAGING | PRODUCT TYPE |
|-------------------|---|---|----------------------|--------------|
| ExoAir® Flex Foam | Flexible, low-expansion polyurethane foam | <ul style="list-style-type: none"> Best suited as a thermal and sound barrier to be used in the perimeters around windows and doors | 700 ml gun-grade can | Installation |
| ExoAir LEF Foam | Low-expanding polyurethane foam | <ul style="list-style-type: none"> Most commonly used as a thermal and sound barrier Best suited around window and door frame joints but can also be used as an effective joint filler in hidden applications | 700 ml gun-grade can | Installation |



Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.

Tremco®, TremGlaze® and ExoAir® are registered trademarks of Tremco Incorporated. Willseal is a registered trademark of Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.



Construction Products Group