

WATCHDOG® QUICK CURE 90

Cures up to 90% faster even in tough weather

Product Overview

The unique Quick Cure 90 waterproofing formulation cures at a rate that's up to 90% faster than our industry-recognized WATCHDOG Waterproofing® brand of foundation, opening up an even wider weather window of opportunity for you to confidently meet your production schedules.

Only Tremco, North America's leader in providing innovative moisture-management products and systems to the most-experienced residential waterproofing contractor network, has the technical expertise and the field know-how to deliver a formulation like Quick Cure 90. This technology-driven product feature cures as much as 90% faster than our standard top quality brands. WATCHDOG Quick Cure 90 can be used on every job you spray, and it's greatest value to you is when it's sprayed with rain, sleet or snow in the forecast and you need to get a job done NOW!



*Fewer wash-offs. Fewer call-backs.
Fewer missed production schedules.*

Features & Benefits

With its exceptional ability to hang on the wall and easily build to your targeted thickness, Tremco now offers a performance warranty on vertical, below-grade foundation wall cracks of up to 1/8" with a cured membrane of 60 mils! That's TWICE the crack coverage of the industry standard! Only Tremco has the confidence and experience to offer this level of protection. So whatever the weather conditions, you can expect WATCHDOG Quick Cure to set up and cure up to 90% faster!



MEMBRANE PROPERTIES

Resistance to Hydrostatic Head	Results: 3' of water	Method: ASTM D-5385
Type	Polymer-enhanced asphalt liquid-applied membrane	
Color	Black	
Solids	68% ± 3% [percent by weight]	
Density	8.2 lbs/gal ± 0.25	
Application Temperature	Minimum 20°F ¹	
Application Thickness	60 mils (wet) ² standard warranty on cracks up to 1/16" wide; 90 mils (wet) for warranty on cracks up to 1/8" wide ¹	
Crack Bridging Ability	Results: Passes	Method: ICC-ES AC29, Sec 3.1
Water Vapor Permeance	Results: <1 perm for 40-mil dry coating [grains/sf/hr]	Method: ASTM E-96 Wet Method
Elongation	Results: >700%	Method: ASTM D-412
Adhesion to Concrete	Results: Exceeds	Method: ASTM C-836
Resistance to Degradation in Soil	Results: Good	Method: ASTM E-154
Mold Growth and Bacterial Attack	Results: No degradation	Method: ASTM D-3273, ASTM D-3274

¹ Measured in-place with ASTM D-4414 notch film gauge. Wet 60 mils on notch film gauge. 60 mil wet membrane cures (dries) to 40 mils; 90 mil wet membrane cures (dries) to 60 mils.

For more details on WATCHDOG Quick Cure 90 contact your local Tremco Contractor or visit tremcosealants.com

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.



Tremco® and WATCHDOG Waterproofing® are registered trademarks of Tremco Incorporated. Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.

1120/WDWQC90

tremcocpg.com