

SAFETY DATA SHEET

1. Identification

Material name: Vulkem® 350 R
Material: 450712 805

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants
3735 Green Road
Beachwood OH 44122
US

Contact person:	EH&S Department
Telephone:	216-292-5000
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids	Category 3
-------------------	------------

Health Hazards

Skin Corrosion/Irritation	Category 2
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A
Toxic to reproduction	Category 1B

Unknown toxicity - Health

Acute toxicity, oral	12.57 %
Acute toxicity, dermal	22.68 %
Acute toxicity, inhalation, vapor	99.99 %
Acute toxicity, inhalation, dust or mist	99.82 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3
--	------------

Unknown toxicity - Environment

Acute hazards to the aquatic environment	83.78 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.
Causes skin irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
May damage fertility or the unborn child.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use... to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aromatic petroleum distillates	64742-95-6	10 - 30%
Clay	1332-58-7	10 - 30%
Calcium Carbonate (Limestone)	1317-65-3	10 - 30%
1,2,4-Trimethylbenzene	95-63-6	7 - 13%
Titanium dioxide	13463-67-7	3 - 7%
1,3,5-Trimethylbenzene	108-67-8	1 - 5%
Trimethyl benzene (mixed isomers)	25551-13-7	1 - 5%
1,2,3-Trimethylbenzene	526-73-8	0.5 - 1.5%
Xylene	1330-20-7	0.5 - 1.5%
Cumene	98-82-8	0.1 - 1%
Magnesite	546-93-0	0.1 - 1%
Amorphous silica	7631-86-9	0.1 - 1%
Polymethylene polyphenyl isocyanate	9016-87-9	0.1 - 1%
Butyl benzyl phthalate	85-68-7	0.1 - 1%
Aluminum hydroxide	21645-51-2	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%
2,4-Toluene diisocyanate	584-84-9	0.1 - 1%
4,4'-Methylene bis(phenylisocyanate)	101-68-8	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:

Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation:

Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact:

Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Wash hands thoroughly after handling. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Clay - Respirable fraction.	TWA	2 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Clay - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Clay - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Clay - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2,4-Trimethylbenzene	REL	25 ppm 125 mg/m ³	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	25 ppm 125 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	25 ppm 125 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL	25 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)

	ST ESL	140 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	125 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	TWA PEL	25 ppm 125 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
1,3,5-Trimethylbenzene	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
Trimethyl benzene (mixed isomers)	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
1,2,3-Trimethylbenzene	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL	180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm 435 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 435 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cumene	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	50 ppm 245 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Amorphous silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum hydroxide - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum hydroxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m ³	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m ³	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m ³	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
	OSHA_ACT	0.025 mg/m ³	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		of air	
	TWA	0.1 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
2,4-Toluene diisocyanate - Inhalable fraction and vapor.	STEL	0.005 ppm	US. ACGIH Threshold Limit Values (03 2016)
	TWA	0.001 ppm	US. ACGIH Threshold Limit Values (03 2016)
2,4-Toluene diisocyanate	Ceiling	0.02 ppm 0.14 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm	US. ACGIH Threshold Limit Values (2011)
	Ceiling	0.02 ppm 0.2 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Clay - Respirable.	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Clay - Respirable dust.	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Clay - Respirable fraction.	TWA	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017)
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA		3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA		10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA		10 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA		3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA		10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA		10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm	123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Trimethyl benzene (mixed isomers)	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Trimethyl benzene (mixed isomers)	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Trimethyl benzene (mixed isomers)	TWA	25 ppm	123 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm	434 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm	651 mg/m ³	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Xylene	STEL	150 ppm	651 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm	434 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Cumene	STEL	75 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm	246 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.025 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA		0.10 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA		0.1 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2,4-Toluene diisocyanate	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2,4-Toluene diisocyanate	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
2,4-Toluene diisocyanate	TWA	0.005 ppm	0.036 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	0.02 ppm	0.14 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
4,4'-Methylene bis(phenylisocyanate)	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm 0.051 mg/m ³	Biological or Chemical Agents) (06 2015) Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
--------------------------------------	-----	-----------------------------------	--

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
2,4-Toluene diisocyanate (Toluene diamine (sum of 2,4- and 2,6-isomers), with hydrolysis: Sampling time: End of shift.)	5 µg/g (Creatinine in urine)	ACGIH BEI (03 2018)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Gray
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	48 °C 118 °F(Setaflash Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.177
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects**Acute toxicity (list all possible routes of exposure)**

Oral	
Product:	ATEmix: 31,803.36 mg/kg
Dermal	
Product:	ATEmix: 25,314.61 mg/kg
Inhalation	
Product:	Not classified for acute toxicity based on available data.

Specified substance(s):

Clay	LC 50 (Rat): > 20 mg/l
1,2,4-Trimethylbenzene	LC 50 (Rat): 10,200 mg/m3
Titanium dioxide	LC 50 (Rat): 3.43 mg/l
1,3,5-Trimethylbenzene	LC 50 (Rat): 10,200 mg/m3
Amorphous silica	LC 50 (Rat): > 2.08 mg/l
Aluminum hydroxide	LC 50 (Rat): 7.6 mg/l
Aluminum oxide	LC 50 (Rat): 7.6 mg/l
2,4-Toluene diisocyanate	LC 50 (Rat): 14 mg/l

Repeated dose toxicity**Product:** No data available.**Skin Corrosion/Irritation****Product:** No data available.**Specified substance(s):**

Aromatic petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
1,2,4-Trimethylbenzene	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
1,3,5-Trimethylbenzene	in vivo (Rabbit): Irritating Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Cumene	in vivo (Rabbit): Not irritant Experimental result, Key study
Magnesite	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Key study
Amorphous silica	in vivo (Rabbit): Not irritant Experimental result, Key study
Butyl benzyl phthalate	in vivo (Rabbit): Not irritant Experimental result, Key study
Aluminum hydroxide	in vivo (Rabbit): Not classified as an Irritant Experimental result, Key study
Aluminum oxide	in vivo (Rabbit): Not irritant Experimental result, Key study
2,4-Toluene diisocyanate	in vivo (Rabbit): Moderately irritating Experimental result, Supporting study
4,4'-Methylene bis(phenylisocyanate)	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Aromatic petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
1,2,4-Trimethylbenzene	Rabbit, 30 min: Not irritating
Titanium dioxide	Rabbit, 24 hrs: Not irritating
1,3,5-Trimethylbenzene	Rabbit, 30 min: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Cumene	Rabbit, 24 hrs: Not irritating
Magnesite	Reconstituted Corneal Epithelium model, 10 min: Not irritating

Amorphous silica	Rabbit, 24 hrs: Not irritating
Butyl benzyl phthalate	Rabbit, 24 - 72 hrs: Not irritating
Aluminum hydroxide	Rabbit, 24 hrs: Not irritating
Aluminum oxide	Rabbit, 24 hrs: Not irritating
2,4-Toluene diisocyanate	Rabbit, 24 - 72 hrs: Category 2

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Cumene	Overall evaluation: Possibly carcinogenic to humans.
Crystalline Silica (Quartz)/ Silica Sand	Overall evaluation: Carcinogenic to humans.
2,4-Toluene diisocyanate	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Cumene	Reasonably Anticipated to be a Human Carcinogen.
Crystalline Silica (Quartz)/ Silica Sand	Known To Be Human Carcinogen.
2,4-Toluene diisocyanate	Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product: No data available.

In vivo Product: No data available.

Reproductive toxicity

Product: May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.
Specified substance(s):
 Cumene Inhalation - vapor: Category 3 with respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Cumene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 6.04 - 6.61 mg/l Mortality
Butyl benzyl phthalate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 1.39 - 3.88 mg/l Mortality
2,4-Toluene diisocyanate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 108.8 - 240.4 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Trimethyl benzene (mixed isomers)	LC 50 (Daggerblade grass shrimp (Palaemonetes pugio), 24 h): 7 mg/l Mortality
Cumene	LC 50 (Water flea (Daphnia magna), 48 h): 7.9 - 45.1 mg/l Mortality

Butyl benzyl phthalate EC 50 (Water flea (Daphnia magna), 48 h): > 10 mg/l Intoxication
 EC 50 (Opossum shrimp (Americamysis bahia), 48 h): > 0.9 mg/l Mortality
 EC 50 (Water flea (Daphnia magna), 24 h): > 10 mg/l Intoxication
 EC 50 (Water flea (Daphnia magna), 21 d): > 0.76 mg/l Intoxication
 EC 50 (Water flea (Daphnia magna), 14 d): > 0.76 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Butyl benzyl phthalate NOAEL (Pimephales promelas, 126 d): 64.6 - 67.5 µg/l Experimental result, Key study
 NOAEL (Oncorhynchus mykiss, 124 d): 0.2 mg/l Experimental result, Key study
 LOAEL (Pimephales promelas, 126 d): 18.1 µg/l Experimental result, Key study
 LC 50 (Pimephales promelas, 4 d): 2.32 mg/l Experimental result, Supporting study
 LC 50 (Pimephales promelas, 14 d): 2.25 mg/l Experimental result, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Butyl benzyl phthalate Bluegill (Lepomis macrochirus), Bioconcentration Factor (BCF): 772 (Flow through)

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Xylene Log Kow: 3.12 - 3.20

Cumene Log Kow: 3.66
Butyl benzyl phthalate Log Kow: 4.91

Mobility in soil: No data available.
Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

UN1263, PAINT, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity

2,4-Toluene diisocyanate

Reportable quantity

De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Cumene	5000 lbs.
Butyl benzyl phthalate	100 lbs.
2,4-Toluene diisocyanate	100 lbs.
4,4'-Methylene bis(phenylisocyanate)	5000 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Toluene	1000 lbs.
Benzene	10 lbs.
Naphthalene	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
2,4-Toluene diisocyanate	100 lbs.	500 lbs.
Toluene-2,6-Diisocyanate	100 lbs.	100 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Cumene	5000 lbs.
Polymethylene polyphenyl isocyanate	
Butyl benzyl phthalate	100 lbs.
2,4-Toluene diisocyanate	100 lbs.
4,4'-Methylene bis(phenylisocyanate)	5000 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Toluene	1000 lbs.
Benzene	10 lbs.
Naphthalene	100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
2,4-Toluene diisocyanate	500lbs
Toluene-2,6-Diisocyanate	100lbs
Aromatic petroleum distillates	10000 lbs
Clay	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
1,2,4-Trimethylbenzene	10000 lbs
Titanium dioxide	10000 lbs
1,3,5-Trimethylbenzene	10000 lbs
Trimethyl benzene (mixed isomers)	10000 lbs
1,2,3-Trimethylbenzene	10000 lbs
Xylene	10000 lbs
Cumene	10000 lbs
Magnesite	10000 lbs
Amorphous silica	10000 lbs
Polymethylene polyphenyl isocyanate	10000 lbs
Butyl benzyl phthalate	10000 lbs
Aluminum hydroxide	10000 lbs
Aluminum oxide	10000 lbs
Crystalline Silica (Quartz)/ Silica Sand	10000 lbs
4,4'-Methylene bis(phenylisocyanate)	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
1,2,4-Trimethylbenzene
2,4-Toluene diisocyanate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	lbs
Toluene-2,6-Diisocyanate	lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Clay
Calcium Carbonate (Limestone)
1,2,4-Trimethylbenzene
Titanium dioxide
1,3,5-Trimethylbenzene
Trimethyl benzene (mixed isomers)
Butyl benzyl phthalate
Crystalline Silica (Quartz)/ Silica Sand
2,4-Toluene diisocyanate

US. Massachusetts RTK - Substance List**Chemical Identity**

Clay
Calcium Carbonate (Limestone)
1,2,4-Trimethylbenzene
Titanium dioxide
1,3,5-Trimethylbenzene
Trimethyl benzene (mixed isomers)
Crystalline Silica (Quartz)/ Silica Sand
2,4-Toluene diisocyanate
Toluene-2,6-Diisocyanate
Benzene

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Clay
Calcium Carbonate (Limestone)
1,2,4-Trimethylbenzene
Titanium dioxide
1,3,5-Trimethylbenzene
Trimethyl benzene (mixed isomers)
2,4-Toluene diisocyanate

US. Rhode Island RTK**Chemical Identity**

Clay
Calcium Carbonate (Limestone)
1,2,4-Trimethylbenzene
Titanium dioxide
1,3,5-Trimethylbenzene
Trimethyl benzene (mixed isomers)

International regulations**Montreal protocol**

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol
Not applicable

VOC:
Regulatory VOC (less water and
exempt solvent) : 334 g/l
VOC Method 310 : 28.33 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision**Revision Date:** 02/05/2019**Version #:** 2.1**Further Information:** No data available.**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

