SAFETY DATA SHEET

1. Identification

Material name: EXOAIR LEF GUN GRADE FOAM SEALANT
Material: 584007GG700

Recommended use and restriction on use

Recommended use: Sealant
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information
Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol	Category 1

Health Hazards

Acute toxicity (Oral)	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A

Unknown toxicity - Health

Acute toxicity, oral	66.9 %
Acute toxicity, dermal	66.9 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	85 %

Label Elements

Hazard Symbol:

Signal Word: Danger

Hazard Statement:
Extremely flammable aerosol.
Pressurized container: May burst if heated.
Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
May be harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause genetic defects.
May cause cancer.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*

2-Propanol, 1-chloro-, phosphate (3:1)	13674-84-5	10 - <25%
Methyl ether (Dimethyl ether)	115-10-6	10 - <20%
Isobutane	75-28-5	5 - <10%
Propane	74-98-6	1 - <5%
Butane	106-97-8	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Stop the flow of material, if this is without risk. Absorb with sand or other inert absorbent.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not taste or swallow. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Isobutane	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)
Propane	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Butane	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)

Chemical name	Type	Exposure Limit Values	Source
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation

			296/97, as amended) (07 2007)
Methyl ether (Dimethyl ether)	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isobutane	STEL	1,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017)
Propane	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Propane	TWA	1,000 ppm 1,800 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Chemical name	Type	Exposure Limit Values	Source
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl ether (Dimethyl ether)	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isobutane	STEL	1,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017)
Propane	TWA	1,000 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Propane	TWA	1,000 ppm 1,800 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Butane	TWA	800 ppm 1,900 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Butane	TWA	600 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
	STEL	750 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2017)
Butane	STEL	1,000 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (08 2017)

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Do not eat, drink or smoke when using the product. Wash hands after handling. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state:	Aerosols
Form:	Aerosols
Color:	Green
Odor:	Strong petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	-11 °C 12 °F
Flash Point:	-97 °C -143 °F
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	Extremely flammable aerosol.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and

	in the bottom of containers.
Relative density:	0.97
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. Causes skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	ATEmix: 1,394.61 mg/kg

Dermal

Product:	Not classified for acute toxicity based on available data.
Specified substance(s):	
2-Propanol, 1-chloro-, phosphate (3:1)	LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product:	Not classified for acute toxicity based on available data.
Specified substance(s):	
2-Propanol, 1-chloro-, phosphate (3:1)	LC 50 (Rat): > 5 mg/l

Repeated dose toxicity

Product:	No data available.

Skin Corrosion/Irritation

Product:	No data available.
Specified substance(s):	
2-Propanol, 1-chloro-, phosphate (3:1)	in vivo (Rabbit): Slightly irritating Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product:	No data available.
Specified substance(s):	
2-Propanol, 1-chloro-, phosphate (3:1)	Rabbit, 24 hrs: Not irritating
Propane	Irritating

Respiratory or Skin Sensitization

Product:	No data available.

Carcinogenicity

Product:	No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:
No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Methyl ether (Dimethyl ether)	Log Kow: 0.10
Isobutane	Log Kow: 2.76
Propane	Log Kow: 2.36
Butane	Log Kow: 2.89

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN1950, AEROSOLS, 2.1

CFR / DOT:

UN1950, Aerosols, 2.1

IMDG:

UN1950, AEROSOLS, 2.1

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Methyl ether (Dimethyl ether)	100 lbs.
Isobutane	100 lbs.
Propane	100 lbs.
Butane	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard
Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route or exposure)
Skin Corrosion or Irritation
Serious eye damage or eye irritation
Germ Cell Mutagenicity
Carcinogenicity

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl ether (Dimethyl ether)	100 lbs.
Isobutane	100 lbs.
Propane	100 lbs.
Butane	100 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
2-Propanol, 1-chloro-, phosphate (3:1)	10000 lbs
Methyl ether (Dimethyl ether)	10000 lbs
Isobutane	10000 lbs
Propane	10000 lbs
Butane	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity
Polymethylene polyphenyl isocyanate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity	Reportable quantity
Methyl ether (Dimethyl ether)	lbs
Isobutane	lbs
Propane	lbs
Butane	lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Polymethylene polyphenyl isocyanate
Methyl ether (Dimethyl ether)
Isobutane
Propane

US. Massachusetts RTK - Substance List

Chemical Identity
Methyl ether (Dimethyl ether)
Isobutane
Propane

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Methyl ether (Dimethyl ether)
Isobutane
Propane

US. Rhode Island RTK

Chemical Identity
Methyl ether (Dimethyl ether)
Propane

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	206 g/l
VOC Method 310	:	21.27 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	01/16/2019
Version #:	1.3
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.