

Revision Date: 08/12/2015

# **SAFETY DATA SHEET**

# 1. Identification

Material name: Vulkem® OC 810

Material: 810802 805

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122

US

**Contact person:** EH&S Department **Telephone:** 216-292-5000

**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

#### **Hazard Classification**

#### **Health Hazards**

Acute toxicity (Inhalation - dust and Category 4

mist)

Respiratory sensitizer Category 1
Skin sensitizer Category 1
Carcinogenicity Category 1A

**Unknown toxicity - Health** 

Acute toxicity, oral 3.52 %
Acute toxicity, dermal 27.38 %
Acute toxicity, inhalation, vapor 99.73 %
Acute toxicity, inhalation, dust or mist 82.41 %

**Environmental Hazards** 

Acute hazards to the aquatic Category 1

environment

**Unknown toxicity - Environment** 

Acute hazards to the aquatic 86.17 %

environment

Chronic hazards to the aquatic 100 %

environment

#### **Label Elements**

### **Hazard Symbol:**



Revision Date: 08/12/2015



Signal Word: Danger

**Hazard Statement:** Harmful if inhaled.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer. Very toxic to aquatic life.

Precautionary Statement: Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a

well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective

equipment as required. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. If experiencing respiratory symptoms: Call a POISON

CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see this label). Wash contaminated

clothing before reuse. Collect spillage.

Storage: Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

# 3. Composition/information on ingredients

# Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Aluminum hydroxide	21645-51-2	7 - 13%
Calcium carbonate	471-34-1	7 - 13%
Polyvinyl chloride	9002-86-2	1 - 5%
Isophorone Diisocyanate	4098-71-9	1 - 5%
Zinc oxide	1314-13-2	1 - 5%
Calcium oxide	1305-78-8	1 - 5%
Carbon Black	1333-86-4	1 - 5%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%
Stearic acid	57-11-4	0.1 - 1%



Revision Date: 08/12/2015

Hydrotreated heavy	64742-52-5	0.1 - 1%
naphthenic distillate		

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

Ingestion: Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

**Inhalation:** Call a physician or poison control center immediately. If breathing stops,

provide artificial respiration. Move to fresh air. If breathing is difficult, give

oxygen.

**Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly

clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an

allergic skin reaction develops, get medical attention.

**Eye contact:** Any material that contacts the eye should be washed out immediately with

water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

## 6. Accidental release measures



Revision Date: 08/12/2015

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** 

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** 

Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

# 7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities:

Store locked up.

# 8. Exposure controls/personal protection

## **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	type	Exposure Limi	it Values	Source
Aluminum hydroxide - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Calcium carbonate - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001- 1050) (02 2006)
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001- 1050) (02 2006)
	OSHA_A CT	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001- 1050) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)





			(02 2006)
Polyvinyl chloride -	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
Total dust.			Contaminants (29 CFR 1910.1000)
			(02 2006)
	T) A / A	50 millions	US. OSHA Table Z-3 (29 CFR
	TWA	of particles	1910.1000) (2000)
			1910.1000) (2000)
		per cubic	
		foot of air	
Polyvinyl chloride -	TWA	15 millions	US. OSHA Table Z-3 (29 CFR
Respirable fraction.		of particles	1910.1000) (2000)
		per cubic	
		foot of air	
Polyvinyl chloride -	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR
Total dust.		10g,	1910.1000) (2000)
Polyvinyl chloride -	TWA	5 mg/m2	US. OSHA Table Z-3 (29 CFR
	IVVA	5 mg/m3	
Respirable fraction.			1910.1000) (2000)
Isophorone	TWA	0.005 ppm	US. ACGIH Threshold Limit Values
Diisocyanate			(2011)
Zinc oxide - Respirable	TWA	2 mg/m3	US. ACGIH Threshold Limit Values
fraction.			(2011)
	STEL	10 mg/m3	US. ACGIH Threshold Limit Values
	SIEL	10 1119/1110	(2011)
Zinc oxide - Fume.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
Zinc oxide - Fume.	PEL	5 mg/ms	
			Contaminants (29 CFR 1910.1000)
			(02 2006)
Zinc oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000)
			(02 2006)
Zinc oxide - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.			Contaminants (29 CFR 1910.1000)
ao			(02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values
Calcium oxide	IVVA	2 mg/ms	
	-	_ , -	(2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000)
			(02 2006)
Carbon Black -	TWA	3 mg/m3	US. ACGIH Threshold Limit Values
Inhalable fraction.		]	(2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air
Jai Doil Diaok	'	3.5 mg/m3	Contaminants (29 CFR 1910.1000)
D2 (16 22	OTE:		(02 2006)
•	STEL	0.2 mg/m3	(02 2006) US. ACGIH Threshold Limit Values
Dibutyl tin dilaurate - as Sn	STEL		(02 2006) US. ACGIH Threshold Limit Values (2011)
•	STEL	0.2 mg/m3 0.1 mg/m3	(02 2006) US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values
•			(02 2006) US. ACGIH Threshold Limit Values (2011)
•	TWA	0.1 mg/m3	(02 2006) US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values
•			US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air
•	TWA	0.1 mg/m3	(02 2006) US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Sn	TWA PEL	0.1 mg/m3 0.1 mg/m3	US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
•	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. ACGIH Threshold Limit Values
Stearic acid	TWA PEL TWA	0.1 mg/m3 0.1 mg/m3 10 mg/m3	US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. ACGIH Threshold Limit Values (2011)
Stearic acid Hydrotreated heavy	TWA PEL	0.1 mg/m3 0.1 mg/m3	US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values
Sn Stearic acid	TWA PEL TWA	0.1 mg/m3 0.1 mg/m3 10 mg/m3	US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. ACGIH Threshold Limit Values (2011)
Stearic acid  Hydrotreated heavy naphthenic distillate -	TWA PEL TWA	0.1 mg/m3 0.1 mg/m3 10 mg/m3	US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values
Stearic acid  Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA PEL TWA TWA	0.1 mg/m3 0.1 mg/m3 10 mg/m3 5 mg/m3	US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011)
Stearic acid  Hydrotreated heavy naphthenic distillate -	TWA PEL TWA	0.1 mg/m3 0.1 mg/m3 10 mg/m3	US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values (2011) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. ACGIH Threshold Limit Values (2011) US. ACGIH Threshold Limit Values



Hydrotreated heavy	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
naphthenic distillate -			Contaminants (29 CFR 1910.1000)
Mist.			(02 2006)

Chemical name	type	Exposure Lin	nit Values	Source
Aluminum hydroxide - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum hydroxide - Respirable fraction.	TWAEV		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium carbonate - Total dust.	STEL		20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Diisodecyl phthalate	TWAEV		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Respirable.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWAEV		1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Isophorone Diisocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational



Isophorone	TWAEV	0.005 ppm		Health and Safety Regulation 296/97, as amended) (07 2007)  Canada. Ontario OELs. (Control of
Diisocyanate	TVV/\LV	0.000 ppiii		Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Isophorone Diisocyanate	TWA	0.005 ppm	0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Respirable.	TWA		2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zinc oxide - Respirable fraction.	TWAEV		2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Zinc oxide - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zinc oxide - Fume.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Revision Date: 08/12/2015

Hydrotreated heavy naphthenic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

**Appropriate Engineering** 

Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

### Individual protection measures, such as personal protective equipment

**General information:** Use personal protective equipment as required.

**Eye/face protection:** Wear goggles/face shield.

**Skin Protection** 

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations below

recommended exposure limits (where applicable) or to an acceptable level

(in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter,

cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace. Avoid contact with skin.

# 9. Physical and chemical properties

### **Appearance**

Physical state:liquidForm:liquidColor:Black

Odor:

Odor threshold:

PH:

No data available.

Flash Point: > 100 °C > 212 °F(Setaflash Closed Cup)

**Evaporation rate:** Slower than Ether

Flammability (solid, gas): No
Upper/lower limit on flammability or explosive limits



Revision Date: 08/12/2015

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.29

Solubility(ies)

Solubility in water:
Solubility (other):
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
No data available.
Viscosity:
No data available.
No data available.

# 10. Stability and reactivity

Reactivity: No data available.

**Chemical Stability:** Material is stable under normal conditions.

**Possibility of Hazardous** 

Reactions:

No data available.

**Conditions to Avoid:** Avoid heat or contamination.

**Incompatible Materials:** Alcohols. Amines. Strong acids. Strong bases. Water, moisture.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

### Information on likely routes of exposure

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

**Inhalation:** In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** Causes mild skin irritation. May cause an allergic skin reaction.

**Eye contact:** Eye contact is possible and should be avoided.

# Information on toxicological effects

## Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix: 39,973.35 mg/kg

**Dermal** 



Revision Date: 08/12/2015

**Product:** ATEmix: 12,114.95 mg/kg

Inhalation

**Product:** ATEmix: 2.62 mg/l

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Specified substance(s):

Aluminum hydroxide in vivo (Rabbit, 24 hrs): Not irritating

Calcium carbonate in vivo (Rabbit, 24 - 72 hrs): Not irritating

Isophorone in vivo (Rabbit, 24 - 72 hrs): Category 1

Diisocyanate

Zinc oxide in vivo (Rabbit, 24 - 72 hrs): Not irritating

Calcium oxide in vivo (Rabbit, 24 hrs): Category 1

Carbon Black in vivo (Rabbit, 24 - 72 hrs): Not irritating

Dibutyl tin dilaurate in vivo (Rabbit, 24 hrs): Highly irritating

Stearic acid in vivo (Rabbit, 27 - 72 hrs): Not irritating

Hydrotreated heavy

naphthenic distillate

in vivo (Rabbit, 24 hrs): Not irritating

Respiratory or Skin Sensitization

**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity

**Product:** No data available.



Revision Date: 08/12/2015

# IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Carbon Black Overall evaluation: Possibly carcinogenic to humans.

Hydrotreated heavy Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

naphthenic distillate evaluation: Carcinogenic to humans.

# **US. National Toxicology Program (NTP) Report on Carcinogens:**

Hydrotreated heavy Known To Be Human Carcinogen.

naphthenic distillate

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

Polyvinyl chloride

Cancer

### **Germ Cell Mutagenicity**

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

# 12. Ecological information

### **Ecotoxicity:**

# Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Calcium carbonate LC 50 (Western mosquitofish (Gambusia affinis), 96 h): > 56,000 mg/l



Revision Date: 08/12/2015

Mortality

Zinc oxide LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2,246 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

Zinc oxide LC 50 (Water flea (Daphnia magna), 48 h): 24.6 mg/l Mortality

Dibutyl tin dilaurate EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Aluminum hydroxide LOAEL (Pimephales promelas, 28 d): 53.8 mg/l experimental result

Zinc oxide NOAEL (Oncorhynchus mykiss, 30 d): 974 µg/l interpreted

Calcium oxide NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Carbon Black NOAEL (Salmo sp., 30 d): 17 mg/l QSAR

Hydrotreated heavy naphthenic distillate

NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates** 

**Product:** No data available.

**Toxicity to Aquatic Plants** 

**Product:** No data available.

Persistence and Degradability

**Biodegradation** 

**Product:** No data available.

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative Potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):



Revision Date: 08/12/2015

Dibutyl tin dilaurate Log Kow: 3.12

Stearic acid Log Kow: 8.23

Mobility in Soil: No data available.

Other Adverse Effects: Very toxic to aquatic organisms.

# 13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

**Contaminated Packaging:** No data available.

# 14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

# 15. Regulatory information

### **US Federal Regulations**

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u> <u>OSHA hazard(s)</u>

Polyvinyl chloride Blood Liver

Cancer Flammability

Central nervous system



Revision Date: 08/12/2015

# CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

bis (2-chloro- 1000 lbs.

1methylethyl) ether

Propylene oxide 100 lbs.
Propionic acid 5000 lbs.
Ethylbenzene 1000 lbs.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

# **Hazard categories**

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

# SARA 302 Extremely Hazardous Substance

Reportable

Chemical Identity quantity

Threshold Planning Quantity

500 lbs

Isophorone Diisocyanate 500 lbs. 500 lbs. Propylene oxide 100 lbs. 10000 lbs.

### SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

Diisodecyl phthalate Isophorone Diisocyanate

Zinc oxide

bis (2-chloro- 1000 lbs.

1methylethyl) ether

Propylene oxide 100 lbs.
Propionic acid 5000 lbs.
Ethylbenzene 1000 lbs.

#### SARA 311/312 Hazardous Chemical

Chemical Identity Threshold Planning Quantity

Isophorone Diisocyanate 500lbs Propylene oxide 500lbs Aluminum hydroxide 500 lbs Calcium carbonate 500 lbs Polyvinyl chloride 500 lbs Zinc oxide 500 lbs Calcium oxide 500 lbs Carbon Black 500 lbs Dibutyl tin dilaurate 500 lbs Stearic acid 500 lbs Hydrotreated heavy 500 lbs naphthenic distillate

# SARA 313 (TRI Reporting)

### **Chemical Identity**

Isophorone Diisocyanate

Zinc oxide

### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

<u>Chemical Identity</u> <u>Reportable quantity</u>



Revision Date: 08/12/2015

Propylene oxide 10000 lbs

# **US State Regulations**

### **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

### US. New Jersey Worker and Community Right-to-Know Act

## **Chemical Identity**

Calcium carbonate Polyvinyl chloride Isophorone Diisocyanate Zinc oxide Calcium oxide Carbon Black

# US. Massachusetts RTK - Substance List

## **Chemical Identity**

Calcium carbonate Isophorone Diisocyanate Zinc oxide Calcium oxide Carbon Black Propylene oxide Crystalline Silica (Quartz)/ Silica Sand

# US. Pennsylvania RTK - Hazardous Substances

# **Chemical Identity**

Calcium carbonate Diisodecyl phthalate Isophorone Diisocyanate Zinc oxide Calcium oxide Carbon Black

#### US. Rhode Island RTK

# **Chemical Identity**

Diisodecyl phthalate Isophorone Diisocyanate Zinc oxide

### Other Regulations:

Regulatory VOC (less water 29 g/l and exempt solvent):

VOC Method 310: 2.02 %

# **Inventory Status:**

Australia AICS: One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List: One or more components in this product are

not listed on or exempt from the Inventory.



Revision Date: 08/12/2015

EINECS, ELINCS or NLP: One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List: One or more components in this product are

not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are

not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this product are

not listed on or exempt from the Inventory.

Canada NDSL Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

Philippines PICCS: One or more components in this product are

not listed on or exempt from the Inventory.

US TSCA Inventory: One or more components in this product are

not listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan ISHL Listing: One or more components in this product are

not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are

not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

**Revision Date:** 08/12/2015

Version #: 1.0

Further Information: No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.