SAFETY DATA SHEET

1. Identification

Material name: IMPAX™ WB+
Material: TBS332

Recommended use and restriction on use

Recommended use: Coatings
Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information
Tremco Canadian Sealants
220 Wicksteed Ave
Toronto ON M4H 1G7
CA

Contact person:	EH&S Department
Telephone:	1-800-263-6046
Emergency telephone number:	1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin sensitizer	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B

Unknown toxicity - Health

Acute toxicity, oral	35.53 %
Acute toxicity, dermal	35.69 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	100 %

Environmental Hazards

Acute hazards to the aquatic environment	Category 3

Unknown toxicity - Environment

Acute hazards to the aquatic environment	99.71 %
Chronic hazards to the aquatic environment	100 %

Label Elements

Hazard Symbol:

Signal Word: Danger

Hazard Statement: May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
Harmful to aquatic life.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	40 - 70%
Stoddard solvent (Mineral Spirits)	8052-41-3	1 - 5%
Wood rosin	8050-09-7	0.5 - 1.5%
Sodium hydroxide	1310-73-2	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air.

Skin Contact: Get medical attention if symptoms occur. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Eye contact: Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (2011)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	500 ppm 2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Sodium hydroxide	Ceiling	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Stoddard solvent (Mineral Spirits)	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Black
Odor: Slight odor
Odor threshold: No data available.
pH: 10 - 12
Melting point/freezing point: No data available.
Initial boiling point and boiling range: 100 °C 212 °F
Flash Point: > 93 °C > 200 °F(Setaflash Closed Cup)
Evaporation rate: Slower than Ether
Flammability (solid, gas): No
Upper/lower limit on flammability or explosive limits
Flammability limit - upper (%): No data available.

Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	0.99
Solubility(ies)	
Solubility in water:	Dispersible
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May be harmful in contact with skin. May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Asphalt	LD 50 (Rat): > 5,000 mg/kg
Wood rosin	LD 50 (Rat): 2,800 mg/kg
Sodium hydroxide	LD 50 (Rabbit): 325 mg/kg

Dermal

Product: ATEmix: 2,167.66 mg/kg

Inhalation

Product:

Specified substance(s):

Asphalt	LC 50 (Rat): > 94.4 mg/m3

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Asphalt	in vivo (Rabbit): Not irritant Experimental result, Key study
Wood rosin	in vivo (Rabbit): Not irritant Experimental result, Key study
Sodium hydroxide	in vivo (Rabbit): Irritating Experimental result, Weight of Evidence study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Asphalt	Rabbit, 24 hrs: Not irritating

Wood rosin	Rabbit, 24 hrs: Irritating
Sodium hydroxide	Rabbit, 1 d: 10% Sodium Hydroxide- Category 1; 0.5% Sodium Hydroxide- Slightly irritating to eyes

Respiratory or Skin Sensitization
Product: No data available.

Carcinogenicity
Product: May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Asphalt	Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:
No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):
No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Sodium hydroxide	LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 125 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
Sodium hydroxide	EC 50 (Water flea (Ceriodaphnia dubia), 48 h): 34.59 - 47.13 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Asphalt	NOAEL (Oncorhynchus mykiss, 28 d): >= 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study LL 50 (Oncorhynchus mykiss, 28 d): > 1,000 mg/l Read-across from supporting substance (structural analogue or surrogate), Key study

Aquatic Invertebrates

Product:	No data available.

Toxicity to Aquatic Plants

Product:	No data available.

Persistence and Degradability

Biodegradation

Product:	No data available.

BOD/COD Ratio

Product:	No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product:	No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.

Specified substance(s):

Stoddard solvent (Mineral Spirits)	Log Kow: 3.16 - 7.15

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Asphalt	100 lbs.
Sodium hydroxide	1000 lbs.
Hydrogen sulfide	100 lbs.
Ethyl Acrylate	1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard

SARA 302 Extremely Hazardous Substance

Chemical Identity	Reportable quantity	Threshold Planning Quantity
Hydrogen sulfide	100 lbs.	500 lbs.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Asphalt	100 lbs.
Sodium hydroxide	1000 lbs.
Hydrogen sulfide	100 lbs.
Ethyl Acrylate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Hydrogen sulfide	500lbs
Asphalt	10000 lbs
Stoddard solvent (Mineral Spirits)	10000 lbs
Wood rosin	10000 lbs
Sodium hydroxide	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity	Reportable quantity
Hydrogen sulfide	lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

WARNING
Cancer - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Asphalt
Stoddard solvent (Mineral Spirits)

US. Massachusetts RTK - Substance List

Chemical Identity
Asphalt
Stoddard solvent (Mineral Spirits)
Hydrogen sulfide
Ethyl Acrylate

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity
Asphalt
Stoddard solvent (Mineral Spirits)

US. Rhode Island RTK

Chemical Identity
Asphalt
Stoddard solvent (Mineral Spirits)

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and exempt solvent)	:	36 g/l
VOC Method 310	:	2.46 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	10/05/2018
Version #:	1.2
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.